

WINDOW LISTING PROGRAM

Class: Fenestration Products – Energy Performance

Customer: #0877658 B.C. Ltd. DBA Stilewood International Door & Window
Location: Port Coquitlam, BC

Listing No. W478
Project No. W478-1
Effective Date: May 4, 2011
Last Revised: May 4, 2011
Expires: N/A

Product: Wood windows

Label: Each product is marked with the following content on a permanent label that is readily visible after installation:

- Manufacturer’s Name, Trademark or other recognized symbol of identification
- QAI File number (W478)
- QAI logo with “c” indicator
- “Evaluation for energy performance in accordance with CSA A440.2-09”
 “Évalué pour la performance d’énergie en accord à la norme CSA A440.2-09”

Standard: CSA A440.2 “Fenestration Energy Performance”

Models: Wood Windows with glazing options as follows:

Wood Picture Window:

Model Code	Window U-Value (W/m ² ·K)	Energy Rating (ER)
WOODPIC-LE(4, e=0.036)-Arg(10)-Cl(4)	1.58	24
WOODPIC-LE(6, e=0.039)-Arg(12.7)-Cl(6)	1.52	26
WOODPIC- Cl(4) -Arg(10)- LE(4, e=0.215)	1.89	34
WOODPIC-LE(6, e=0.035)-Arg(12.7)-Cl(6)	1.51	26
WOODPIC-LE(6, e=0.018)-Arg(12.7)-Cl(6)	1.47	22

Wood Casement Window:

Model Code	Window U-Value (W/m ² ·K)	Energy Rating (ER)
WOODCAS-LE(4, e=0.036)-Arg(10)-Cl(4)	1.69	17
WOODCAS-LE(6, e=0.039)-Arg(12.7)-Cl(6)	1.64	18
WOODCAS- Cl(4) -Arg(10)- LE(4, e=0.215)	1.91	24
WOODCAS-LE(6, e=0.035)-Arg(12.7)-Cl(6)	1.64	18
WOODCAS-LE(6, e=0.018)-Arg(12.7)-Cl(6)	1.61	15

Wood Awning Window:

Model Code	Window U-Value (W/m ² ·K)	Energy Rating (ER)
WOODAWN-LE(4, e=0.036)-Arg(10)-Cl(4)	1.69	17
WOODAWN-LE(6, e=0.039)-Arg(12.7)-Cl(6)	1.64	18
WOODAWN- Cl(4) -Arg(10)- LE(4, e=0.215)	1.92	24
WOODAWN-LE(6, e=0.035)-Arg(12.7)-Cl(6)	1.64	18
WOODAWN-LE(6, e=0.018)-Arg(12.7)-Cl(6)	1.61	15

Wood Fixed Casement Window:

Model Code	Window U-Value (W/m ² ·K)	Energy Rating (ER)
WOODFIX-LE(4, e=0.036)-Arg(10)-Cl(4)	1.79	14
WOODFIX-LE(6, e=0.039)-Arg(12.7)-Cl(6)	1.81	15
WOODFIX- Cl(4) -Arg(10)- LE(4, e=0.215)	2.01	22
WOODFIX-LE(6, e=0.035)-Arg(12.7)-Cl(6)	1.81	16
WOODFIX-LE(6, e=0.018)-Arg(12.7)-Cl(6)	1.78	12

Note:

Windows are not intended for installation in storefronts, non-operable portions of curtain wall, fixed glazing cast into precast concrete panels, greenhouses, skylights or sloped glazing. Test procedures are designed to test the performance of the test specimen only and are not necessarily used to test the performance of the installation, particularly the perimeter sealant joint and anchoring of the assembly.
