

FIRE DOORS LISTING PROGRAM

Customer: Artsy Contracting Co. Ltd.
 Class: Fire Doors
 Location: Delta, BC
 Website: www.artsyco.com

Listing No. F445-1
 Project No. F445-1 Edition 1

Effective Date: June 16, 2017
 Last Revised Date: June 16, 2017

Standards: CAN/ULC-S104 *Standard Method for Fire Tests of Door Assemblies.*

Product: 20 min Rated Fire Doors

Labels: See [FD001 - Fire Door Labeling requirements](#)

Models: **20-MINUTE WOOD CORE PANEL DOORS:**

Minimum 44 mm (1-3/4") Thickness

Swing Type:	Maximum Dimensions		Panel Type:	Latching:
	Width:	Length:		
Single Swing	950 mm (3'0")	2750 mm (9'0")	Flush	Single Point (Mortised or Cylindrical)
	1250 mm (4'0")	2450 mm (8'0")		

Limitations: (Review Machining Report for further detail)

- Cylindrical Latches (Listed and Labelled)
- Mortise Lockset (Listed and Labelled)
 - Assa Abloy Hospitality AS – Vingcard Mortise Hardware
 - "VingCard Alu" or "Trio VingAccess Alu", Series 1050, 1060, 1070, 1080, 1090
 - 1000 Series; Models 1001, -02, -04, -07, -12, -14, -15, -57, -85 with 19.05 mm (3/4 in.) latch bolts; may include suffix letters -K, -KVC, -L or -LVC
 - "3000 DaVinci, Euro DaVinci and Presidio" battery operated units
 - "Signature Series, Euro, ANSI and US ANSI" battery operated units
 - "Allure Series, Euro, ANSI and US ANSI" battery operated units
 - "Essence Series, Euro, ANSI (DB) and US ANSI (DA)" battery operated units
- Deadbolts (Listed and Labelled)
- Viewers (Listed and Labelled)
- Surface Mounted Door Closer (Listed and Labelled)
- Glass Lights (Listed and Labelled)
 - Maximum area of exposed glass per door leaf is 0.064 m² (Max. width of 255 mm, Max. height of 635 mm).
- Surface Mounted Door Bottom (Listed and Labelled)
- Surface Mounted Protection Plates



Notes: *Refer to QAI evaluation report F445-1 and the applicable test reports for test assembly configurations used for fire endurance testing.*

Refer to the [QAI FD002 - Fire Door Guidelines for general guidelines of fire door assemblies](#)

Final acceptance of the product in the intended application is to be determined by the authority having jurisdiction (AHJ).

Product is to be installed in accordance with the manufacturer's published installation instructions by qualified installing personnel.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warrantee is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.
