



WINDOWS & DOORS LISTING PROGRAM

Customer: DD Builders Door Supply Ltd.
Class: Fenestration Products – Energy Performance
Location: Abbotsford, British Columbia
Website: www.woodwindows.ca

Listing No. W434-2
Project No. W434-2 ED3
Effective Date: August 11, 2017
Last Revised Date: July 27, 2023
Expires: N/A

Standards: CSA A440.2 “Fenestration Energy Performance”

Product: Wood Doors

Markings: Products are marked with the following content in a permanent manner where it is readily visible after installation:

- a) Manufacturer’s name, Trademark or other recognized symbol or identification.
- b) QAI file Number: W434
- c) QAI logo shown here:



- d) “Evaluation for energy performance in accordance with CSA A440.2” / “Évalué pour la performance d’énergie en accord à la norme CSA A440.2”

Models / Ratings:

Wood Lift and Slide Door

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	BDW-WLSD-5,SB60(2)-5,CL-19AR90SS	1.60	0.25	19
G02	BDW-WLSD-5,SB60(2)-5,CL-19AR90SS-G2>1	1.62	0.21	16
G03	BDW-WLSD-5,SB60(2)-5,CL-19AR90SS-T1>1	1.79	0.19	12
G04	BDW-WLSD-5,SB60(2)-5,CL-19AR90SS-T2>1	1.78	0.17	11
G05	BDW-WLSD-5,SB60(2)-5,ENAD(4)-19AR90SS	1.40	0.24	23



Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G06	BDW-WLSD-5,SB60(2)-5,ENAD(4)-19AR90SS-G2>1	1.49	0.20	19
G07	BDW-WLSD-5,SB60(2)-5,ENAD(4)-19AR90SS-T1>1	1.67	0.18	14
G08	BDW-WLSD-5,SB60(2)-5,ENAD(4)-19AR90SS-T2>1	1.69	0.16	12
G09	BDW-WLSD-4,SB60(2)-4,CL-4,CL-11AR90SS	1.34	0.23	24
G10	BDW-WLSD-4,SB60(2)-4,CL-4,CL-11AR90SS-G2>1	1.41	0.19	20
G11	BDW-WLSD-4,SB60(2)-4,CL-4,CL-11AR90SS-T1>1	1.56	0.18	16
G12	BDW-WLSD-4,SB60(2)-4,CL-4,CL-11AR90SS-T2>1	1.57	0.16	15
G13	BDW-WLSD-4,SB60(2)-4,CL-4,ENAD(6)-11AR90SS	1.23	0.22	26
G14	BDW-WLSD-4,SB60(2)-4,CL-4,ENAD(6)-11AR90SS-G2>1	1.35	0.18	21
G15	BDW-WLSD-4,SB60(2)-4,CL-4,ENAD(6)-11AR90SS-T1>1	1.50	0.17	17
G16	BDW-WLSD-4,SB60(2)-4,CL-4,ENAD(6)-11AR90SS-T2>1	1.52	0.15	15

Wood Folding Door

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
1.75" Door Slab				
G01	BDW-WFD175-NOLITE	1.83	0.02	1
G02	BDW-WFD175-FULL-4,SB60(2)-4,CL-11AR90SS	1.76	0.17	11
G03	BDW-WFD175-FULL-4,SB60(2)-4,CL-11AR90SS-G2>1	1.78	0.16	10
G04	BDW-WFD175-FULL-4,SB60(2)-4,CL-11AR90SS-T1>1	1.99	0.13	4
G05	BDW-WFD175-FULL-4,SB60(2)-4,CL-11AR90SS-T2>1	1.97	0.13	4
G06	BDW-WFD175-FULL-4,SB60(2)-4,ENAD(4)-11AR90SS	1.64	0.17	14
G07	BDW-WFD175-FULL-4,SB60(2)-4,ENAD(4)-11AR90SS-G2>1	1.68	0.15	12
G08	BDW-WFD175-FULL-4,SB60(2)-4,ENAD(4)-11AR90SS-T1>1	2.04	0.12	2
G09	BDW-WFD175-FULL-4,SB60(2)-4,ENAD(4)-11AR90SS-T2>1	2.05	0.12	2
2.25" Door Slab				
G10	BDW-WFD225-NOLITE	1.53	0.01	7
G11	BDW-WFD225-FULL-4,SB60(2)-4,CL-4,CL-11AR90SS	1.42	0.16	18
G12	BDW-WFD225-FULL-4,SB60(2)-4,CL-4,CL-11AR90SS-G2>1	1.43	0.15	17
G13	BDW-WFD225-FULL-4,SB60(2)-4,CL-4,CL-11AR90SS-T1>1	1.57	0.12	13
G14	BDW-WFD225-FULL-4,SB60(2)-4,CL-4,CL-11AR90SS-T2>1	1.54	0.12	13
G15	BDW-WFD225-FULL-4,SB60(2)-4,CL-4,ENAD(6)-11AR90SS	1.36	0.15	19
G16	BDW-WFD225-FULL-4,SB60(2)-4,CL-4,ENAD(6)-11AR90SS-G2>1	1.37	0.14	18
G17	BDW-WFD225-FULL-4,SB60(2)-4,CL-4,ENAD(6)-11AR90SS-T1>1	1.64	0.11	10
G18	BDW-WFD225-FULL-4,SB60(2)-4,CL-4,ENAD(6)-11AR90SS-T2>1	1.65	0.11	10



Wood Inswing Door with Aluminum Sill

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
1.75" Door Slab				
G01	BDW-SHD-ISA45-4,SB60(2)-4,CL-11AR90SS	1.66	0.17	13
G02	BDW-SHD-ISA45-4,SB60(2)-4,CL-11AR90SS-G1<1	1.69	0.15	11
G03	BDW-SHD-ISA45-4,SB60(2)-4,CL-11AR90SS-T1>1	1.80	0.15	9
G04	BDW-SHD-ISA45-4,SB60(2)-4,CL-11AR90SS-T2>1	1.81	0.15	8
G05	BDW-SHD-ISA45-4,SB60(2)-4,ENAD(4)-11AR90SS	1.53	0.17	16
G06	BDW-SHD-ISA45-4,SB60(2)-4,ENAD(4)-11AR90SS-G1<1	1.57	0.14	13
G07	BDW-SHD-ISA45-4,SB60(2)-4,ENAD(4)-11AR90SS-T1>1	1.69	0.14	10
G08	BDW-SHD-ISA45-4,SB60(2)-4,ENAD(4)-11AR90SS-T2>1	1.70	0.14	10
2.25" Door Slab				
G09	BDW-SHD-ISA57-4,SB60(2)-4,CL-4,CL-11AR90SS	1.35	0.16	19
G10	BDW-SHD-ISA57-4,SB60(2)-4,CL-4,CL-11AR90SS-G2>1	1.36	0.13	17
G11	BDW-SHD-ISA57-4,SB60(2)-4,CL-4,CL-11AR90SS-T1>1	1.45	0.13	15
G12	BDW-SHD-ISA57-4,SB60(2)-4,CL-4,CL-11AR90SS-T2>1	1.46	0.13	15
G13	BDW-SHD-ISA57-4,SB60(2)-4,CL-4,ENAD(6)-11AR90SS	1.28	0.15	20
G14	BDW-SHD-ISA57-4,SB60(2)-4,CL-4,ENAD(6)-11AR90SS-G2>1	1.31	0.13	18
G15	BDW-SHD-ISA57-4,SB60(2)-4,CL-4,ENAD(6)-11AR90SS-T1>1	1.40	0.13	16
G16	BDW-SHD-ISA57-4,SB60(2)-4,CL-4,ENAD(6)-11AR90SS-T2>1	1.41	0.13	16

Wood Inswing Door with Wood Sill

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
1.75" Door Slab				
G01	BDW-SHD-ISW45-4,SB60(2)-4,CL-11AR90SS	1.66	0.17	N/A
G02	BDW-SHD-ISW45-4,SB60(2)-4,CL-11AR90SS-G1<1	1.69	0.15	N/A
G03	BDW-SHD-ISW45-4,SB60(2)-4,CL-11AR90SS-T1>1	1.80	0.15	N/A
G04	BDW-SHD-ISW45-4,SB60(2)-4,CL-11AR90SS-T2>1	1.81	0.15	N/A
G05	BDW-SHD-ISW45-4,SB60(2)-4,ENAD(4)-11AR90SS	1.53	0.17	N/A
G06	BDW-SHD-ISW45-4,SB60(2)-4,ENAD(4)-11AR90SS-G1<1	1.57	0.14	N/A
G07	BDW-SHD-ISW45-4,SB60(2)-4,ENAD(4)-11AR90SS-T1>1	1.69	0.14	N/A
G08	BDW-SHD-ISW45-4,SB60(2)-4,ENAD(4)-11AR90SS-T2>1	1.70	0.14	N/A
2.25" Door Slab				
G09	BDW-SHD-ISW57-4,SB60(2)-4,CL-4,CL-11AR90SS	1.35	0.16	N/A
G10	BDW-SHD-ISW57-4,SB60(2)-4,CL-4,CL-11AR90SS-G2>1	1.36	0.13	N/A
G11	BDW-SHD-ISW57-4,SB60(2)-4,CL-4,CL-11AR90SS-T1>1	1.45	0.13	N/A
G12	BDW-SHD-ISW57-4,SB60(2)-4,CL-4,CL-11AR90SS-T2>1	1.46	0.13	N/A
G13	BDW-SHD-ISW57-4,SB60(2)-4,CL-4,ENAD(6)-11AR90SS	1.28	0.15	N/A
G14	BDW-SHD-ISW57-4,SB60(2)-4,CL-4,ENAD(6)-11AR90SS-G2>1	1.31	0.13	N/A
G15	BDW-SHD-ISW57-4,SB60(2)-4,CL-4,ENAD(6)-11AR90SS-T1>1	1.40	0.13	N/A
G16	BDW-SHD-ISW57-4,SB60(2)-4,CL-4,ENAD(6)-11AR90SS-T2>1	1.41	0.13	N/A

**Wood Outswing Door with Aluminum Sill**

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
1.75" Door Slab				
G01	BDW-SHD-OSA45-4,SB60(2)-4,CL-11AR90SS	1.65	0.18	14
G02	BDW-SHD-OSA45-4,SB60(2)-4,CL-11AR90SS-G1<1	1.68	0.15	11
G03	BDW-SHD-OSA45-4,SB60(2)-4,CL-11AR90SS-T1>1	1.79	0.15	9
G04	BDW-SHD-OSA45-4,SB60(2)-4,CL-11AR90SS-T2>1	1.79	0.15	9
G05	BDW-SHD-OSA45-4,SB60(2)-4,ENAD(4)-11AR90SS	1.52	0.17	16
G06	BDW-SHD-OSA45-4,SB60(2)-4,ENAD(4)-11AR90SS-G1<1	1.56	0.14	14
G07	BDW-SHD-OSA45-4,SB60(2)-4,ENAD(4)-11AR90SS-T1>1	1.68	0.14	11
G08	BDW-SHD-OSA45-4,SB60(2)-4,ENAD(4)-11AR90SS-T2>1	1.69	0.14	11
2.25" Door Slab				
G09	BDW-SHD-OSA57-4,SB60(2)-4,CL-4,CL-11AR90SS	1.35	0.16	19
G10	BDW-SHD-OSA57-4,SB60(2)-4,CL-4,CL-11AR90SS-G2>1	1.36	0.13	17
G11	BDW-SHD-OSA57-4,SB60(2)-4,CL-4,CL-11AR90SS-T1>1	1.45	0.13	15
G12	BDW-SHD-OSA57-4,SB60(2)-4,CL-4,CL-11AR90SS-T2>1	1.45	0.13	15
G13	BDW-SHD-OSA57-4,SB60(2)-4,CL-4,ENAD(6)-11AR90SS	1.27	0.16	21
G14	BDW-SHD-OSA57-4,SB60(2)-4,CL-4,ENAD(6)-11AR90SS-G2>1	1.31	0.13	18
G15	BDW-SHD-OSA57-4,SB60(2)-4,CL-4,ENAD(6)-11AR90SS-T1>1	1.39	0.13	17
G16	BDW-SHD-OSA57-4,SB60(2)-4,CL-4,ENAD(6)-11AR90SS-T2>1	1.40	0.13	16

Wood Outswing Door with Wood Sill

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
1.75" Door Slab				
G01	BDW-SHD-OSW45-4,SB60(2)-4,CL-11AR90SS	1.65	0.18	N/A
G02	BDW-SHD-OSW45-4,SB60(2)-4,CL-11AR90SS-G1<1	1.68	0.15	N/A
G03	BDW-SHD-OSW45-4,SB60(2)-4,CL-11AR90SS-T1>1	1.79	0.15	N/A
G04	BDW-SHD-OSW45-4,SB60(2)-4,CL-11AR90SS-T2>1	1.79	0.15	N/A
G05	BDW-SHD-OSW45-4,SB60(2)-4,ENAD(4)-11AR90SS	1.52	0.17	N/A
G06	BDW-SHD-OSW45-4,SB60(2)-4,ENAD(4)-11AR90SS-G1<1	1.56	0.14	N/A
G07	BDW-SHD-OSW45-4,SB60(2)-4,ENAD(4)-11AR90SS-T1>1	1.68	0.14	N/A
G08	BDW-SHD-OSW45-4,SB60(2)-4,ENAD(4)-11AR90SS-T2>1	1.69	0.14	N/A
2.25" Door Slab				
G09	BDW-SHD-OSW57-4,SB60(2)-4,CL-4,CL-11AR90SS	1.35	0.16	N/A
G10	BDW-SHD-OSW57-4,SB60(2)-4,CL-4,CL-11AR90SS-G2>1	1.36	0.13	N/A
G11	BDW-SHD-OSW57-4,SB60(2)-4,CL-4,CL-11AR90SS-T1>1	1.45	0.13	N/A
G12	BDW-SHD-OSW57-4,SB60(2)-4,CL-4,CL-11AR90SS-T2>1	1.45	0.13	N/A
G13	BDW-SHD-OSW57-4,SB60(2)-4,CL-4,ENAD(6)-11AR90SS	1.27	0.16	N/A
G14	BDW-SHD-OSW57-4,SB60(2)-4,CL-4,ENAD(6)-11AR90SS-G2>1	1.31	0.13	N/A
G15	BDW-SHD-OSW57-4,SB60(2)-4,CL-4,ENAD(6)-11AR90SS-T1>1	1.39	0.13	N/A
G16	BDW-SHD-OSW57-4,SB60(2)-4,CL-4,ENAD(6)-11AR90SS-T2>1	1.40	0.13	N/A



Notes:

- Products are not intended for installation in storefronts, non-operable portions of curtain wall, fixed glazing cast into precast concrete panels, greenhouses, skylights or sloped glazing.
- Test procedures are designed to test the performance of the test specimen only and are not necessarily used to test the performance of the installation, particularly the perimeter sealant joint and anchoring of the assembly.
- The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI.
- No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing.
- Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.