



RECREATIONAL VEHICLE GAS COMPONENT PROGRAM

- Customer: DDR LLC dba Starcraft Distribution
Class: Gas Burner Cooktop – For Recreational Vehicle Use Only
Location: Bristol, Indiana
Listing No. REC607-2
Effective Date: April 1, 2016
Last Revised Date: January 15, 2018
Expires: N/A
- Standards: CAN1-1.16-M79 (R2011) “Propane Fire Cooking Appliance for Recreational Vehicles”
- ANSI Z21.57-2010 & ANSI Z21.57a-2012 “Recreational Vehicle Cooking Gas Appliances”
- With reference to
- ANSI Z21.58-2007 / CSA 1.6-2007 “Outdoor Cooking Gas Appliances”
- Product: Propane gas appliance for recreational vehicle use only, for sale in Canada and the United State of America
- Markings: Products are marked in a permanent manner where it is readily visible after installation with the following information in both English and French:
- a) QAI logo with ‘c’, ‘us’ and ‘rv’ indicators
 - b) QAI File Number: REC607-2
 - c) Listee identification and address
 - d) Model number of the appliance
 - e) The product standards
 - f) Information for traceability: month and year of manufacture or batch number
 - g) Product ratings: normal hourly BTU input rating for all main burners and the manifold pressure in inches water column
 - h) The statement, “For Use with Propane Only.”
 - i) The statement, “For Use In Recreational Vehicles Only”
 - j) The statement, “Approved As An Unvented Unit”
 - k) Each appliance shall be clearly marked with the minimum horizontal distance from the sides and back of appliance to adjacent vertical combustible walls extending above the top panel from rear wall and minimum horizontal distance from front edge of counter to front side of appliance.
 - l) Each appliance shall be clearly marked with the minimum clearances between the appliance and combustible construction

extending from the cooking surface to 18 in (457 mm) above the level of the cooking surface.

- m) Each appliance shall have a marking stating a maximum depth of 13 in (330 mm) for the overhead cabinets.
- n) Statement, "This appliance is not to be installed with a ventilation system that blows air downward toward the cooktop"
- o) QAI logo shown here:



Models / Ratings:

| Model | Rating | Fuel |
|-----------|---|---------|
| D-2728 | 7,500 BTU/hr | Propane |
| D-2728REV | 7,500 BTU/hr | Propane |
| 1204 | Right Burner: 5,200 BTU/hr Left Burner: 7,200 BTU/hr | Propane |

Clearances:

| Model: D-2728 & D2728REV | |
|---|-------------------|
| Left side clearance | 6 in (152 mm) |
| Right side clearance | 6 in (152 mm) |
| Front clearance | 3 in (76 mm) |
| Rear clearance | 3 in (76 mm) |
| Clearance from upper cabinet to top surface within minimum horizontal clearances to cooktop | 18 in (457 mm) |
| Clearance between top of unit and bottom of uncovered wood or metal cabinet | 30 in (762 mm) ** |
| Left side under the unit (when in use) *** | 6 in (152 mm) |
| Right side under the unit (when in use) *** | 6 in (152 mm) |
| Front side under the unit (when in use) *** | 3 in (76 mm) |
| Rear side under the unit (when in use) *** | 3 in (76 mm) |
| Clearance below the unit (when in use) *** | 12 in (305 mm) |

** Vertical clearance to combustible surface over the cooktop can be reduced to 16 inches (406.4 mm) under the condition that combustible surface only extends 2 inches (50.8 mm) from the rear wall; otherwise, the minimum vertical clearance above the cooking surface must be 30 inches (762 mm).

*** Models D-2728 and D-2728REV are intended to be installed using drawer slides to pull it away and provide additional clearance from the unit and under cabinet shelving during use. The unit, once cool, is then pushed back into the storage space after use.

| Model: 1204 |
|-------------|
| |



| | |
|---|------------------|
| Left side clearance | 3-3/8 in (85 mm) |
| Right side clearance | 3-3/8 in (85 mm) |
| Front clearance | 1-1/2 in (38 mm) |
| Rear clearance | 8 in (203 mm) |
| Clearance from upper cabinet to top surface within minimum horizontal clearances to cooktop | 18 in (457 mm) |
| Clearance between top of unit and bottom of uncovered wood or metal cabinet | 30 in (762 mm) |
| Left side under the unit | 1-1/2 in (38 mm) |
| Right side under the unit | 1-1/2 in (38 mm) |
| Front side under the unit | 1-1/2 in (38 mm) |
| Rear side under the unit | 1-1/2 in (38 mm) |
| Clearance below the unit | 1-1/2 in (38 mm) |

Notes: Devices included in this listing are for use in recreational vehicles only. Final acceptance of those devices in the recreational vehicle is subject to inspection by the recreational vehicle certifier.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warrantee is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.
