



## BUILDING PRODUCTS LISTING PROGRAM

**Customer:** Elevation Building Products, LLC. dba CeDUR  
**Class:** Plastic Shakes  
**Location:** Aurora, Colorado USA  
**Website:** [www.cedur.com](http://www.cedur.com)

**Listing No.** B1090  
**Project No.** B1090-1 Edition 4  
**Effective Date:** March 13, 2016  
**Last Revised Date:** July 14, 2025  
**Expires:** N/A

**Standards:** ASTM E108-20a      *“Standard Test Methods for Fire Tests of Roof Coverings”.*  
CAN/ULC S107-19      *“Standard Test Methods for Fire Tests of Roof Coverings”.*  
UL 2218-22      *“Impact Resistance of Prepared Roof Covering Materials”.*

**Product:** Elevation Building Products, LLC dba CeDUR® are plastic composite roof coverings available in the following models:

- CeDUR® Shakes

**Markings:** Each panel is marked with a permanent label containing the following information:

- a) Manufacturer’s name or trademark
- b) Product Name
- c) Production date
- d) Standards “UL2218” and “ASTM E108” or “UL 790”
- e) QAI file number: B1090 / CER<sub>US</sub>-1025
- f) QAI logo shown here:



:



**Models/Rating:** The following outlines roof-fire classified assemblies determined in accordance with ASTM E108 / UL 790 / CAN/ULC S107 and hail impact resistance in accordance with UL 2218:

**Assembly 1: Class A Roof Fire Classified Applications (Unlimited Slope)**

Sheathing	Underlayment	Approved Roof Covering(s)	Maximum Exposure
Minimum 15/32-inch (11.9 mm) AC Exterior Plywood	Minimum one layer Type II (No. 30) asphalt-saturated felt complying with ASTM D226/CSA A123.3 Type 2	CeDUR® Shakes	10 inches (254 mm)

**Assembly 2: Class IV Impact Resistant Applications (Unlimited Slope)**

Sheathing	Underlayment	Approved Roof Covering(s)	Maximum Exposure
Minimum 15/32-inch (11.9 mm) AC Exterior Plywood	Unrestricted	CeDUR® Shakes	10 inches (254 mm)

- Note 1: Underlayment components are to be installed in accordance with the manufacturer’s published installation instructions.
- Note 2: Products must be installed with the manufacturer’s published installation instructions and in accordance with the building codes recognized by the authority having jurisdiction
- Note 3: Listed manufacturers are subject to on-going inspections by QAI to ensure that the products outlined above remains as it is listed.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at [www.qai.org](http://www.qai.org) for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to [info@qai.org](mailto:info@qai.org). Please include the listing number in the request.

\*\*\*