



WINDOWS & DOORS LISTING PROGRAM

Customer: Eurosell Windows Ltd.
Class: Fenestration Products – Energy Performance
Location: Surrey, British Columbia
Website: www.eurosellwindows.com

Listing No. W481-1
Project No. W481-1 ED7
Effective Date: January 2, 2013
Last Revised Date: January 30, 2024
Expires: N/A

Standards: CSA A440.2 “Fenestration Energy Performance”

Product: Vinyl Windows and Doors

Markings: Products are marked with the following content in a permanent manner where it is readily visible after installation:

- a) Manufacturer’s name, Trademark or other recognized symbol or identification.
- b) QAI file Number: W481
- c) QAI logo shown here:



- d) “Evaluation for energy performance in accordance with CSA A440.2” / “Évalué pour la performance d’énergie en accord à la norme CSA A440.2”

Models / Ratings:

5000 Series Picture Window

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	ESW-5000PC-3,272(2)-3,CL-13AR90SS	1.49	0.33	26
G02	ESW-5000PC-3,272(2)-3,i89(3)-13AR90SS	1.48	0.33	27
G03	ESW-5000PC-3,SB60(2)-6,CL-13AR90SS	1.47	0.32	26
G04	ESW-5000PC-3,272(2)-3,CL-3,CL-13AR90SS	1.16	0.31	33
G05	ESW-5000PC-3,272(2)-3,CL-3,CL-13AR90SS-G1<1	1.19	0.28	30



Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G06	ESW-5000PC-3,SB60(2)-3,CL-3,CL-13AR90SS	1.15	0.30	32
G07	ESW-5000PC-3,SN68(2)-3,SN68(4)-13AR90SS	1.19	0.27	30
G08	ESW-5000PC-3,SB60(2)-3,i89(4)-13AR90SS	1.25	0.31	31
G09	ESW-5000PC-3,366(2)-3,SB60(4)-3,CL-13AR90SS	0.87	0.19	32
G10	ESW-5000PC-3,366(2)-3,180(4)-3,CL-13AR90SS	0.89	0.19	31

5000 Series Casement Window

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	ESW-5000CA-3,272(2)-3,CL-13AR90SS	1.47	0.26	23
G02	ESW-5000CA-3,272(2)-3,i89(3)-13AR90SS	1.46	0.26	23
G03	ESW-5000CA-3,SB60(2)-6,CL-13AR90SS	1.45	0.25	22
G04	ESW-5000CA-3,272(2)-3,CL-3,CL-13AR90SS	1.21	0.24	27
G05	ESW-5000CA-3,272(2)-3,CL-3,CL-13AR90SS-G1<1	1.22	0.22	26
G06	ESW-5000CA-3,SB60(2)-3,CL-3,CL-13AR90SS	1.20	0.23	27
G07	ESW-5000CA-3,SN68(2)-3,SN68(4)-13AR90SS	1.24	0.21	25
G08	ESW-5000CA-3,SB60(2)-3,i89(4)-13AR90SS	1.28	0.25	26
G09	ESW-5000CA-3,366(2)-3,SB60(4)-3,CL-13AR90SS	0.99	0.15	27
G10	ESW-5000CA-3,366(2)-3,180(4)-3,CL-13AR90SS	1.01	0.15	26
G11	ESW-5000CA-3,180(2)-3,CL-13AR90EE	1.51	0.40	30
G12	ESW-5000CA-3,CL-3,180(3)-13AR90EE	1.51	0.42	31

5000 Series Awning Window

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	ESW-5000AW-3,272(2)-3,CL-13AR90SS	1.48	0.26	22
G02	ESW-5000AW-3,272(2)-3,i89(3)-13AR90SS	1.47	0.26	23
G03	ESW-5000AW-3,SB60(2)-6,CL-13AR90SS	1.46	0.25	22
G04	ESW-5000AW-3,272(2)-3,CL-3,CL-13AR90SS	1.22	0.24	27
G05	ESW-5000AW-3,272(2)-3,CL-3,CL-13AR90SS-G1<1	1.22	0.22	26
G06	ESW-5000AW-3,SB60(2)-3,CL-3,CL-13AR90SS	1.21	0.23	27
G07	ESW-5000AW-3,SN68(2)-3,SN68(4)-13AR90SS	1.28	0.22	24
G08	ESW-5000AW-3,SB60(2)-3,i89(4)-13AR90SS	1.32	0.25	25
G09	ESW-5000AW-3,366(2)-3,SB60(4)-3,CL-13AR90SS	1.00	0.15	27
G10	ESW-5000AW-3,366(2)-3,180(4)-3,CL-13AR90SS	1.01	0.15	26



9000 Series Picture Window

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	ESW-9000PC-3,272(2)-3,CL-13AR90SS	1.51	0.33	26
G02	ESW-9000PC-3,366(2)-3,CL-13AR90SS	1.48	0.22	20
G03	ESW-9000PC-3,366(2)-3,CL-13AR90SS-G1<1	1.53	0.20	18
G04	ESW-9000PC-3,SB60(2)-6,CL-13AR90SS	1.49	0.32	26
G05	ESW-9000PC-3,SB60(2)-3,CL-12AR90SD	1.59	0.32	23
G06	ESW-9000PC-3,SB60(2)-3,CL-12AIRSD	1.80	0.32	19
G07	ESW-9000PC-3,272(2)-3,CL-3,i89(5)-6AR90SS	1.35	0.30	28
G08	ESW-9000PC-3,SN68(2)-3,SN68(4)-13AR90SS	1.22	0.27	29
G09	ESW-9000PC-3,SB60(2)-3,i89(4)-13AR90SS	1.27	0.31	30

9000 Series Single Sliding Window

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	ESW-9000SS-3,272(2)-3,CL-13AR90SS-R1	1.58	0.31	23
G02	ESW-9000SS-3,366(2)-3,CL-13AR90SS-R1	1.54	0.21	18
G03	ESW-9000SS-3,366(2)-3,CL-13AR90SS-R1-G1<1	1.59	0.19	16
G04	ESW-9000SS-3,SB60(2)-6,CL-13AR90SS-R1	1.55	0.30	23
G05	ESW-9000SS-3,SB60(2)-3,CL-12AR90SD-R1	1.70	0.30	20
G06	ESW-9000SS-3,SB60(2)-3,CL-12AIRSD-R1	1.89	0.30	16
G07	ESW-9000SS-3,272(2)-3,CL-3,i89(5)-6AR90SS-R1	1.42	0.29	25
G08	ESW-9000SS-3,SN68(2)-3,SN68(4)-13AR90SS-R1	1.31	0.26	26
G09	ESW-9000SS-3,SB60(2)-3,i89(4)-13AR90SS-R1	1.35	0.29	27

9000 Series Single Hung Window

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	ESW-9000SH-3,272(2)-3,CL-13AR90SS-R1	1.58	0.31	23
G02	ESW-9000SH-3,366(2)-3,CL-13AR90SS-R1	1.54	0.21	18
G03	ESW-9000SH-3,366(2)-3,CL-13AR90SS-R1-G1<1	1.59	0.19	15
G04	ESW-9000SH-3,SB60(2)-6,CL-13AR90SS-R1	1.55	0.30	23
G05	ESW-9000SH-3,SB60(2)-3,CL-12AR90SD-R1	1.68	0.30	20
G06	ESW-9000SH-3,SB60(2)-3,CL-12AIRSD-R1	1.87	0.30	16
G07	ESW-9000SH-3,272(2)-3,CL-3,i89(5)-6AR90SS-R1	1.41	0.29	25
G08	ESW-9000SH-3,SN68(2)-3,SN68(4)-13AR90SS-R1	1.32	0.26	25
G09	ESW-9000SH-3,SB60(2)-3,i89(4)-13AR90SS-R1	1.36	0.30	27



Vinyl Series Picture Window

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	ESW-VPC-3,272(2)-3,CL-16AR90SP-R1	1.51	0.33	N/A
G02	ESW-VPC-3,272(2)-3,i89(4)-16AR90SP-R1	1.27	0.32	N/A

Vinyl Series Tilt & Turn Window

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	ESW-VTT-3,272(2)-3,CL-16AR90SP-R1	1.53	0.21	N/A
G02	ESW-VTT-3,272(2)-3,i89(4)-16AR90SP-R1	1.38	0.21	N/A
G03	ESW-VTT-3,272(2)-3,CL-19AR90SP-R1	1.54	0.21	N/A
G04	ESW-VTT-3,272(2)-3,i89(4)-19AR90SP-R1	1.39	0.21	N/A
G05	ESW-VTT-3,272(2)-3,CL-3,CL-13AR90SP-R1	1.30	0.20	N/A
G06	ESW-VTT-3,272(2)-3,CL-3,i89(6)-13AR90SP-R1	1.21	0.20	N/A

Vinyl Series In-Swing Side-Hinged Door

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	ESW-VISHD-4,272(2)-4,CL-14AR90SP-R1	1.48	0.25	N/A
G02	ESW-VISHD-4,272(2)-4,i89(4)-14AR90SP-R1	1.33	0.24	N/A
G03	ESW-VISHD-4,272(2)-4,CL-17AR90SP-R1	1.49	0.25	N/A
G04	ESW-VISHD-4,272(2)-4,i89(4)-17AR90SP-R1	1.31	0.24	N/A



Notes:

- Products are not intended for installation in storefronts, non-operable portions of curtain wall, fixed glazing cast into precast concrete panels, greenhouses, skylights or sloped glazing.
- Test procedures are designed to test the performance of the test specimen only and are not necessarily used to test the performance of the installation, particularly the perimeter sealant joint and anchoring of the assembly.
- The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI.
- No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing.
- Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.