

ELECTRICAL PRODUCTS LISTING PROGRAM

Class: Luminaires

Customer: IP Lighting Ltd.
Location: 3611 Commercial St, Vancouver, B.C Canada, V5N 4G1

Listing No. E10428
Project No. E10428-1401
Effective Date: August 9, 2011
Last Revised: April 2, 2014
Expires: N/A

Product: Luminaires (Retrofit kits)

Label: Products are marked in a permanent manner where it is readily visible after installation with the following: Manufacturer's Name, Trademark or other recognized symbol of identification; Model Designation; Month and Year of Manufacture; Rated Input Voltage; Frequency; Amperes or Volt-Amperes Input; QAI logo with the "c" identifier; QAI File Number E10428; and the wording "CSA C22.2 No. 250.0-08" and "CSA C22.2 No. 250.13-12".

Warning markings as required in both national languages (Canada).

Standards: CSA C22.2 No. 250.0 – 08 "Luminaire",
CSA C22.2 No. 250.13 – 12 "LED equipment for lighting applications"

Models:

<u>Model</u>	<u>Voltage</u>	<u>Wattage</u>	<u>Hertz</u>	<u>Locations **</u>	<u>Environmental</u>	<u>Date added dd/mm/yy</u>
3037	120VAC	25W	60	LOC-3	Outdoor	04/08/11
*6555	120VAC	50W	60	Suspended Ceiling	Indoor	04/08/11
2077	120VAC	10W	60	LOC-4	Outdoor	04/08/11
5740	240VAC	110W	60	LOC-6	Outdoor	04/08/11
3037R	120VAC	44W	60	LOC-3	Outdoor	10/10/12
609560	120VAC	24W	60	LOC-1	Indoor	10/10/12
70/2082R-27W-120	120VAC	34.4W	60	LOC-3	Dry location	02/04/14
70/2082R-27W-347	347VAC	34.4W	60	LOC-3	Dry location	02/04/14
70/2082R-36W-120	120VAC	40W	60	LOC-3	Dry location	02/04/14
70/2082R-36W-347	347VAC	40W	60	LOC-3	Dry location	02/04/14
6008R-30W	120VAC	30W	60	LOC-3	Dry location	02/04/14

NOTES:

1. * 1' x 4', 2' x 2' and 6" x 4" length options.
2. ** Locations as defined in C22.2 No. 250.0-08

3. Vila Casino and SFU models certified with CSA C22.2 No. 250.0-08 with reference to CSA C22.2 No. 250.13-12
4. R – Retro-fit luminaire
5. Permanently connected
6. NOT for use with dimmers
7. Original fixtures (enclosures for the retrofit kits) must have been previously approved.
8. Model 6008R-30W is only for use in open luminaires.
9. Model 70/2082R-27W and 70/2082R-36W are suitable for use in enclosed recessed luminaires.