

**BUILDING PRODUCTS LISTING PROGRAM**

**Class:** Housewrap

**Customer:** Jumpstart Consultants, Inc.  
**Location:** 4649 Carolina Ave., Bldg 1  
 Richmond, VA 23222

**Listing No.** B1063-2  
**Effective Date:** March 19, 2015  
**Last Revised:** No Revisions to Date  
**Expires:** N/A

**Product(s):** Jumpstart Synthetic Housewrap Products

<b>MODEL</b>	<b>WIDTH</b>	<b>LENGTH</b>	<b>WEIGHT</b>
<b>HW03-LPA</b>	108 or 120 inches (2.7 or 3.0 m)	100, 150, or 195 feet (30, 46, or 59 m)	2.4 lbs/100 ft <sup>2</sup> (117 g/m <sup>2</sup> )
<b>HWD2-72A</b>	108 or 120 inches (2.7 or 3.0 m)	100, 150, or 195 feet (30, 46, or 59 m)	1.5 lbs/100 ft <sup>2</sup> (73 g/m <sup>2</sup> )
<b>HWD3-67A</b>	108 or 120 inches (2.7 or 3.0 m)	100, 150, or 195 feet (30, 46, or 59 m)	1.4 lbs/100 ft <sup>2</sup> (67 g/m <sup>2</sup> )

Note 1: Other sizes commercially available

**Standard:** ASTM E2273- *Standard Test Method for Determining the Drainage Efficiency of Exterior Insulation and Finish Systems (EIFS) Clad Wall Assemblies*

The following outlines drainage capacity of QAI certified Jumpstart synthetic underlayment products when tested to ASTM E2273:

**Rating(s):** **Jumpstart Synthetic Underlayment – Physical Property Specifications**

<b>PRODUCT</b>	<b>TEST METHOD</b>	<b>DRAINAGE EFFICIENCY</b>
HW03-LPA	ASTM E2273	98%
HWD2-72A	ASTM E2273	95%
HWD3-67A	ASTM E2273	96%

\* Note 2: The products in this listing above, demonstrate compliance with Exception 1, Section 703.1.1. of the 2011 Oregon Residential Specialty Code as a Water-Resistant Barrier with enhanced drainage and exceeding 75% drainage efficiency when tested in accordance with ASTM E2273.

- Label: Listed products are identified with a label bearing the following information:
- Product Identification Label
  - Company name, logo, address and phone number
  - Product name
  - QAI logo with 'us' indicator
  - QAI Certification Listing Number (B1063-2)
- Note: Products for end use in Canada may be required to have marking in both French and English. It is the responsibility of the Applicant to apply bilingual markings as required by the applicable evaluation reports and in accordance with Provincial and Territorial Regulatory Authorities.
- Notes: The product must be installed in accordance with the code enforced by the authority having jurisdiction. Final acceptance of the product in the final installation is subject to inspection by the authority having jurisdiction.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI.

No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing.

Visit the QAI Online Listing Directory located at [www.qai.org](http://www.qai.org) for the most up to date version of this Listing and to validate that this QAI Listing is active.

Questions regarding this listing may be directed to [info@qai.org](mailto:info@qai.org). Please include the listing number in the request.

\*\*\*