

**BUILDING PRODUCTS LISTING PROGRAM**

Class: Exterior Insulation and Finish Systems

Customer: Les Enduits STEF, Inc.  
Location: 4365 rue Robitaille, Sherbrooke, Quebec J1L 2K2

Listing No.: B1045-1  
Effective Date: April 30, 2012  
Last Revised: August 2015  
Expires: N/A  
Website: [www.stef.cc](http://www.stef.cc)

Product(s): STEF Exterior Insulation and Finish Systems (EIFS)

Standards: CAN/ULC S101 "Standard Methods of Fire Endurance Tests of Building Construction and Materials".

CAN/ULC S114 "Standard Methods of Fire Endurance Tests of Building Construction and Materials".

CAN/ULC S134 "Standard Method of Fire Test of Exterior Wall Assemblies".

Models: STEF Premium Drainscreen  
 STEF Premium I  
 STEF Premium II

Ratings: STEF Basecoat is classified as noncombustible, and complies with CAN/ULC S114.

The following Les Enduits STEF, Inc. EIFS assemblies have been evaluated for use in noncombustible construction as outlined in Section 3.1.5.5 of the National Building Code of Canada through testing to CAN/ULC S134.

Table 1. STEF EIFS CAN/ULC S134 Certified Assemblies

| QAI Design #                | APPROVED SYSTEM                                       | Heat Flux 3.5 m above Opening (kW/m <sup>2</sup> ) | Flame Spread Above Opening (meters) |
|-----------------------------|---|--|-------------------------------------|
| <b>B1045-1a<sup>1</sup></b> | STEF Drainscreen<br>STEF Premium I<br>STEF Premium II | < 35   | < 5.0                               |

Note<sup>1</sup>: See design listing B1045-1a for details regarding approved components and installation evaluated by QAI.

The following Les Enduits STEF, Inc. EIFS assemblies have been evaluated for use for protection of exterior building face containing foam plastic insulation as

outlined in Section 3.2.3.8 of the National Building Code of Canada through testing to CAN/ULC S101.

Table 1. STEF EIFS CAN/ULC S101 Certified Assemblies

| QAI Design #          | APPROVED SYSTEM                                       | FIRE ENDURANCE | OPENINGS               |
|-----------------------|---|----------------|------------------------|
| B1045-1b <sup>2</sup> | STEF Drainscreen<br>STEF Premium I<br>STEF Premium II | 15 Minutes     | No Openings Developed. |

Note<sup>2</sup>: See design listing B1045-1b for details regarding approved components and installation evaluated by QAI. All noted STEF assemblies require installation with noncombustible STEF Basecoat component at thickness outlined in the noted QAI design listing.

Label: Product is labeled by Les Enduits STEF, Inc include the following information:

- Manufacturer's name (Les Enduits STEF, Inc.),
- Expanded Polystyrene Type (Type 1),
- QAI<sub>c</sub> logo
- Certified Standards
- Material identification lot number

**Note:** The product must be installed in accordance with the code enforced by the authority having jurisdiction. Final acceptance of the product in the final installation is subject to inspection by the authority having jurisdiction.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI.

Visit the QAI Online Listing Directory located at [www.qai.org](http://www.qai.org) for the most up to date version of this Listing and to validate that this QAI Listing is active.

Questions regarding this listing may be directed to [info@qai.org](mailto:info@qai.org). Please include the listing number in the request.

\*\*\*