

## BUILDING PRODUCTS LISTING PROGRAM

Customer: Owens Corning Canada LP  
 Class: Thermal Insulation  
 Location: Scarborough, Ontario  
 Website: www.owenscorning.ca  
 Product Site: www.thermafiber.com

Listing No. B1079  
 Project No. B1079-1 Edition 2

Effective Date: January 30, 2017  
 Last Revised Date: September 9, 2021  
 Expires: N/A

Standards: CAN/ULC-S124 “Standard Method of Test for the Evaluation of Protective Coverings for Foamed Plastic”

Product: Thermafiber Mineral Wool Thermal Insulation Products:

- Ultrabatt™
- VersaBoard™ 60 unfaced and faced.
- Rainbarrier® ci High Compressive (80)

Markings: Listed products are identified with a label bearing the following information:

- a) Owens Corning Canada LP
- b) Address, including city and country of manufacture
- c) Product Name
- d) Date of Production
- e) QAI Certification logo with “c” indicator
- f) QAI Certification Listing Number (B1079-1)
- g) Certified standards (CAN/ULC-S124)

Models / Ratings: **The following outlines Thermafiber Ultrabatt™, VersaBoard™ 60 and Rainbarrier® ci High Compressive (80) mineral wool thermal insulation performance determined in accordance with the noted standards. The ratings outlined in the tables below are achieved in assemblies that are defined in the QAI Design Listings.**

Thermafiber Ultrabatt™ mineral wool thermal insulation as a protective covering for foamed plastic per CAN/ULC-S124 for use over foam plastic insulation of a maximum R value of 7.5/inch

QAI Design #	Batt Thickness	Batt R Value	Classification
-----------------	----------------	--------------	----------------



<b>B1079-1a</b>	5.5"	R22 & R23	A
-----------------	------	-----------	---

Thermafiber VersaBoard™ 60 and Rainbarrier® ci High Compressive (80) mineral wool thermal insulations are protective coverings for foamed plastic per CAN/ULC-S124 for use over foam plastic insulation of a maximum R value of 7.5/inch

QAI Design #	Board Thickness	Classification
<b>B1079-1b</b>	2"	B
	3"	A

Notes: Final acceptance of the product in the intended application is to be determined by the authority having jurisdiction.

Product is to be installed in accordance with the QAI Design Listing and manufacturer's published installation instructions by qualified installing personnel.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at [www.qai.org](http://www.qai.org) for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to [info@qai.org](mailto:info@qai.org). Please include the listing number in the request.

\*\*\*