

BUILDING PRODUCTS LISTING PROGRAM

Customer: Roxul, dba ROCKWOOL
Class: Thermal Insulation
Location: Milton, Ontario
Website: www.rockwool.com

Listing No. B1067
Project No. B1067-1 Edition 7

Effective Date: September 29, 2014
Last Revised Date: September 22, 2021

Standards: CAN/ULC-S101 *Fire Endurance Tests of Building Construction and Materials.*
CAN/ULC-S124 *Evaluation of Protective Coverings for Foamed Plastics.*
ASTM C665 *Standard Specification for Mineral-fiber Blanket Thermal Insulation for Light Frame Construction and Manufactured Housing.*
ASTM C612 *Standard Specification for Mineral Fiber Block and Board Thermal Insulation.*
ASTM C726 *Standard Specification for Mineral Wool Roof Insulation Board.*
ASTM E136 *Standard Test Method for Assessing Combustibility of Materials Using a Vertical Tube Furnace at 750oC.*
ASTM E84 *Standard Test Method for Surface Burning Characteristics of Building Materials.*
ASTM D3345 *Standard Test Method for Laboratory Evaluation of Wood and Other Cellulosic Materials for Resistance to Termites.*
ASTM C518 *Standard Test Method for Steady-State Thermal Transmission Properties by Means of the Heat Flow Meter Apparatus.*

Products: ROCKWOOL COMFORTBATT® – Mineral Wool Batt Insulation
ROCKWOOL COMFORTBOARD® 110 – Mineral Wool Board Insulation
ROCKWOOL COMFORTBOARD® 80 – Mineral Wool Board Insulation
ROCKWOOL TOPROCK® DD – Mineral Wool Roof and Deck Insulation
ROCKWOOL MULTIFIX™ – Mineral Wool Roof and Deck Insulation

Markings: Product is marked with labels supplied by ROCKWOOL with the following information:

- Manufacturer's Name
- Manufacturing Address
- Product Name
- Date of Manufacture
- QAI logo with the "C" identifier
- QAI Listing Number (B1067-1)
- QAI CERus-1004
- QAI Certification Logo outlined below:



Ratings: ROCKWOOL COMFORTBATT®, COMFORTBOARD® 80, COMFORTBOARD® 110, TOPROCK® DD and MULTIFIX™ products have been evaluated for compliance to the 2018 / 2015 International Building Code and 2018 / 2015 International Residential Code as outlined in QAI CER_{us}-1004.

ROCKWOOL COMFORTBATT®, COMFORTBOARD® 80, COMFORTBOARD® 110, TOPROCK® DD and MULTIFIX™ products comply with ASTM E136 and are classified noncombustible.

ROCKWOOL COMFORTBATT®, COMFORTBOARD® 80, COMFORTBOARD® 110, TOPROCK® DD and MULTIFIX™ products classification as thermal insulation per ASTM C665, ASTM C612 and ASTM C726 are outlined below:

PRODUCT	CLASSIFICATION		
	ASTM C665	ASTM C612	ASTM C726
COMFORTBATT®	Type I Class B	Type I	-
COMFORTBOARD® 80	-	Type IVB Category 2	-
COMFORTBOARD® 110	-	Type IVB Category 2	-
TOPROCK® DD	-	-	Type I Class I
MULTIFIX™	-	-	Type I Class I

ROCKWOOL COMFORTBATT®, COMFORTBOARD® 80, COMFORTBOARD® 110, TOPROCK® DD and MULTIFIX™ products surface burning characteristics per ASTM E84 are outlined below:

PRODUCT	CLASSIFICATION		
	Thickness (inches)	Flame Spread Index	Smoke Developed Index
COMFORTBATT®	≤ 10	≤ 25	≤ 50
COMFORTBOARD® 80	≤ 6		
COMFORTBOARD® 110	≤ 6		
TOPROCK® DD	≤ 6		
MULTIFIX™	≤ 4		

ROCKWOOL COMFORTBOARD® 80 and COMFORTBOARD® 110 products comply with ASTM D3345 and are classified as termite resistant, including Formosa termite types.

For use in fire resistance rated assemblies, and non-combustible construction, see QAI CER_{us}-1004.

ROCKWOOL COMFORTBATT® mineral wool thermal insulation per CAN/ULC-S101 – Loadbearing† Walls and Partitions

QAI Design #	Batt Thickness	Fire Endurance Period	Hose Stream
B1067-1a B1067-1b	3.5"	1 hour	Pass

† Restricted-Load Bearing - Load rating for this assembly was calculated and tested using the limit states design method outlined in CAN/ULC-S101 – Appendix C with a load reduction of 18%

ROCKWOOL COMFORTBOARD™ 80 / COMFORTBOARD™ 110 mineral wool thermal insulation per CAN/ULC-S101 – Non-Loadbearing Walls and Partitions

QAI Design #	Board Thickness	Sheathing:	20 min Temperature Rise	Fire Endurance Period*
B1067-1c	3"	None	Complies	40 minute
B1067-1d	1-1/4"	3/8" OSB	Complies	40 minute

* Remain-in place

ROCKWOOL COMFORTBATT®. COMFORTBOARD™ 80 / COMFORTBOARD™ 110 mineral wool thermal insulation as a protective covering for foamed plastic when friction fit between code approved supports per CAN/ULC-S124 for use over foamed plastic insulation of a maximum R value of 7.5/inch.

QAI Design #	Product	Thickness:	Classification	Installation
B1067-1e	COMFORTBATT®	5.5"	B	Friction fit into wall stud cavity. Minimum 2 in. x 4 in. wood wall studs.
	COMFORTBOARD™ 80 / COMFORTBOARD™ 110	2"	B	Friction fit into joist cavity. Minimum 2 in. x 6 in. members.
	COMFORTBOARD™ 80 / COMFORTBOARD™ 110	3"	A	

ROCKWOOL COMFORTBOARD™ 80 / COMFORTBOARD™ 110 mineral wool thermal insulation as a protective covering for foamed plastic per CAN/ULC-S124 for use over foamed plastic insulation of a maximum R value of 7.5/inch

QAI Design #	Board Thickness:	Classification	Installation
B1067-1f	2"	B	Fastened to the foamed plastic using Ramset Insulfast insulation fasteners and non-combustible fasteners at manufacturer's recommended instructions, anchored into code compliant substrate. Tight butt-edge fit.
	3"	A	

Notes: Final acceptance of the product in the intended application is to be determined by the authority having jurisdiction.

Product is to be installed in accordance with the QAI Design Listing and manufacturer's published installation instructions by qualified installing personnel.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warrantee is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions



LABORATORIES

CERTIFICATION TESTING INSPECTION

VANCOUVER, BC: 877.461.8378 ph. | 604.527.8368 fx.
LOS ANGELES, CA: 909.483.0250 ph. | 909.483.0336 fx.
TULSA, OK: 918.437.8333 ph. | 918.437.8487 fx.
TORONTO, ON: 416.550.9280
WEBSITE: WWW.QAI.ORG

regarding this listing may be directed to info@qai.org. Please include the listing number in the request.
