



ELECTRICAL LISTING PROGRAM

Customer: Twice Bright Lighting
Class: Luminaires
Location: Delta, BC

Listing No. E11108
Report No. E11108-2401 Ed.1
Project No. E11108-2401
Effective Date: Jan 16 , 2026
Last Revised
Date:
Expires: <N/A>

Standards: CSA C22.2 No. 250.0-21/ UL1598 5th Ed - Luminaires
CSA c22.2 no. 250.7:20 - Extra-low-voltage landscape lighting
systems
CSA c22.2 no. 250.13:20 - Light emitting diode (LED) equipment
for lighting applications,
UL 1838 3rd ed. 2020 - low voltage landscape lighting systems
UL 8750 2nd ed. 2021 - led equipment for use in lighting products

Product: Luminaires, LED, handrail lights

Markings: Products are marked in a permanent manner where it is readily
visible after installation with the following:

- a) Manufacturer's name or trademark
- b) Model designation
- c) Month and year of manufacture
- d) Product ratings: voltage, frequency, watts
- e) QAI file Number: E11108
- f) The wording "CSA C22.2 No. 250.0 ,UL1598, CSA c22.2 no.
250.7, CSA c22.2 no. 250.13, UL 1838 , UL 8750"
- g) Warning markings as required by the standards in English
and French>
- h) QAI logo shown here:





Models / Ratings:

Family	Model	Volts	Wattage	Location
RGB light series	RLR242-A- RGBDMX-YY (Where "YY" indicates HANDRAIL SIZE) YY=15 - 1.50" (38mm) dia. 0.120" Wall Tube 17 - 1.66" (42mm) dia. Schedule 40 Pipe 19 - 1.90" (48mm) dia. Schedule 40 Pipe	24VDC	2W max	WET or DRY
	RLR242-S- RGBDMX-YY (Where "YY" indicates HANDRAIL SIZE) YY=15 - 1.50" (38mm) dia. 0.120" Wall Tube 17 - 1.66" (42mm) dia. Schedule 40 Pipe 19 - 1.90" (48mm) dia. Schedule 40 Pipe	24VDC	2W max	WET or DRY



Non-RGB light series	RLR242-A-XX-YY (Where "XX" indicates the CCT or color option:) XX = 27 - 2700K 30 - 3000K 35 - 3500K 40 - 4000K 50 - 5000K RD - Red GR - Green BL - Blue AMB - Amber) (Where "YY" indicates HANDRAIL SIZE) YY=15 - 1.50" (38mm) dia. 0.120" Wall Tube 17 - 1.66" (42mm) dia. Schedule 40 Pipe 19 - 1.90" (48mm) dia. Schedule 40 Pipe	24VDC	2W max	WET or DRY
	RLR242-S-XX-YY (Where "XX" indicates the CCT or color option:) XX = 27 - 2700K	24VDC	2W max	WET or DRY



	30 - 3000K 35 - 3500K 40 - 4000K 50 - 5000K RD - Red GR - Green BL - Blue AMB - Amber) (Where "YY" indicates HANDRAIL SIZE) YY=15 - 1.50" (38mm) dia. 0.120" Wall Tube 17 - 1.66" (42mm) dia. Schedule 40 Pipe 19 - 1.90" (48mm) dia. Schedule 40 Pipe			
--	--	--	--	--