

VERIFICATION PROGRAM

Customer: ULINE, INC.
 Class: Fire-Resistant Safes
 Location: Pleasant Prairie, WI

Website: www.uline.com
 Listing No. F471-1
 Effective Date: November 30, 2020
 Last Revised: November 30, 2020
 Date:
 Expires: <N/A>

Standards: Uline 1400°F Temperature Exposure 30 Minute Test

Product: Security and Fire-resistant safes of the following models:

- H-8940
- H-8939
- H-8938

Markings: Product models described above are labeled with a permanent label with the following information:

- Uline
- Product Name
- Country of Manufacture
- QAI Listing Number (F471)
- QAI logo shown here:



Models / Ratings: **Uline Material Handling Security and Fire-resistant Safes are verified for attributes as outlined in Table 1 below.**

Table 1: Achieved Maximum Internal Temperature Rise of Uline Material Handling Security and Fire-Resistant Safes

Series	Models:	Test Specification	350°F Fire Rating
H	H-8940	Uline 1400°F Temperature Exposure Achieved by 30 Minutes	30 Min.
	H-8939		
	H-8938		



LABORATORIES

CERTIFICATION TESTING INSPECTION

VANCOUVER, BC:	877.461.8378 ph.	604.527.8368 fx.
LOS ANGELES, CA:	909.483.0250 ph.	909.483.0336 fx.
WASHINGTON, DC:	540.636.9445 ph.	540.636.9414 fx.
TULSA, OK:	918.437.8333 ph.	918.437.8487 fx.
TORONTO, ON	905.605.5444	
SEATTLE, WA	425.512.8419	
WEBSITE:	WWW.QAI.ORG	

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.
