

ELECTRICAL LISTING PROGRAM

Customer: Wespac International
 Class: Dimmable LED Recessed Luminaires
 Location: 311 NE 14th Avenue, Fort Lauderdale, FL, 33301, USA
 Listing No. E10543
 Report No. E10543-1509 Edition 4
 Project No. E10543-1611
 Effective Date: January 4, 2016
 Last Revised Date: October 28, 2016
 Expires: N/A

Standards: CSA C22.2 No. 250.0 Luminaires
 UL 1598 Luminaires

Product: Dimmable LED Recessed Luminaires
 Suitable for Wet Location, Permanently Connected

Markings: Products are marked in a permanent manner where it is readily visible after installation with the following:

- a) Manufacturer's name or trademark
- b) Model designation
- c) Month and year of manufacture
- d) Product ratings: voltage, frequency, watts
- e) QAI file Number: E10543
- f) The wording "CSA C22.2 No. 250.0 and UL 1598"
- g) Warning markings as required by the standards in English and French

h) QAI logo 

Models / Ratings:

Model #	Voltage VAC	Wattage W	Descriptions	Location
HRS04SL	110	9	4" (101.6mm) Recessed IC Ceiling Shallow LED Light Self-Contained EZ Install Recessed Housing with Spring Clips Quick Electrical Connectors included for quick and easy wiring installation Finish: White Color Temperature: 3000K±100 Total Lumen: 600 LM± 50 Height: 3 ¼" (82.6mm) Rough Opening: 4 ½" (114.3mm) Junction Box: 2.56" x 2.56" x 1.7" (65 x 65 x 43mm)	Wet Locations
HRS04SLN	110	9	4" (101.6mm) Recessed IC Ceiling Shallow LED Light Self-Contained EZ Install Recessed Housing with Spring Clips	Wet Locations



			<p>Quick Electrical Connectors included for quick and easy wiring installation Finish: White Color Temperature: 3000K ±100 Total Lumen: 600 LM ± 50 Height: 3 ¼" (82.6mm) Rough Opening: 4 ½" (114.3mm) Junction Box: 2.56" x 2.56" x 2" (65 x 65 x 51mm)</p>	
HRS04SLNB	110	9	<p>4" (101.6mm) Recessed IC Ceiling Shallow LED Light Self-Contained EZ Install Recessed Housing with Spring Clips Quick Electrical Connectors included for quick and easy wiring installation Finish: White Color Temperature: 3000K ± 100 Total Lumen: 600 LM ± 50 Height: 3 ¼" (82.6mm) Rough Opening: 4 ½" (114.3mm) Junction Box: 2.76" x 2.76" x 2" (70 x 70 x 51mm)</p>	Wet Locations
HRS06SL	110	15	<p>6" (152.4mm) Recessed IC Ceiling Shallow LED Light Self-Contained EZ Install Recessed Housing with Spring Clips Quick Electrical Connectors included for quick and easy wiring installation Color Temperature: 3000K ± 100 Total Lumen: 1000 LM ± 50 Finish: White Height: 3 3/8" (85.7mm) Rough Opening: 6 ½" (165.1mm) Junction Box: 2.56" x 2.56" x 1.7" (65 x 65 x 43mm)</p>	Wet Locations
HRS06SLN	110	15	<p>6" (152.4mm) Recessed IC Ceiling Shallow LED Light Self-Contained EZ Install Recessed Housing with Spring Clips Quick Electrical Connectors included for quick and easy wiring installation Color Temperature: 3000K ± 100 Total Lumen: 1000 LM ± 50 Finish: White Height: 3 3/8" (85.7mm) Rough Opening: 6 ½" (165.1mm) Junction Box: 2.56" x 2.56" x 2" (65 x 65 x 51mm)</p>	Wet Locations
HRS06SLNB	110	15	<p>6" (152.4mm) Recessed IC Ceiling Shallow LED Light Self-Contained EZ Install Recessed Housing with Spring Clips Quick Electrical Connectors included for quick and easy wiring installation Color Temperature: 3000K ± 100 Total Lumen: 1000 LM ± 50 Finish: White Height: 3 3/8" (85.7mm) Rough Opening: 6 ½" (165.1mm) Junction Box: 2.76" x 2.76" x 2" (70 x 70 x 51mm)</p>	Wet Locations

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warrantee is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.
