

ELECTRICAL LISTING PROGRAM

Customer: Wespac International
 Class: LED Lighting for use in Recreational Vehicles
 Location: 311 NE 14th Avenue, Fort Lauderdale, FL, 33301, USA
 Listing No. E10543
 Report No. E10543-1505 Edition 5
 Project No. E10543-1603
 Effective Date: September 4, 2015
 Last Revised Date: June 20, 2016
 Expires: N/A

Standards: CSA C22.2 No. 250.0 Luminaires
 UL 234 Low Voltage Lighting for Use in Recreational Vehicles

Product: Luminaires and LED Equipment for use in Recreational Vehicles.
 Dry, Damp and wet Locations use, Permanently and Cord-Connected.

Markings: Products are marked in a permanent manner where it is readily visible after installation with the following:

- a) Manufacturer's name or trademark
- b) Model designation
- c) Month and year of manufacture
- d) Product ratings: voltage, frequency, watts
- e) QAI logo with 'c' and 'us' identifiers
- f) QAI file Number: E10543
- g) The wording "CSA C22.2 No. 250.0 and UL 234"
- h) Warning markings as required by the standards in English and French

Models / Ratings:

Model #	Voltage VDC	Wattage W	Descriptions	Location
NFLF4-xxx	12	4	Sunn Flushmount 4.5 inch with Frosted Opal Plastic lens Cover Easy – Safe Installation 4W SMD LED 360LM	Dry Location
NFLF3-xxx	12	3	Sunn Flushmount 3 inch with Frosted Opal Plastic lens Cover Easy – Safe Installation 3W SMD LED 280LM	Dry Location
PCLS01N-xxx	12	4	Little Star Low Profile Construction w/Frosted Lens Cover 4W SMD LED 360LM No Driver ON/OFF Switch Size: L 5 7/8" X W 3 3/4"	Dry Location



PCMS01N-xxx	12	4	Little Moonn Low Profile Construction w/Opal Lens Cover 4W SMD LED 360LM No Driver ON/OFF Switch Size: L 5 7/8" X W 3 3/4" X H 1 3/10"	Dry Location
PCJS01N-xxx	12	4	StarLink Single - Low Profile Construction w/Frosted Lens Cover Lens - easy installation & removal 4W SMD LED 360LM No Driver ON/OFF Switch Size: L 5 7/8" X W 3 3/4"	Dry Location
PCLS02N-xxx	12	4	Little Star Low Profile Construction w/Frosted Lens Cover 4W SMD LED 360LM No Driver Night Light Function Size: L 5 7/8" X W 3 3/4"	Dry Location
PCMS02N-xxx	12	4	Little Moonn Low Profile Construction w/Opal Lens Cover 4W SMD LED 360LM No Driver Night Light Function Size: L 5 7/8" X W 3 3/4" X H 1 3/10"	Dry Location
PCJS02N-xxx	12	4	StarLink Single - Low Profile Construction w/Frosted Lens Cover Lens - easy installation & removal 4W SMD LED 360LM No Driver Night Light Function Size: L 5 7/8" X W 3 3/4"	Dry Location
PCLS03N-xxx	12	4	Damp Location Little Star Low Profile Construction w/Frosted Lens Cover 4W SMD LED 360LM No Driver ON/OFF Switch Size: L 5 7/8" X W 3 3/4"	Damp Location
PCMS03N-xxx	12	4	Damp Location Little Moonn Low Profile Construction w/Opal Lens Cover 4W SMD LED 360LM No Driver ON/OFF Switch Size: L 5 7/8" X W 3 3/4" X H 1 3/10"	Damp Location



PCJS03N-xxx	12	4	StarLink Single - Damp Location Low Profile Construction w/Frosted Lens Cover Lens - easy installation & removal 4W SMD LED 360LM No Driver ON/OFF Switch Size: L 5 7/8" X W 3 3/4"	Damp Location
PCLS04N-xxx	12	4	Damp Location Little Star Low Profile Construction w/Frosted Lens Cover 4W SMD LED 360LM No Driver Night Light Function Size: L 5 7/8" X W 3 3/4"	Damp Location
PCMS04N-xxx	12	4	Damp Location Little Moonn Low Profile Construction w/Opal Lens Cover 4W SMD LED 360LM No Driver Night Light Function Size: L 5 7/8" X W 3 3/4" X H 1 3/10"	Damp Location
PCJS04N-xxx	12	4	StarLink Single - Damp Location Low Profile Construction w/Frosted Lens Cover Lens - easy installation & removal 4W SMD LED 360LM No Driver Night Light Function Size: L 5 7/8" X W 3 3/4"	Damp Location
PCDS01N-xxx	12	6	Double Star - Low Profile Construction w/Frosted Lens Cover 6W SMD LED 470LM No Driver ON/OFF Switch Size: L 9 1/4" X W 3 3/4" X H 1"	Dry Location
PCJD01N-xxx	12	6	StarLink Double - Low Profile Construction w/Frosted Lens Cover Lens - easy installation & removal 6W SMD LED 470LM No Driver ON/OFF Switch Size: L 9 1/4" X W 3 3/4" X H 1"	Dry Location
PCMD01N-xxx	12	6	Double Moonn - Low Profile Construction w/Opal Lens Cover	Dry Location



			6W SMD LED 470LM No Driver ON/OFF Switch Size: L 9 ¼ " X W 3 ¾ " X H 1 3/10"	
PCDS02N-xxx	12	6	Double Star - Low Profile Construction w/Frosted Lens Cover 6W SMD LED 470LM No Driver Night Light Function Size: L 9 ¼ " X W 3 ¾ " X H 1"	Dry Location
PCJD02N-xxx	12	6	StarLink Double - Low Profile Construction w/Frosted Lens Cover Lens - easy installation & removal 6W SMD LED 470LM No Driver Night Light Function Size: L 9 ¼ " X W 3 ¾ " X H 1"	Dry Location
PCMD02N-xxx	12	6	Double Moonn - Low Profile Construction w/Opal Lens Cover 6W SMD LED 470LM No Driver Night Light Function Size: L 9 ¼ " X W 3 ¾ " X H 1 3/10"	Dry Location
PCDS03N-xxx	12	6	Double Star Damp Location - Low Profile Construction w/Frosted Lens Cover 6W SMD LED 470LM No Driver ON/OFF Switch Size: L 9 ¼ " X W 3 ¾ " X H 1"	Damp Location
PCJD03N-xxx	12	6	StarLink Double - Damp Location Low Profile Construction w/Frosted Lens Cover Lens - easy installation & removal 6W SMD LED 470LM No Driver ON/OFF Switch Size: L 9 ¼ " X W 3 ¾ " X H 1"	Damp Location
PCMD03N-xxx	12	6	Double Moonn Damp Location - Low Profile Construction w/Opal Lens Cover 6W SMD LED 470LM No Driver ON/OFF Switch Size: L 9 ¼ " X W 3 ¾ " X H 1"	Damp Location



			1 3/10"	
PCDS04N-xxx	12	6	Double Star Damp Location - Low Profile Construction w/Frosted Lens Cover 6W SMD LED 470LM No Driver Night Light Function Size: L 9 ¼ " X W 3 ¾ " X H 1"	Damp Location
PCJD04N-xxx	12	6	StarLink Double - Damp Location Low Profile Construction w/Frosted Lens Cover Lens - easy installation & removal 6W SMD LED 470LM No Driver Night Light Function Size: L 9 ¼ " X W 3 ¾ " X H 1"	Damp Location
PCMD04N-xxx	12	6	Double Moonn Damp Location - Low Profile Construction w/Opal Lens Cover 6W SMD LED 470LM No Driver Night Light Function Size: L 9 ¼ " X W 3 ¾ " X H 1 3/10"	Damp Location
PC6FN-xxx	12	6	PopUp Style Female Pancake Plastic Pancake - Low Profile Construction w/Frosted Lens Cover Lens - easy installation & removal 6W SMD LED 470LM No Driver ON/OFF Switch Size: L 9 ¼ " X W 3 ¾ " X H 1"	Dry Location
PC6MN-xxx	12	6	PopUp Style Male Pancake Plastic Pancake - Low Profile Construction w/Frosted Lens Cover Lens - Easy Installation & removal 6W SMD LED 470LM No Driver ON/OFF Switch Size: L 9 ¼ " X W 3 ¾ " X H 2 3/5"	Dry Location
NFLF3W-xxx	12	3	Sunn Flush mount 3 Inch Damp Location with Frosted Opal Plastic Lens Cover Easy - Safe Installation 3W SMD LED 280LM	Damp Location
NFLF4W-xxx	12	4	Sunn Flush mount 4.5 Inch	Damp



			Damp Location with Frosted Opal Plastic Lens Cover Easy - Safe Installation 4W SMD LED 360LM	Location
NFLF4S-xxx	12	4	Sunn Flush mount 4.5 Inch w/Switch with Frosted Opal Plastic Lens Cover Easy - Safe Installation 4W SMD LED 360LM	Dry Location
NFLF4SW-xxx	12	4	Sunn Flush mount 4.5 Inch w/Switch, Damp Location with Frosted Opal Plastic Lens Cover Easy - Safe Installation 4W SMD LED 360LM	Damp Location
RVSMDBF-129512N-xxx	12	9	Flush Mount 10"W * 4.6"H w/ MAX 3*3W SMD LED, Lumen 540 LM, Fitter Only (No driver)	Dry Location
RVSMDBF-133501-xxx	12	3	Bristol 1-Lt Wall Sconce Fitter For Glass Shade 3.5"W * 3.55"H * 4.55"E w/ SMD LED MAX 1X3W 180LM (No driver)	Dry Location
RVSMDBF-110004-xxx	12	3	12V RV USE 12" Stick Pendant Fitter Only with Swivel, Can Use Glass with Small And Larger Hole, w/ LED SMD MAX 1X3W, 180LM, (No driver)	Dry Location
RVSMDBF-110006-xxx	12	3	12V RV USE 16" Stick Pendant Fitter Only with Swivel, Can Use Glass with Small And Larger Hole, w/ LED SMD MAX 1X3W, 180LM, (No driver)	Dry Location
RVSMDBF-135401-xxx	12	3	Capital 1-Lt Spot / Wall Light 3.5"W * 5.5"H ,Complete Fixture, w/ SMD LED MAX 1X3W 180LM (No driver)	Dry Location
RSFW3-xxx	12	3	EZ Spring Recessed 3 inch Shallow Metal Fitter, No driver. With Frosted Plastic Lens, Quick connector and 3 clips. Nylon Threaded Trim Ring Inside for Safe Easy Installation. 3W SMD LED 280LM	Damp Location
RSFW3N-xxx	12	3	EZ Spring Recessed 3 inch Shallow Metal Fitter, No Driver. With Frosted Plastic Lens and 3 Clips	Damp Location



			No Quick Connector Nylon Threaded Trim Ring Inside for Safe Easy Installation. 3W SMD LED 280LM	
RSFW4-xxx	12	4	EZ Spring Recessed 4.5 inch Shallow Metal Fitter, No driver. With Frosted Plastic Lens, Quick connector and 3 clips. Nylon Threaded Trim Ring Inside for Safe Easy Installation. 4W SMD LED 360LM	Damp Location
RSFW4N-xxx	12	4	EZ Spring Recessed 4.5 inch Shallow Metal Fitter, No Driver. With Frosted Plastic Lens and 3 Clips No Quick Connector Nylon Threaded Trim Ring Inside for Safe Easy Installation. 4W SMD LED 360LM	Damp Location
RSBF3N-xxx	12	3	Star Recessed 3 Inch Shallow Metal Fitter Optional Frosted Glass or Frosted Plastic Lens Nylon Threaded Trim Ring Inside For Safe Easy Installation Screw or Clip Installation 3W SMD LED 280LM	Damp Location
RSBF3NN-xxx	12	3	Star Recessed 3 Inch Shallow Metal Fitter No Spring Loaded Clips, No Driver Optional Frosted Glass or Frosted Plastic Lens Nylon Threaded Trim Ring Inside For Safe Easy Installation Screw Installation 3W SMD LED 280LM	Damp Location
RSBF4N-xxx	12	4	Star Recessed 4.5 Inch Shallow Metal Fitter Optional Frosted Glass or Frosted Plastic Lens Nylon Threaded Trim Ring Inside For Safe Easy Installation Screw or Clip Installation 4W SMD LED 360LM	Damp Location
RSBF4NN-xxx	12	4	Star Recessed 4.5 Inch Shallow Metal Fitter No Spring Loaded Clips, No Driver Optional Frosted Glass or	Damp Location



			Frosted Plastic Lens Nylon Threaded Trim Ring Inside For Safe Easy Installation Screw Installation 4W SMD LED 360LM	
RVLTB-xxx	12	0.4	FireFly Light, Blue Light, Wet Location. 12VDC LED Light, No Driver Plastic Lens D 1 1/16" x H 15/16"	Wet Location
RVLTR-xxx	12	0.4	FireFly Light, Red Light, Wet Location. 12VDC LED Light, No Driver Plastic Lens D 1 1/16" x H 15/16"	Wet Location
RVLTW-xxx	12	0.4	FireFly Light, White Light, Wet Location. 12VDC LED Light, No Driver Plastic Lens D 1 1/16" x H 15/16"	Wet Location
RVLTA-xxx	12	0.4	FireFly Light, Amber Light, Wet Location. 12VDC LED Light, No Driver Plastic Lens D 1 1/16" x H 15/16"	Wet Location
RSJBF3N-xxx	12	3	StarLink 3" Recessed Shallow Metal Fitter, with Spring Loaded Clips, No Driver. Optional Frosted Glass or Frosted Plastic Lens Nylon Threaded Trim Ring Inside For Safe Easy Installation Screw or Clip Installation 3W SMD LED 280LM	Damp Location
RSJBF4N-xxx	12	4	StarLink 4.5" Recessed Shallow Metal Fitter, with Spring Loaded Clips, No Driver. Optional Frosted Glass or Frosted Plastic Lens Nylon Threaded Trim Ring Inside For Safe Easy Installation Screw or Clip Installation 4W SMD LED 360LM	Damp Location
RVPN2412-xxx	12	18	Skyllite Dimmable 12V DC LED Panel Espistar 4014 LED, Total 18W, 1000 LM w/Frosted Plastic Lens, Aluminum Frame No Driver Size: 23 5/8" x 11 4/5"	Dry Location
RVPN3012-xxx	12	30	Skyllite Dimmable 12V DC LED Panel	Dry Location



			Espistar 4014 LED, Total 30W,1600 LM w/Frosted Plastic Lens, Aluminum Frame No Driver Size: 30 1/4 " x 12"	
RVPN3712-xxx	12	18	Skyllite Dimmable 12V DC LED Panel Espistar 4014 LED, Total 38W,1800 LM w/Frosted Plastic Lens, Aluminum Frame No Driver Size: 37 3/8" x11 3/4"	Dry Location
SL03-xxx	12	3	Spot/Reading Dimmable 12V DC LED Light With Frosted Glass. 1X3W, 150LM FCC Approved Driver ON/OFF Switch Size: L 2 3/8"x W4"x H 4 3/4"	Dry Location
RVSMD-LF- 140721S-xxx	12	2.16	Metal Wall Mount with Frosted Glass Shade, Complete Fixture No Driver 15" W * 3.22" H * 2" D LED Strip 36 x 0.06W	Dry Location
RV-LF-123502-xxx	12	36	12V Bristol 2-Lt Ceiling, Completed Fixture With Frosted Glass 9" W * 6.85" H * 5.2" E w/ 921 Bulb 2 x 18W	Dry Location
RV-BF-123502-xxx	12	36	12V Bristol 2-Lt Ceiling, Fitter 5.65" W * 4.75" H * 5.15" E w/ 921 Bulb 2 x 18W	Dry Location
RVPN2406-xxx	12	18	Skyllite Dimmable 12V DC LED Panel Espistar 4014 LED, Total 18W,900 LM w/Frosted Plastic Lens, Aluminum Frame No Driver Size: 23 5/8" x 5 7/8"	Dry Location
RVSMD-LF- 140617S-xxx	12	9	12V 3-Lt Vanity with Frosted Opal Glass, Completed Fixture,15"W*5"H*4.25"E MAX 3x3W SMD LED 540LM No Driver	Dry Location
RVSMD-LF- 140618S-xxx	12	9	12V 3-Lt Vanity with Frosted Opal Glass, Completed Fixture,15"W*5.75"H*4.33"E MAX 3x3W SMD LED 540LM	Dry Location



			No Driver	
RVSMDBF150310xxx	12	3	12V 1Lt Wall Sconce, Fitter Only, 3.54"W*8.3"H*4.33"D, w/ SMD LED MAX 1x3W 180LM No driver	Dry Location
RVSMDBF150311xxx	12	3	12V 1Lt Wall Sconce, Fitter Only, 3.54"W*6.8"H*5.8"D, w/ SMD LED MAX 1x3W 180LM No driver	Dry Location
RVSMDBF129512NLxxx	12	6	12v Flush Mount 10"W * 4.6"H w/12*0.5W SMD LED, Lumen 540 LM, Fitter Only, No driver	Dry Location
PPJS01xxx	12	4	StarLink Single with PIR - Low Profile Construction w/Frosted Lens Cover Lens - easy installation & removal 4W SMD LED 360LM No Driver Size: L 5 7/8" X W 3 3/4" X H 1"	Dry Location
PPJD01xxx	12	6	StarLink Double with PIR - Low Profile Construction w/Frosted Lens Cover Lens - easy installation & removal 6W SMD LED 470LM No Driver Size: L 9 1/4" X W 3 3/4" X H 1"	Dry Location
Note: 'xxx' or "xxxxx" may be any set of number used by manufacturer to signify non-critical differences between models such as color and finish or retail package ways				

Notes: Devices included in this listing are for use in Recreational Vehicles only. Final acceptance of those devices in the recreational vehicle is subject to inspection by the Recreational Vehicle Certifier.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warrantee is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.
