

ELECTRICAL LISTING PROGRAM

Customer: Wespac International
 Class: LED Lighting for use in Recreational Vehicles
 Location: 311 NE 14th Avenue, Fort Lauderdale, FL, 33301, USA
 Listing No. E10543
 Report No. E10543-1606 Edition 5
 Project No. E10543-1709
 Effective Date: November 23, 2016
 Last Revised Date: August 28, 2017
 Expires: N/A

Standards: CSA C22.2 No. 250.0 Luminaires
 UL 234 Low Voltage Lighting for Use in Recreational Vehicles

Product: Luminaires and LED Equipment for use in Recreational Vehicles.
 Dry and Damp Locations use, Permanently and Cord-Connected.

Markings: Products are marked in a permanent manner where it is readily visible after installation with the following:

- a) Manufacturer's name or trademark
- b) Model designation
- c) Month and year of manufacture
- d) Product ratings: voltage, frequency, watts
- e) QAI file Number: E10543
- f) The wording "Conforms to CSA C22.2 No. 250.0 and UL 234"
- g) Warning markings as required by the standards in English and French



h) QAI Logo

Models / Ratings:

Model #	Voltage VDC	Wattage W	Descriptions	Location
RVSMD-LF-160410S-xxx	12	39	12V 3-Lt Island Pendant, Completed Fixture 30" x 23.5" (W*H) 3 x 13W bulb	Dry Location
LSD4-xxx	12	4	4.5 Inch Sundowner Flushmount with Frosted Opal Plastic Lens Cover. Easy – Safe Installation, 4W SMD LED 360LM	Dry Location
LSD4S-xxx	12	4	4.5 Inch Sundowner Flushmount w/Switch, with Frosted Opal Plastic Lens Cover. Easy – Safe Installation, 4W SMD LED 360LM	Dry Location
LSD4SW-xxx	12	4	4.5 Inch Sundowner Flushmount	Damp



			w/Switch, Damp Location, with Frosted Opal Plastic Lens Cover. Easy – Safe Installation, 4W SMD LED 360LM	location
RSLF3P-xxx	12	3	Star 3 Inch Shallow Metal Recessed, No Driver w/ Frosted Plastic Lens Installed on Fitter Nylon Threaded Trim Ring Inside For Safe Easy Installation Uses Spring Loaded Clips to Install 3W SMD LED 280LM	Damp Location
RSLF4P-xxx	12	4	Star 4.5 Inch Shallow Metal Recessed, No Driver w/ Frosted Plastic Lens Installed on Fitter Nylon Threaded Trim Ring Inside For Safe Easy Installation Uses Spring Loaded Clips to Install 4W SMD LED 360LM	Damp Location
RSEB3-xxx	12	1	3 Inch Eyeball Recessed Light, No Driver With Frosted Glass Lens Push Switch 1W SMD LED 100LM	Dry Location
RVSM-D-LF-140612N-xxx	12	6	12V 3-Lt semi flushmount with alabaster glass shade, complete fixture, SMD LED 3x2W 540lm 13.9"W x 13.9"D x 5.5"H (No driver)	Dry Location
RVSM-D-BF-130302D-xxx	12	4	12V 2-Lt Semi Flush Fitter Only 11"W x 11"D x 8"H, w/ SMD LED 2x2W, 360LM, (No driver)	Dry Location
RVSM-D-LF-140726N-xxx	12	2	12V 1-Lt wall mount with frosted alabaster glass shade completed fixture 5"W x 6.45"H x 3"E, w/ SMD LED 1x2W 180LM, (No driver)	Dry Location
RVSM-D-BF-110001N-xxx	12	2	12V RV Use 9" Stick Pendant, Frosted Glass, Product Size 3.94"D*11.14"H, w/ 1*2W SMD LED (No Driver)	Dry Location
NFLF4SS-xxx	12	4	Sunn Flushmount 4.5 Inch w/Switch, Wet Location with Frosted Opal Plastic Lens Cover Easy – Safe Installation 4W SMD LED 360LM	Wet Location
RVSM-D-BF-135501N-xxx	12	2	12V 1-Lt Wall Sconce, Product Size 5.63"D*4.17"W*5.87"H, w/ 1*2W SMD LED (No Driver)	Dry Location
RVSM-D-BF-	12	2	12V RV USE 16" Stick Pendant,	Dry

110005N-xxx			Product Size 4.33"D*17.95"H, w/1*2W SMD LED (No Driver)	Location
RVSM-D-LF- 160425-xxx	12	6	12V Semi Flush With Frosted Alabaster Glass, Completed With New Mounting Bracket. SMD LED 6W 540LM (No Driver) 9.27" W * 5.7" H Frosted Alabaster Glass Size: 8" W * 3.25" H	Dry Location
RVSM-D-LF- 160425S-xxx	12	6	12V Semi Flush With Frosted Alabaster Glass, Completed With New Mounting Bracket. SMD LED 6W 540LM (No Driver) 9.27" W * 5.7" H Frosted Alabaster Glass Size: 8" W * 3.25" H	Dry Location
FDR4-xxx	12	4	SunStar 4.5 Inch Flushmount Aluminum Fitter + Frosted Opal Plastic Lens Cover Easy – Safe Installation 4W SMD LED 360LM	Dry Location
FDR4S-xxx	12	4	SunStar 4.5 Inch Flushmount w/Switch Aluminum Fitter + Frosted Opal Plastic Lens Cover Easy – Safe Installation 4W SMD LED 360LM	Dry Location
FDR4W-xxx	12	4	SunStar 4.5 Inch Flushmount, Damp Location Aluminum Fitter + Frosted Opal Plastic Lens Cover Easy – Safe Installation 4W SMD LED 360LM	Damp Location
FDR4SW-xxx	12	4	SunStar 4.5 Inch Flushmount w/Switch, Damp Location Aluminum Fitter + Frosted Opal Plastic Lens Cover Easy – Safe Installation 4W SMD LED 360LM	Damp Location
Note: 'xxx' or "xxxxx" may be any set of number used by manufacturer to signify non-critical differences between models such as color and finish or retail package ways.				

Notes: Devices included in this listing are for use in Recreational Vehicles only. Final acceptance of those devices in the recreational vehicle is subject to inspection by the Recreational Vehicle Certifier.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warrantee is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.
