

BUILDING PRODUCTS LISTING PROGRAM

Customer: Wildhawk Investments, LLC dba Brava Roof Tile
Class: Plastic Roof Tiles
Location: 915 E. Tyler Street, Washington, IA
Website: www.bravarooftile.com

Listing No. B1138
Project No. B1138-1 Edition 1
Effective Date: August 30 ,2022
Last Revised Date: August 30, 2022
Expires: <N/A>

Standards: ASTM E108 *Standard Test Methods for Fire Tests of Roof Coverings.*
UL 790 *Standard Test Methods for Fire Tests of Roof Coverings.*
UL 2218 *Impact Resistance of Prepared Roof Covering Materials.*

Products: Brava Roof Tile roof coverings are polymeric products available in the following models:

- Old World Slate
- Cedar Shake
- Spanish Barrel Tile

Markings: Listed products are identified with the following information:

- Address of manufacture
- Product Name
- Date of Manufacture
- Standards "UL2218", "ASTM E108" or "UL 790"
- QAI logo shown here:

Ratings: The following outlines roof-fire classified assemblies determined in accordance with ASTM E108 / UL 790 and UL 2218:

Assembly 1: Class A Roofing Applications: Unlimited Slope

SHEATHING	UNDERLAYMENT	APPROVED ROOF COVERING(s)	Maximum Exposure (inches)
Minimum 15/32" (12mm) Exposure 1 Plywood	1 layer of ASTM D226 Type II asphalt felt, with joints overlapped minimum inches (152 mm).	Old World Slate Class A Cedar Shake Class A Spanish Barrel Tile Class A	10 10 13.5

Assembly 2: Class C Roofing Applications: Unlimited Slope

SHEATHING	UNDERLAYMENT ¹	APPROVED ROOF COVERING(s) ²	Maximum Exposure (inches)
Minimum 15/32" (12mm) Exposure 1 Plywood	1 layer of ASTM D226 Type II asphalt felt, with joints overlapped minimum inches (152 mm).	Old World Slate Class C Cedar Shake Class C Spanish Barrel Tile Class C	10 10 13.5

Assembly 3: Impact Resistant (Class 4) Applications: Unlimited Slope

SHEATHING	UNDERLAYMENT ¹	APPROVED ROOF COVERING(s) ²	Maximum Exposure (inches)
Minimum 15/32" (12 mm) Exposure 1 Plywood	Unrestricted	Old World Slate Class A Cedar Shake Class A Spanish Barrel Tile Class A	10 10 13.5
		Old World Slate Class C Cedar Shake Class C Spanish Barrel Tile Class C	10 10 13.5

Note 1: Underlayment components are to be installed in accordance with the manufacturer's published installation instructions.

Note 2: These products are listed and labeled under QAI's certification program.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.
