

VANCOUVER, BC: LOS ANGELES, CA: WASHINGTON, DC: TULSA, OK: TORONTO, ON SEATTLE, WA WERSITE-

877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 540.636.9445 ph. | 540.636.9414 fx. 918.437.8333 ph. | 918.437.8487 fx. 905.605.5444 425.512.8419

WWW.QAI.ORG

BUILDING PRODUCTS LISTING PROGRAM

Customer: BASF Polyurethane Foam Enterprises LLC

Class: Thermal Insulation Location: Houston, TX

Website: www.polyurethanes.basf.us

Listing No. B1013-1

Project No. B1013-1 Edition 2

Effective Date: November 31, 2009 Last Revised Date: October 20, 2017

Standards: ASTM E84 Standard Test Method for Surface Burning Characteristics of

Building Materials

Product: Foam Plastic Insulation

Markings: Products are marked in a permanent manner where it is readily visible after

installation with the following:

a) Manufacturers name or recognized trademark

b) Product Model Designation

c) Date of Manufacture

d) QAI file number: B1013

e) ASTM E84 Flame Spread Index and Smoke Developed Index

f) QAI logo shown here:





VANCOUVER, BC: LOS ANGELES, CA: WASHINGTON, DC: TULSA, OK: TORONTO, ON SEATTLE, WA WERSITE- 877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 540.636.9445 ph. | 540.636.9414 fx. 918.437.8333 ph. | 918.437.8487 fx. 905.605.5444 425.512.8419

WWW.QAI.ORG

Models: The following outlines the performance of the BASF Polyurethane Foam Plastic Insulation determined in accordance with the noted standards:

BASF Surface Burning Characteristics per ASTM E84:

Model(s)	Flame Spread Index	Smoke Developed Index	Thickness Max. (inches)
Walltite 200	25	350	4
Spraytite 178	25	350	4
Spraytite 180	25	400	4
Spraytite 181	25	450	4
Spraytite 182	25	400	4
Spraytite 190	25	300	2
Spraytite 191	25	250	2
Spraytite 191	25	300	3
Spraytite 81206	25	350	4
Comfort Foam CF178	25	350	4
Walltite	25	350	4
Spraytite 81207	25	300	2

Notes: Products are subjected to limitations as specified above and must be installed in accordance with the manufacturer's instructions. Authorities having jurisdiction should be consulted regarding allowable applications.

Listed manufacturers are subject to on-going inspections by QAI to ensure that the products outlined above remains as it is listed.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warrantee is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.
