

FENESTRATION LISTING PROGRAM

Customer: Window Pro Inc.
Class: Fenestration Products – Energy Performance
Location: Etobicoke, ON
Website: <https://windowprocanada.com/>
Listing No. W510
Report No. W510-1 ED7
Effective Date: March 14, 2014
Last Revised Date: June 3, 2021
Expires: <N/A>
Standards: CSA A440.2 “Fenestration Energy Performance”
Product: Vinyl Windows
Markings: Products are marked in a permanent manner where it is readily visible after installation with the following:
a) Manufacturer’s name or trademark
b) QAI file Number: W510
c) Evaluation for energy performance only to CSA A440.2.
d) Évaluation pour le performance d’énergie seulement a CSA A440.2.
e) QAI logo shown here:



Models / Ratings: See following page.

L Series Casement Window

Model Code (Glass Option)	Window U-Value (W/m ² K)	Energy Rating (ER)
CAS_IS_3mm_ClrCard-Arg90-Card180#3-Arg90-ClrCard	1.24	36
CAS_IS_3mm_ClrCard-Arg90-Card180#3-Arg90-ClrCard_Grids<1"	1.24	34
CAS_IS_3mm_Card180#2-Arg90-ClrCard-Arg90-Card180#5	1.02	38
CAS_IS_3mm_Card180#2-Arg90-ClrCard-Arg90-Card180#5_Grids<1"	1.02	36
CAS_IS_4mm_Card180#2-Arg90-ClrCard-Arg90-Card180#5	1.07	36
CAS_IS_4mm_Card180#2-Arg90-ClrCard-Arg90-Card180#5_Penc	1.07	35
CAS_IS_4mm_Card180#2-Arg90-ClrCard-Arg90-Card180#5_Rect3/8	1.08	34
CAS_IS_4mm_Card180#2-Arg90-ClrCard-Arg90-Card180#5_Rect5/8	1.08	34
CAS_IS_3mm_Card180#2-Arg90-Card180#4-Arg90-i89#6	0.95	39
CAS_IS_3mm_Card180#2-Arg90-Card180#4-Arg90-i89#6_Grids<1"	0.95	39
CAS_IS_4mm_Card180#2-Arg90-Card180#4-Arg90-i89#6	0.99	37
CAS_IS_4mm_Card180#2-Arg90-Card180#4-Arg90-i89#6_Penc	0.99	35
CAS_IS_4mm_Card180#2-Arg90-Card180#4-Arg90-i89#6_Rect3/8	1.00	35
CAS_IS_4mm_Card180#2-Arg90-Card180#4-Arg90-i89#6_Rect5/8	1.00	35
CAS_ED_3mm_180-Arg90-i89	1.31	34
CAS_ED_4mm_180-Arg90-i89	1.30	34
CAS_ED_3mm_clrCGI-Arg90-366-Arg90-clrCGI	1.15	25
CAS_ED_4mm_clrCGI-Arg90-366-Arg90-clrCGI	1.17	25

L Series Awning Window

Model Code (Glass Option)	Window U-Value (W/m ² K)	Energy Rating (ER)
AWN_ED_3mm_ClrCard-Arg90-Card180#3-Arg90-ClrCard	1.22	35
AWN_ED_3mm_ClrCard-Arg90-Card180#3-Arg90-ClrCard_Grids<1"	1.22	34
AWN_ED_3mm_Card180#2-Arg90-ClrCard-Arg90-Card180#5	1.01	38
AWN_ED_3mm_Card180#2-Arg90-ClrCard-Arg90-Card180#5_Grids<1"	1.01	36
AWN_ED_4mm_Card180#2-Arg90-ClrCard-Arg90-Card180#5	1.04	36
AWN_ED_4mm_Card180#2-Arg90-ClrCard-Arg90-Card180#5_Penc	1.04	35
AWN_ED_4mm_Card180#2-Arg90-ClrCard-Arg90-Card180#5_Rect3/8	1.04	35
AWN_ED_4mm_Card180#2-Arg90-ClrCard-Arg90-Card180#5_Rect5/8	1.04	35
AWN_ED_3mm_ClrCard-Arg90-D89#3	1.41	35
AWN_ED_3mm_ClrCard-Arg90-D89#3_Grids<1"	1.41	32
AWN_ED_3mm_180-Arg90-i89	1.35	33
AWN_ED_4mm_180-Arg90-i89	1.35	32
AWN_ED_3mm_clrCGI-Arg90-366-Arg90-clrCGI	1.15	25
AWN_ED_4mm_clrCGI-Arg90-366-Arg90-clrCGI	1.17	24

L Series Low Fixed Frame Window

Model Code (Glass Option)	Window U-Value (W/m ² K)	Energy Rating (ER)
LF_ED_3MM_CLRCARD-ARG90-CARD180#3	1.56	40
LF_IS_4mm_ClrCard-Arg90-Card180#3-Arg90-ClrCard_Penc	1.20	45
LF_IS_4mm_ClrCard-Arg90-Card180#3 Arg90-ClrCard Rect5/8	1.20	42
LF_ED_3MM_CLRCARD-ARG90-CARD180#3-ARG90-CLRCARD	0.91	48
LF_ED_3MM_CLRCARD-ARG90-CARD180#3-ARG90-CLRCARD_GRIDS<1	0.91	45
LF_ED_3MM_180#2-ARG90-CLRCARD-ARG90-CARD180#5	0.95	46
LF_ED_3MM_180#2-ARG90-CLRCARD-ARG90-CARD180#5_GRIDS<1	0.95	43
LF_ED_4MM_180#2-ARG90-CLRCARD-ARG90-CARD180#5	0.96	43
LF_ED_4MM_180#2-ARG90-CLRCARD-ARG90-CARD180#5_PENC	0.96	43
FL_ED_3mm_180-Arg90-i89	1.28	43
FL_ED_4mm_180-Arg90-i89	1.27	42
FL_ED_3mm_clrCGI-Arg90-366-Arg90-clrCGI	1.09	31
FL_ED_4mm_clrCGI-Arg90-366-Arg90-clrCGI	1.11	30

L Series High Fixed Frame Window

Model Code (Glass Option)	Window U-Value (W/m ² K)	Energy Rating (ER)
HF_ED_3MM_CLRCARD-ARG90-CARD180#3-ARG90-CLRCARD	1.20	41
HF_ED_3MM_CLRCARD-ARG90-CARD180#3-ARG90-CLRCARD_GRIDS<1	1.20	39
HF_ED_3MM_180#2-ARG90-CLRCARD-ARG90-CARD180#5	0.94	44
HF_ED_3MM_180#2-ARG90-CLRCARD-ARG90-CARD180#5_GRIDS<1	0.94	42
HF_ED_4MM_180#2-ARG90-CLRCARD-ARG90-CARD180#5	0.97	43
HF_ED_4MM_180#2-ARG90-CLRCARD-ARG90-CARD180#5_PENC	0.97	40
HF_ED_4MM_180#2-ARG90-CLRCARD-ARG90-CARD180#5_RECT3/8	0.99	40
HF_ED_4MM_180#2-ARG90-CLRCARD-ARG90-CARD180#5_RECT5/8	0.99	40
HL_ED_3mm_180-Arg90-i89	1.28	40
HL_ED_4mm_180-Arg90-i89	1.26	39
HL_ED_3mm_clrCGI-Arg90-366-Arg90-clrCGI	1.11	28
HL_ED_4mm_clrCGI-Arg90-366-Arg90-clrCGI	1.12	29

L Series Single Slider Lift Out Window

Model Code (Glass Option)	Window U-Value (W/m ² K)	Energy Rating (ER)
SSLO_ED_3MM_CARD180#2-ARG90-i89#4	1.42	35
SSLO_ED_3MM_CARD180#2-ARG90-i89#4_GRIDS<1	1.42	32
SSLO_ED_4MM_CARD180#2-ARG90-i89#4	1.41	34
SSLO_ED_4MM_CARD180#2-ARG90-i89#4_GRIDS<1	1.41	31

L Series Single Slider Tilt Window

Model Code (Glass Option)	Window U-Value (W/m ² K)	Energy Rating (ER)
SST_ED_3MM_CARD180#2-ARG90-i89#4	1.42	35
SST_ED_3MM_CARD180#2-ARG90-i89#4_GRIDS<1	1.42	32
SST_ED_4MM_CARD180#2-ARG90-i89#4	1.41	34
SST_ED_4MM_CARD180#2-ARG90-i89#4_GRIDS<1	1.41	31

L Series Single Hung Tilt Window

Model Code (Glass Option)	Window U-Value (W/m ² K)	Energy Rating (ER)
SHT_ED_3MM_CARD180#2-ARG90-i89#4	1.41	36
SHT_ED_3MM_CARD180#2-ARG90-i89#4_GRIDS<1	1.41	33
SHT_ED_4MM_CARD180#2-ARG90-i89#4	1.40	36
SHT_ED_4MM_CARD180#2-ARG90-i89#4_GRIDS<1	1.40	33

L Series Double Hung Tilt Window

Model Code (Glass Option)	Window U-Value (W/m ² K)	Energy Rating (ER)
DHT_ED_3MM_CARD180#2-ARG90-i89#4	1.42	35
DST_ED_3MM_CARD180#2-ARG90-i89#4_GRIDS<1	1.42	32
DST_ED_4MM_CARD180#2-ARG90-i89#4	1.41	35
DST_ED_4MM_CARD180#2-ARG90-i89#4_GRIDS<1	1.41	32

L Series Double Slider Tilt Window

Model Code (Glass Option)	Window U-Value (W/m ² K)	Energy Rating (ER)
DST_ED_3MM_CARD180#2-ARG90-i89#4	1.42	33
DST_ED_3MM_CARD180#2-ARG90-i89#4_GRIDS<1	1.42	31
DST_ED_4MM_CARD180#2-ARG90-i89#4	1.40	33
DST_ED_4MM_CARD180#2-ARG90-i89#4_GRIDS<1	1.40	30
DST_ED_3mm_ClrCard-Arg90-D89#3	1.50	35
DST_ED_3mm_ClrCard-Arg90-D89#3_Grids<1"	1.50	32
DST_ED_3mm_ClrCard-Arg90-ClrCard-Arg90-CARD180#5	1.58	29

L Series Double Slider Lift Out Window

Model Code (Glass Option)	Window U-Value (W/m ² K)	Energy Rating (ER)
DSLO_ED_3MM_CARD180#2-ARG90-i89#4	1.42	34
DSLO_ED_3MM_CARD180#2-ARG90-i89#4_GRIDS<1	1.42	31
DSLO_ED_4MM_CARD180#2-ARG90-i89#4	1.40	34
DSLO_ED_4MM_CARD180#2-ARG90-i89#4_GRIDS<1	1.40	31

L Series End Vent (Triple) Slider Tilt Window

Model Code (Glass Option)	Window U-Value (W/m ² K)	Energy Rating (ER)
EVS_ED_3MM_CARD180#2-ARG90-i89#4	1.43	35
EVS_ED_3MM_CARD180#2-ARG90-i89#4_GRIDS<1	1.43	32
EVS_ED_4MM_CARD180#2-ARG90-i89#4	1.41	35
EVS_ED_4MM_CARD180#2-ARG90-i89#4_GRIDS<1	1.41	32

Notes: Listed products meet the energy requirements of the standards listed above. Windows are not intended for installation in storefronts, non-operable portions of curtain wall, fixed glazing cast into precast concrete panels, greenhouses, skylights or sloped glazing. Test procedures are designed to test the performance of the test specimen only and are not necessarily used to test the performance of the installation, particularly the perimeter sealant joint and anchoring of the assembly.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.
