

WINDOWS & DOORS LISTING PROGRAM

Customer: Super Windows Ltd. DBA Silverline Exterior Solutions
Class: Fenestration Products – Energy Performance
Location: Port Coquitlam, British Columbia
Website: www.silverlineexteriors.com

Listing No. W470-1
Project No. W470-1 ED4
Effective Date: January 13, 2011
Last Revised Date: September 15, 2022
Expires: N/A

Standards: CSA A440.2-19 “Fenestration Energy Performance”

Product: Vinyl Windows

Markings: Products are marked with the following content in a permanent manner where it is readily visible after installation:

- a) Manufacturer’s name, Trademark or other recognized symbol or identification.
- b) QAI file Number: W470
- c) QAI logo shown here:



- d) “Evaluation for energy performance in accordance with CSA A440.2” / “Évalué pour la performance d’énergie en accord à la norme CSA A440.2”

Models / Ratings:

2000 Series Picture Window

Glass / Grille Option #	Model Code	U-Value (W/m ² K)	Product SHGC	Energy Rating
G01	SLIN-2000-PC-3,SB60(2)-3,CL-12AR95CU	1.51	0.33	26
G02	SLIN-2000-PC-3,SB70(2)-3,CL-12AR95CU	1.48	0.23	20
G03	SLIN-2000-PC-3,SB60(2)-3,IS20(4)-12AR95CU	1.30	0.32	30
G04	SLIN-2000-PC-4,SB60(2)-4,CL-12AR95CU	1.51	0.32	25
G05	SLIN-2000-PC-4,SB70(2)-4,CL-12AR95CU	1.48	0.23	20

Glass / Grille Option #	Model Code	U-Value (W/m ² K)	Product SHGC	Energy Rating
G06	SLIN-2000-PC-4,SB60(2)-4,IS20(4)-12AR95CU	1.31	0.32	29
G07	SLIN-2000-PC-3,SB60(2)-7,I2LM(4)-10AR95CU	1.34	0.32	29
G08	SLIN-2000-PC-4,SB60(2)-7,I2LM(4)-10AR95CU	1.34	0.31	28
G09	SLIN-2000-PC-3,SB60(2)-3,I89(4)-12AR95CU	1.28	0.32	30
G10	SLIN-2000-PC-4,SB60(2)-4,I89(4)-12AR95CU	1.29	0.32	30
G11	SLIN-2000-PC-5,SB60(2)-5,I89(4)-10AR95CU	1.34	0.32	29

2000 Series Single Sliding Window

Glass / Grille Option #	Model Code	U-Value (W/m ² K)	Product SHGC	Energy Rating
G01	SLIN-2000-SS-3,SB60(2)-3,CL-12AR95CU	1.58	0.31	23
G02	SLIN-2000-SS-3,SB70(2)-3,CL-12AR95CU	1.55	0.22	18
G03	SLIN-2000-SS-3,SB60(2)-3,IS20(4)-12AR95CU	1.38	0.30	27
G04	SLIN-2000-SS-4,SB60(2)-4,CL-12AR95CU	1.59	0.31	22
G05	SLIN-2000-SS-4,SB70(2)-4,CL-12AR95CU	1.56	0.22	18
G06	SLIN-2000-SS-4,SB60(2)-4,IS20(4)-12AR95CU	1.40	0.30	26
G07	SLIN-2000-SS-3,SB60(2)-7,I2LM(4)-10AR95CU	1.43	0.30	25
G08	SLIN-2000-SS-3,SB60(2)-3,I89(4)-12AR95CU	1.38	0.31	27
G09	SLIN-2000-SS-4,SB60(2)-4,I89(4)-12AR95CU	1.39	0.30	26

2000 Series Single Hung Window

Glass / Grille Option #	Model Code	U-Value (W/m ² K)	Product SHGC	Energy Rating
G01	SLIN-2000-SH-3,SB60(2)-3,CL-12AR95CU	1.58	0.31	22
G02	SLIN-2000-SH-3,SB70(2)-3,CL-12AR95CU	1.55	0.22	18
G03	SLIN-2000-SH-3,SB60(2)-3,IS20(4)-12AR95CU	1.38	0.30	26
G04	SLIN-2000-SH-3,SB60(2)-7,I2LM(4)-10AR95CU	1.43	0.30	25
G05	SLIN-2000-SH-3,SB60(2)-3,I89(4)-12AR95CU	1.37	0.31	27

4000 Series Picture Window

Glass / Grille Option #	Model Code	U-Value (W/m ² K)	Product SHGC	Energy Rating
G01	SLIN-4000-PC-3,SB60(2)-3,CL-14AR95CU	1.46	0.33	27
G02	SLIN-4000-PC-3,SB70(2)-3,CL-14AR95CU	1.43	0.22	21
G03	SLIN-4000-PC-3,SB60(2)-3,IS20(4)-14AR95CU	1.24	0.32	31

Glass / Grille Option #	Model Code	U-Value (W/m ² K)	Product SHGC	Energy Rating
G04	SLIN-4000-PC-4,SB60(2)-4,CL-12AR95CU	1.44	0.33	28
G05	SLIN-4000-PC-4,SB70(2)-4,CL-12AR95CU	1.41	0.23	22
G06	SLIN-4000-PC-4,SB60(2)-4,IS20(4)-12AR95CU	1.23	0.32	32
G07	SLIN-4000-PC-5,SB60(2)-5,CL-12AR95CU	1.44	0.32	27
G08	SLIN-4000-PC-5,SB70(2)-5,CL-12AR95CU	1.41	0.22	22
G09	SLIN-4000-PC-3,SB70(2)-6,CLLM-12AR95CU	1.40	0.22	22
G10	SLIN-4000-PC-4,SB70(2)-6,CLLM-12AR95CU	1.40	0.22	22
G11	SLIN-4000-PC-3,SB70(2)-3,IS20(4)-14AR95CU	1.22	0.22	26
G12	SLIN-4000-PC-4,SB70(2)-4,IS20(4)-12AR95CU	1.20	0.22	26
G13	SLIN-4000-PC-3,SB60(2)-3,I89(4)-14AR95CU	1.23	0.32	32
G14	SLIN-4000-PC-4,SB60(2)-4,I89(4)-12AR95CU	1.22	0.32	32
G15	SLIN-4000-PC-5,SB60(2)-5,I89(4)-12AR95CU	1.22	0.32	32
G16	SLIN-4000-PC-6,SB60(2)-6,I89(4)-10AR95CU	1.27	0.31	30
G17	SLIN-4000-PC-3,SB70(2)-3,I89(4)-14AR95CU	1.21	0.21	26
G18	SLIN-4000-PC-4,SB70(2)-4,I89(4)-12AR95CU	1.20	0.22	26

4000 Series Casement Window

Glass / Grille Option #	Model Code	U-Value (W/m ² K)	Product SHGC	Energy Rating
G01	SLIN-4000-CA-3,SB60(2)-3,CL-14AR95CU	1.55	0.25	20
G02	SLIN-4000-CA-3,SB70(2)-3,CL-14AR95CU	1.52	0.17	16
G03	SLIN-4000-CA-3,SB60(2)-3,IS20(4)-14AR95CU	1.38	0.24	23
G04	SLIN-4000-CA-3,SB70(2)-6,CLLM-12AR95CU	1.51	0.17	17
G05	SLIN-4000-CA-3,SB60(2)-3,I89(4)-14AR95CU	1.41	0.25	23
G06	SLIN-4000-CA-3,SB70(2)-3,I89(4)-14AR95CU	1.39	0.17	19

4000 Series Awning Window

Glass / Grille Option #	Model Code	U-Value (W/m ² K)	Product SHGC	Energy Rating
G01	SLIN-4000-AW-3,SB60(2)-3,CL-14AR95CU	1.55	0.25	20
G02	SLIN-4000-AW-3,SB70(2)-3,CL-14AR95CU	1.52	0.17	16
G03	SLIN-4000-AW-3,SB60(2)-3,IS20(4)-14AR95CU	1.39	0.24	23
G04	SLIN-4000-AW-3,SB70(2)-6,CLLM-12AR95CU	1.51	0.17	17
G05	SLIN-4000-AW-3,SB60(2)-3,I89(4)-14AR95CU	1.42	0.25	23
G06	SLIN-4000-AW-3,SB70(2)-3,I89(4)-14AR95CU	1.40	0.17	19

Notes:

- Products are not intended for installation in storefronts, non-operable portions of curtain wall, fixed glazing cast into precast concrete panels, greenhouses, skylights or sloped glazing.
- Test procedures are designed to test the performance of the test specimen only and are not necessarily used to test the performance of the installation, particularly the perimeter sealant joint and anchoring of the assembly.
- The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI.
- No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing.
- Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.