



WINDOWS & DOORS LISTING PROGRAM

Customer: Window Pro Inc.
Class: Fenestration Products – Energy Performance
Location: Mississauga, Ontario
Website: www.windowprocanada.com

Listing No. W510-1
Project No. W510-1 ED10
Effective Date: March 14, 2014
Last Revised Date: November 14, 2023
Expires: N/A

Standards: CSA A440.2 “Fenestration Energy Performance”

Product: Vinyl Windows

Markings: Products are marked with the following content in a permanent manner where it is readily visible after installation:

- a) Manufacturer’s name, Trademark or other recognized symbol or identification.
- b) QAI file Number: W510
- c) QAI logo shown here:



- d) “Evaluation for energy performance in accordance with CSA A440.2” / “Évalué pour la performance d’énergie en accord à la norme CSA A440.2”

Models / Ratings:

L Series Low Fixed Frame Window

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	WPR-LPC-4,180(2)-4,i89(4)-13AR90EN	1.27	0.52	42
G02	WPR-LPC-3,CL-3,366(4)-3,CL-13AR90EN	1.09	0.25	31
G03	WPR-LPC-4,CL-4,366(4)-4,CL-12AR90EN	1.11	0.25	30
G04	WPR-LPC-4,CL-4,180(3)-12AR90EN	1.53	0.56	39
G05	WPR-LPC-3,180(2)-3,i89(4)-15AR90EN	1.29	0.54	43



Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G06	WPR-LPC-3,CL-3,180(3)-15AR90EN	1.56	0.59	40
G07	WPR-LPC-3,CL-3,180(3)-3,CL-13AR90EN	1.19	0.54	45
G08	WPR-LPC-3,CL-3,180(3)-3,CL-13AR90EN-G1<1	1.19	0.49	42
G09	WPR-LPC-4,CL-4,180(3)-4,CL-12AR90EN	1.20	0.53	44
G10	WPR-LPC-4,CL-4,180(3)-4,CL-12AR90EN-G1<1	1.23	0.48	41
G11	WPR-LPC-3,180(2)-3,CL-3,180(5)-13AR90EN	0.91	0.48	48
G12	WPR-LPC-3,180(2)-3,CL-3,180(5)-13AR90EN-G1<1	0.91	0.43	45
G13	WPR-LPC-4,180(2)-4,CL-4,180(5)-12AR90EN	0.93	0.47	47
G14	WPR-LPC-4,180(2)-4,CL-4,180(5)-12AR90EN-G1<1	0.94	0.42	44

L Series High Fixed Frame Window

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	WPR-LFC-4,180(2)-4,i89(4)-13AR90EN	1.26	0.46	39
G02	WPR-LFC-3,CL-3,366(4)-3,CL-13AR90EN	1.11	0.22	28
G03	WPR-LFC-4,CL-4,366(4)-4,CL-12AR90EN	1.12	0.23	29
G04	WPR-LFC-4,CL-4,180(3)-12AR90EN	1.50	0.50	36
G05	WPR-LFC-3,180(2)-3,i89(4)-15AR90EN	1.28	0.48	40
G06	WPR-LFC-3,CL-3,180(3)-15AR90EN	1.52	0.52	37
G07	WPR-LFC-3,CL-3,180(3)-3,CL-13AR90EN	1.19	0.48	42
G08	WPR-LFC-3,CL-3,180(3)-3,CL-13AR90EN-G1<1	1.19	0.43	39
G09	WPR-LFC-4,CL-4,180(3)-4,CL-12AR90EN	1.20	0.47	41
G10	WPR-LFC-4,CL-4,180(3)-4,CL-12AR90EN-G1<1	1.23	0.42	37
G11	WPR-LFC-3,180(2)-3,CL-3,180(5)-13AR90EN	0.94	0.43	44
G12	WPR-LFC-3,180(2)-3,CL-3,180(5)-13AR90EN-G1<1	0.94	0.39	42
G13	WPR-LFC-4,180(2)-4,CL-4,180(5)-12AR90EN	0.96	0.42	43
G14	WPR-LFC-4,180(2)-4,CL-4,180(5)-12AR90EN-G1<1	0.97	0.37	40

L Series Casement Window

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	WPR-LCA-4,180(2)-4,i89(4)-13AR90EN	1.30	0.39	34
G02	WPR-LCA-3,CL-3,366(4)-3,CL-13AR90EN	1.15	0.19	25
G03	WPR-LCA-4,CL-4,366(4)-4,CL-12AR90EN	1.17	0.19	25
G04	WPR-LCA-4,CL-4,180(3)-12AR90EN	1.49	0.43	32
G05	WPR-LCA-3,180(2)-3,i89(4)-15AR90EN	1.31	0.40	34
G06	WPR-LCA-3,CL-3,180(3)-15AR90EN	1.51	0.44	32
G07	WPR-LCA-3,CL-3,180(3)-3,CL-13AR90EN	1.21	0.41	37
G08	WPR-LCA-3,CL-3,180(3)-3,CL-13AR90EN-G1<1	1.21	0.37	34
G09	WPR-LCA-4,CL-4,180(3)-4,CL-12AR90EN	1.22	0.40	36
G10	WPR-LCA-4,CL-4,180(3)-4,CL-12AR90EN-G1<1	1.24	0.36	33
G11	WPR-LCA-3,180(2)-3,CL-3,180(5)-13AR90EN	1.00	0.36	38



Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G12	WPR-LCA-3,180(2)-3,CL-3,180(5)-13AR90EN-G1<1	1.00	0.33	37
G13	WPR-LCA-4,180(2)-4,CL-4,180(5)-12AR90EN	1.02	0.35	37
G14	WPR-LCA-4,180(2)-4,CL-4,180(5)-12AR90EN-G1<1	1.03	0.32	36

L Series Awning Window

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	WPR-LAW-4,180(2)-4,i89(4)-13AR90EN	1.35	0.39	32
G02	WPR-LAW-3,CL-3,366(4)-3,CL-13AR90EN	1.15	0.19	25
G03	WPR-LAW-4,CL-4,366(4)-4,CL-12AR90EN	1.17	0.19	24
G04	WPR-LAW-4,CL-4,180(3)-12AR90EN	1.50	0.43	31
G05	WPR-LAW-3,180(2)-3,i89(4)-15AR90EN	1.34	0.40	33
G06	WPR-LAW-3,CL-3,180(3)-15AR90EN	1.53	0.44	31
G07	WPR-LAW-3,CL-3,180(3)-3,CL-13AR90EN	1.21	0.41	36
G08	WPR-LAW-3,CL-3,180(3)-3,CL-13AR90EN-G1<1	1.21	0.37	34
G09	WPR-LAW-4,CL-4,180(3)-4,CL-12AR90EN	1.23	0.40	35
G10	WPR-LAW-4,CL-4,180(3)-4,CL-12AR90EN-G1<1	1.24	0.36	33
G11	WPR-LAW-3,180(2)-3,CL-3,180(5)-13AR90EN	1.00	0.36	38
G12	WPR-LAW-3,180(2)-3,CL-3,180(5)-13AR90EN-G1<1	1.00	0.33	36
G13	WPR-LAW-4,180(2)-4,CL-4,180(5)-12AR90EN	1.02	0.35	37
G14	WPR-LAW-4,180(2)-4,CL-4,180(5)-12AR90EN-G1<1	1.03	0.32	35

L Series Single Sliding Tilt Window

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	WPR-LSST-3,180(2)-3,i89(4)-15AR90EN	1.44	0.48	35
G02	WPR-LSST-3,CL-3,180(3)-15AR90EN	1.68	0.53	32
G03	WPR-LSST-3,CL-3,366(3)-15AR90EN	1.60	0.30	21

L Series Single Sliding Lift-Out Window

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	WPR-LSSL-3,180(2)-3,i89(4)-15AR90EN	1.43	0.48	34
G02	WPR-LSSL-3,CL-3,180(3)-15AR90EN	1.68	0.53	32



Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G03	WPR-LSSL-3,CL-3,366(3)-15AR90EN	1.60	0.30	20

L Series Double Sliding Tilt Window

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	WPR-LDST-3,180(2)-3,i89(4)-15AR90EN	1.43	0.47	33
G02	WPR-LDST-3,CL-3,180(3)-15AR90EN	1.67	0.52	31
G03	WPR-LDST-3,CL-3,366(3)-15AR90EN	1.59	0.30	20

L Series Double Sliding Lift-Out Window

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	WPR-LDSL-3,180(2)-3,i89(4)-15AR90EN	1.42	0.47	34
G02	WPR-LDSL-3,CL-3,180(3)-15AR90EN	1.66	0.52	32
G03	WPR-LDSL-3,CL-3,366(3)-15AR90EN	1.58	0.30	21

L Series Single Hung Window

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	WPR-LSH-3,180(2)-3,i89(4)-15AR90EN	1.43	0.48	35
G02	WPR-LSH-4,180(2)-4,i89(4)-13AR90EN	1.41	0.47	35

L Series Double Hung Window

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	WPR-LDH-3,180(2)-3,i89(4)-15AR90EN	1.43	0.47	34
G02	WPR-LDH-4,180(2)-4,i89(4)-13AR90EN	1.41	0.46	34



Notes:

- Products are not intended for installation in storefronts, non-operable portions of curtain wall, fixed glazing cast into precast concrete panels, greenhouses, skylights or sloped glazing.
- Test procedures are designed to test the performance of the test specimen only and are not necessarily used to test the performance of the installation, particularly the perimeter sealant joint and anchoring of the assembly.
- The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI.
- No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing.
- Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.