

VANCOUVER, BC: LOS ANGELES, CA: WASHINGTON, DC: TULSA, OK: TORONTO, ON SEATTLE, WA WERSITE 877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 540.636.9445 ph. | 540.636.9414 fx. 918.437.8343 ph. | 918.437.8487 fx. 905.605.5444 425.512.8419

WWW.QAI.ORG

## **ELECTRICAL LISTING PROGRAM**

Customer: ITC Inc.

Class: Lighting for use in Recreational Vehicles

Location: Hudsonville, MI, USA Website: http://www.itc-us.com/

Listing No. E10589

Report No. E10589-1501 Edition 7

Project No. E10589-2103 Effective Date: July 02, 2014 Last Revised February 10, 2023

Date:

Expires: N/A

Standards: CSA C22.2 No. 250.0 "Luminaires"

UL 234 "Low Voltage Lighting Fixtures for use in Recreational Vehicles"

Product: Recreational Vehicles Luminaires, Indoor & Outdoor use, permanently

connected.

Markings: Products are marked in a permanent manner where it is readily visible

after installation with the following:

a) Manufacturer's name or trademark

b) Model designation

c) Month and year of manufacture

d) Product ratings: voltage, frequency, watts

e) QAI file Number: E10589

f) The wording "Conforms to CSA C22.2 No. 250.0 and UL 234"

g) Warning markings as required by the standards in English and

French

h) QAI logo: CAA

Models / Ratings:

Model	Ratings	Description	Dry / Wet Locations
69231C-6xx12	12 VDC, 4W	3" Round Recessed	Dry
		Luminaire, 6LEDs	Locations
69231C-9xx12	12 VDC, 4W	3" Round Recessed	Dry
		Luminaire, 9LEDs	Locations
69240C-12xx12	12 VDC, 4W	4-1/2" Round Recessed	Dry
		Luminaire, 12LEDs	Locations
C0240C 45:0:42	12 VDC, 5W	4-1/2" Round Recessed	Dry
69240C-15xx12		Luminaire, 15LEDs	Locations
69240C-21xx12	12 VDC, 7W	4-1/2" Round Recessed	Dry
		Luminaire, 21LEDs	Locations
		3" Round Recessed	Dn.
69231CNS-6xx12	12 VDC, 4W	Luminaire, 6LEDs, No	Dry
	,	Spring	Locations



TORG SEA'

VANCOUVER, BC: 877.461.8378 ph. | 604.527.8368 fx. LOS ANGELES, CA: 909.483.0250 ph. | 909.483.0336 fx. WASHINGTON, DC: 540.636.9445 ph. | 540.636.9414 fx. TORONTO ON 1005.65644.918.437.8333 ph. | 918.437.8487 fx.

ONTO, ON	905.605.5444
TTLE, WA	425.512.8419
WEBSITE:	WWW.QAI.ORG
WEDSITE:	w w w.QAI.OKG

69231CNS-9xx12	12 VDC, 4W	3" Round Recessed Luminaire, 9LEDs No Spring	Dry Locations
69240CNS-12xx12	12 VDC, 4W	4-1/2" Round Recessed Luminaire, 12LEDs, No Spring	Dry Locations
69240CNS-15xx12	12 VDC, 5W	4-1/2" Round Recessed Luminaire, 15LEDs, No Spring	Dry Locations
69240CNS-21xx12	12 VDC, 7W	4-1/2" Round Recessed Luminaire, 21LEDs, No Spring	Dry Locations
69231CLS-6xx12	12 VDC, 4W	3" Round Recessed Luminaire, 6LEDs, Leaf Spring	Dry Locations
69231CLS-9xx12	12 VDC, 4W	3" Round Recessed Luminaire, 9LEDs, Leaf Spring	Dry Locations
69387Byxx-L&R	12-24VDC, 5W	RV Outdoor luminaire, 1 LED light	Wet Locations
Where: xx = (35) 3500k or y = (F) Flood or		LED colour temperature	
LED Porch Light:			
69767B-XX	12VDC/6W	Single LED Strip Porch Light, 1 colour	Wet Locations
69768B-XX	12VDC/6W	Dual LED Strip Porch Light, 2 colours	Wet Locations
69769B-XX	12VDC/6W	Dual LED Strip Porch Light, 2 colours	Wet Locations
Where: XX = CH, BK, WH	l only		
Vanity Light:	,		
59430-Uabcc0003	12VDC / 12W Max	2 Square LED Vanity, LED temp 3000k	Dry Locations
59460-Uabcc0002	12VDC / 4W Max	15" Long, Linear Strip LED Vanity, LED temp 3000k	Dry Locations
59050-z1bcc0003	12VDC / 3.2W Max	Candle LED Light	Dry Locations
Where: z = U or S ; a,b,co	:= A-Z or 0-9		
Linear Light, Storage C		ht:	
690261FE.16.KK.12	12VDC / 6W	Linear Light, Touch Switch, 403mm long	Dry Locations
690261FE.16.KK.12.U	12VDC / 10W	Linear Light, No Switch ,406mm long	Dry Locations
690261FE.16.KK.12SS	12VDC / 6.1W	Linear Light, Touch Switch, 403mm long.	Dry Locations
Where: KK is the LED Co KK = 30, 65 (whe			



VANCOUVER, BC: LOS ANGELES, CA: WASHINGTON, DC: TULSA, OK: TORONTO, ON SEATTLE, WA WERSITE: 877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 540.636.9445 ph. | 540.636.9414 fx. 918.437.8333 ph. | 918.437.8487 fx. 905.605.5444 425.512.8419

WWW.QAI.ORG

Docking Light:					
69389E-XX-L	10-24VDC / 0.33A @ 12V	RV Exterior luminaire, Surface Mount, LED, Left side	Wet Locations		
69389E-XX-R	10-24VDC / 0.33A @ 12V	RV Exterior luminaire, Surface Mount, LED, Right side	Wet Locations		
Where: XX = SS for stainless bezel, BS for brushed stainless bezel.					

## Notes:

- 1- Devices included in this listing are for use in Recreational Vehicles only. Final acceptance of those devices in the recreational vehicle is subject to inspection by the Recreational Vehicle Certifier.
- 2- ELV fixture to be connected to the secondary side of approval power supply Class 2 or similar certified / listed limited power supply sources, supply to be fused, 5A max.
- 3- Product is design for Interior Use Only.
- 4- Suitable for Dry, or Wet Locations as per model location designator.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warrantee is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at <a href="www.qai.org">www.qai.org</a> for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to <a href="mailto:info@qai.org">info@qai.org</a>. Please include the listing number in the request.

\*\*\*