

FIRE DOOR LISTING PROGRAM

Customer: Masonite Architectural
 Class: Fire Doors
 Location: London, Ontario
 Website: www.masonitearchitectural.com

Listing No. F424

Effective Date: April 22, 2016
 Last Revised: July 4, 2017

Standards: CAN/ULC-S104	<i>Standard Method for Fire Tests of Door Assemblies.</i>
UL 10(b)	<i>Fire Tests of Doors Assemblies.</i>
UL 10(c)	<i>Fire Tests of Doors Assemblies.</i>
NFPA 252	<i>Standard Methods of Fire Tests of Door Assemblies.</i>

Label: See [FD001 - Fire Door Labeling requirements](#)

Models / Ratings:	<u>Specification Owner:</u>	<u>Manufacturing/Machining Specifications:</u>	<u>Listing No.:</u>	<u>Criteria:</u>
	Masonite Architectural	20 minute Fire Rated Door	F424-1-20 - BASF Wood Core	CPL
	Masonite Architectural	20 minute Fire Rated Door	F424-1-20 - BASF Laminated Core	CPL
	Masonite Architectural	20 minute Fire Rated Door	F424-1-20 - 1-3/4" Thickness	CPL
	Masonite Architectural	20 minute Fire Rated Door	F424-1-20 - 2-1/4" Thickness	CPL
	Masonite Architectural	45 minute Fire Rated Door	F424-1-45 - BASF	CPL
	Masonite Architectural	60 minute Fire Rated Door	F424-1-60 - BASF	CPL
	Masonite Architectural	90 minute Fire Rated Door	F424-1-90 - BASF	CPL

<u>Specification Owner:</u>	<u>Manufacturing/Machining Specifications:</u>	<u>Listing No.:</u>	<u>Criteria:</u>
Masonite Architectural	20 minute Fire Rated Door Frame	F424-2-20 - BASF	CPL
Masonite Architectural	20 minute Fire Rated Door Frame	F424-2-20 - Harring Doors	CPL
Masonite Architectural	20 minute Fire Rated Door Frame	F424-2-20 - Warm Springs	CPL
Masonite Architectural	45 minute Fire Rated Door Frame	F424-2-45 - BASF	CPL
Masonite Architectural	45 minute Fire Rated Door Frame	F424-2-45 - Warm Springs	CPL
Masonite Architectural	60 minute Fire Rated Door Frame	F424-2-60 - BASF	CPL
Masonite Architectural	60 minute Fire Rated Door Frame	F424-2-60 - Warm Springs	CPL
Masonite Architectural	90 minute Fire Rated Door Frame	F424-2-90 - BASF	CPL
Masonite Architectural	90 minute Fire Rated Door Frame	F424-2-90 - Warm Springs	CPL



LABORATORIES

CERTIFICATION TESTING INSPECTION

VANCOUVER, BC: 877.461.8378 ph. | 604.527.8368 fx.
LOS ANGELES, CA: 909.483.0250 ph. | 909.483.0336 fx.
WASHINGTON, DC: 540.636.9445 ph. | 540.636.9414 fx.
TULSA, OK: 918.437.8333 ph. | 918.437.8487 fx.
TORONTO, ON: 416.550.9280
SEATTLE, WA: 425.512.8419
WEBSITE: WWW.QAI.ORG

Notes: *Refer to QAI evaluation report F424-1 and the applicable test reports for test assembly configurations used for fire endurance testing.*

Refer to the [QAI FD002 - Fire Door Guidelines for general guidelines of fire door assemblies](#)

Final acceptance of the product in the intended application is to be determined by the authority having jurisdiction (AHJ).

Product is to be installed in accordance with the manufacturer's published installation instructions by qualified installing personnel.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warrantee is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.
