

VANCOUVER, BC: LOS ANGELES, CA: WASHINGTON, DC: TULSA, OK: TORONTO, ON SEATTLE, WA WEBSITE:

877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 540.636.9445 ph. | 540.636.9414 fx. 918.437.8333 ph. | 918.437.8487 fx. 416.550.9280 425.512.8419

WWW.QAI.ORG

ELECTRICAL LISTING PROGRAM

Customer: Kendal Lighting (BC) Inc.

Class: Luminaires

Location: Delta, BC, Canada Website: kendallighting.com

Listing No. E10390

Report No. E10390-1601, Edition 2

Project E10390-1702

No.

Effective April 28, 2016

Date:

Last April 4th, 2017

Revised

Date:

Expires: N/A

Standards: CSA C22.2 No. 250.0 "Luminaires

UL 1598 "Luminaires"

Product: Luminaires, indoor use, permanently connected.

Vanity, pendant, and ceiling luminaires.

Markings: Products are marked in a permanent manner where it is readily visible after

installation with the following:

a) Manufacturer's name or trademark

- b) Model designation
- c) Month and year of manufacture
- d) Product ratings: voltage, frequency
- e) Product power; total ampere (LED) or lamp wattage (Halogen)
- f) QAI file Number: E10390
- g) The wording "Conforms to CSA C22.2 No. 250.0 & UL 1598"
- h) Warning markings as required by the standards in English and French
- QAI logo shown here:





VANCOUVER, BC: LOS ANGELES, CA: WASHINGTON, DC: TULSA, OK: TORONTO, ON SEATTLE, WA

WEBSITE:

877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 540.636.9445 ph. | 540.636.9414 fx. 918.437.8333 ph. | 918.437.8487 fx. 416.550.9280 425.512.8419

WWW.QAI.ORG

Models / Ratings:

Model #	Note	Voltage (V)	Freq. (Hz)	Wattage*, Bulb Type	Loc.
VF75xx-CH	xx = 18, 24, 30	120	60	(20W, 26W, 30W), Led	Dry
PF7536-CH	, ,	120	60	25W, Led	Dry
PFxx15SF-CH	xx = 75, 77, 78	120	60	(13W, 13W, 13W), Led	Dry
PF7613WL/FL- CH		120	60	24W, Led	Dry
PF76xx-CH	xx = 36, 46	120	60	(44W, 48W), Led	Dry
VF77xx-CH	xx = 18, 24, 30	120	60	(20W, 26W, 30W), Led	Dry
PF7740-CH		120	60	27W, Led	Dry
VF78xx-CH	xx = 18, 24, 30	120	60	(20W, 26W, 30W), Led	Dry
PF78xx-CH	xx = 36, 48	120	60	(25W, 29W), Led	Dry
PF81xx-CH	xx = 30, 42	120	60	(24W, 29W), Led	Dry
PF8114FL-CH		120	60	9W, Led	Dry
PF8112Wxx-CH	xx = LI, LO	120	60	(9W, 9W), Led	Dry
PF7913Wxx-CH	xx = LI, LO	120	60	(10W, 10W), Led	Dry
VF7400-xL-CH	x = 1, 2, 3, 4, 5	120	60	(1,2,3,4,5)x50W, G9	Dry
VF82xx-CH	xx = 15, 24, 30, 36	120	60	(13W, 38W, 45W, 57W), Led	Dry
VF9100-xL-yy	x = 1, 2, 3, 4, 5	120	60	(5W, 10W, 15W, 20W, 25W), Led	Dry
PF91-xLPA-yy	x = 3, 5, 9	120	60	(15W, 25W, 45W), Led	Dry
PF91-xLBR-yy	x = 3, 5	120	60	(15W, 25W), Led	Dry
PF91-1LPE-yy		120	60	5W, Led	Dry
PF87xx-yy	xx = 18, 24, 30	120	60	(32W, 41W, 50W), Led	Dry

Notes: Notes:

The final part number suffix, "-CH", "-xx", "-yy" or "-zz", refer to luminaire metallic plating and can be any of the following codes: "CH', "SN", "SN/SF", "SN/WH", "BST", "BLK", "MCH", "SB", "ORB", "PN", "BKS", or others as indicated elsewhere in this report. For further details of exact models with plating options see catalog pages attached. These are not safety related for the purposes of this report.

* Note: For all multiple wattages noted above; they are related to the corresponding 'x' model numbers directly.

ie, "... x = a,b,c ... (1,3,2)x50W", corresponds to the following: a = 1x50W; b = 3x50W; c = 2x50W.

ie, "... x = a,b,c ... (5W,10W,15W), Led", corresponds to the following a = 5W; b = 10W; c = 15W.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warrantee is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.

**