VANCOUVER, BC: LOS ANGELES, CA: WASHINGTON, DC: TULSA, OK: TORONTO, ON WEBSITE: 877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 540.636.9445 ph. | 540.636.9414 fx. 918.437.8333 ph. | 918.437.8487 fx. 416.550.9280 WWW.QALORG

## **BUILDING PRODUCTS LISTING PROGRAM**

Customer: G.E.M. Incorporated

Class: Roof Coverings Location: Calgary, Alberta

Website: www.euroshieldroofing.com

Listing No. B1092-1

Project No. B1092-1 Edition 3

Effective Date: June 10, 2016 Last Revised Date: February 28, 2019

Standards: ASTM E108 "Standard Test Methods for Fire Tests of Roof Coverings"

CAN/ULC S107 "Methods of Fire Tests of Roof Coverings"

UL 2218 "Standard for Impact Resistance of Prepared Roof Covering

Materials"

Product: Euroshield® Recycled Composite Roof Covering Products as outlined below:

- Harvest Shake
- Granville Slate
- Ranchlands Shake
- Rundle Slate
- Beaumont Shake

Markings: Product is marked with labels supplied by G.E.M. Incorporated. The label includes:

- a) Manufacturer's name
- b) Product name
- c) Date of manufacture
- d) QAI logo with 'c' and 'us' identifier
- e) QAI Listing number (B1092)
- f) CAN/ULC S107 and ASTM E108 Fire Classification (Class C)
- g) UL 2218 Impact Classification (Class IV)

Labels are applied to palletized finished products to ensure visibility on the jobsite.

VANCOUVER, BC: LOS ANGELES, CA: WASHINGTON, DC: TULSA, OK: TORONTO, ON WEBSITE: 877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 540.636.9445 ph. | 540.636.9414 fx. 918.437.8333 ph. | 918.437.8487 fx. 416.550.9280 WWW.QAI.ORG

Models / Ratings: G.E.M. Incorporated manufactures roof covering products in the following configurations and ratings:

## CAN/ULC S107 and ASTM E108 Class C Roofing Application: Unlimited slope

| Roof Covering<br>Product | Panel Dimensions |         |           |  |
|--------------------------|------------------|---------|-----------|--|
|                          | Width            | Height  | Thickness | Deck Assembly  |
| Harvest<br>Shake         | 40"              | 17"     | 1/2"      | Deck:  • Minimum 1/2" AC Exterior grade plywood  Underlayment:  • See Note 1 and 2  • One layer fastened to the test deck with 2" overlap at horizontal joints |
| Granville<br>Slate       | 40"              | 17"     | 3/8"      |  |
| Ranchlands<br>Shake      | 36"              | 22-1/2" | 3/4"      |  |
| Rundle<br>Slate          | 36"              | 22-1/2" | 3/4"      |  |
| Beaumont<br>Shake        | 40"              | 20"     | 1/2"      | Deck:  • Minimum 1/2" AC Exterior grade plywood  |
|                          |                  |         |           | <ul> <li>Underlayment:</li> <li>See Note 1 and 2</li> <li>One layer fastened to the test deck with 4" overlap at horizontal joints</li> </ul>                  |

## **UL 2218 Impact Resistant Class IV Roofing Application: Unlimited slope**

| Roof Covering<br>Product | Panel Dimensions |         |           |  |
|--------------------------|------------------|---------|-----------|--|
|                          | Width            | Height  | Thickness | Deck Assembly  |
| Harvest<br>Shake         | 40"              | 17"     | 1/2"      | Deck:  • Minimum 1/2" AC Exterior grade plywood  Underlayment:  • See Note 1 and 2  • One layer fastened to the test deck with 2" overlap at horizontal joints |
| Granville<br>Slate       | 40"              | 17"     | 3/8"      |  |
| Ranchlands<br>Shake      | 36"              | 22-1/2" | 3/4"      |  |
| Rundle<br>Slate          | 36"              | 22-1/2" | 3/4"      |  |
| Beaumont<br>Shake        | 40" 20           |         | 1/2"      | Deck:  • Minimum 1/2" AC Exterior grade plywood  |
|                          |                  | 20"     |           | <ul> <li>Underlayment:</li> <li>See Note 1 and 2</li> <li>One layer fastened to the test deck with 4" overlap at horizontal joints</li> </ul>                  |



VANCOUVER, BC: LOS ANGELES, CA: WASHINGTON, DC: TULSA, OK: TORONTO, ON WEBSITE: 877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 540.636.9445 ph. | 540.636.9414 fx. 918.437.8333 ph. | 918.437.8487 fx. 416.550.9280 WWW.QALORG

Notes: **Note 1:** Underlayment and roof covering products are to be installed with mechanical fasteners in accordance with the manufacturer's published installation instructions. Self-adhering or adhesive applied underlayment installations are outside the scope of this listing.

**Note 2:** Underlayment shall be a listed ASTM D226 complying Type II felt underlay.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warrantee is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at <a href="www.qai.org">www.qai.org</a> for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to <a href="mailto:info@qai.org">info@qai.org</a>. Please include the listing number in the request.

\*\*\*