

VANCOUVER, BC: LOS ANGELES, CA: WASHINGTON, DC: TULSA, OK: TORONTO, ON SEATTLE, WA WEBSITE:

877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 540.636.9445 ph. | 540.636.9414 fx. 918.437.8333 ph. | 918.437.8487 fx. 905-605-5444 425.512.8419

WWW.OAI.ORG

ELECTRICAL LISTING PROGRAM

Customer: iGuardFire Ltd.
Class: Signal Equipment
Location: Kelowna, BC, Canada

Website: iguardfire.com

Listing No.: E10697

Report No.: E10697-1601 Ed.3 Project No.: E10679-2001

Effective Date: June 28, 2016

Last Revised

Date: April 29th, 2020

Expires: N/A

Standards: CSA C22.2 No. 205 "Signal Equipment"

UL 2017 "General Purpose Signaling Devices and System"

Product: The products covered by this report are used to automatically disable power to a Range

(Oven/Stove)/Cooktop when an operator is not present for some known duration.

Permanently connected and Cord connected in-line between the Range/Cooktop and the wall receptacle/junction box. Control Panel is mounted to have an unobstructed view of the Range operator space containing a motion sensor controlling the Power Box through

a cable.

Markings: Products are marked in a permanent manner where it is readily visible after installation

with the following:

- a) Manufacturer's name or trademark
- b) Model designation
- c) Month and year of manufacture
- d) Nominal rated voltage, amperes, and frequency
- e) QAI logo with 'c' and 'us' identifier
- f) QAI file Number: E10697
- g) The wording "CSA C22.2 No. 205 and UL 2017"
- h) Warning markings as required by the standards in English and French





VANCOUVER, BC: LOS ANGELES, CA: WASHINGTON, DC: TULSA, OK: TORONTO, ON SEATTLE, WA

WEBSITE:

877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 540.636.9445 ph. | 540.636.9414 fx. 918.437.8333 ph. | 918.437.8487 fx. 905-605-5444

425.512.8419 WWW.QAI.ORG

Models / Ratings:

Model #	Connection to Supply	Volts (V)	Current (A)	Frequency (Hz)	Location
IGSE4, EPB-11x & EMU	Cord connected	120/240	50	47-63	Dry
IGSE-C, EPB-11x-C & EMU	Permanently connected	120/240	30	47-63	Dry

Notes:

- Where the IGSE4 contains both an EPB-11x and an EMU.
- Where EPB-11x, the 'x' refers to 0, 1, 2, or 3 and are variants of the same product.
- Where the IGSE-C contains both an EPB-11x-C and an EMU.
- Where EPB-11x-C, the 'x' refers to 0, 1, 2, or 3 and are variants of the same product.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warrantee is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.
