

BUILDING PRODUCTS LISTING PROGRAM

Class: Cementitious Roofing and Walking Deck Covering

Customer: Westcoat Specialty Coating Systems
Location: 4007 Lockridge Street
San Diego, CA 92102

Listing No. B1095
Project No. B1095-1, Edition 1
Effective Date: October 1, 2016
Last Revised <N/A>
Date:
Expires: <N/A>

Standards: ASTM E108 – “Standard Test Methods for Fire Tests of Roof Coverings.”

Products: Westcoat Specialty Coating Systems ALX Standard (System 1 and 1A) Cementitious Partially Bonded System installed over nominal 5/8 (1⁹/32-inch) plywood.

Markings: Listed products are identified with a label bearing the following information:

- Product name
- Company name, logo, address and phone number
- Manufacturing plant address, including city and state of manufacture
- QAI logo with ‘us’ indicators
- QAI Certification Listing Number (B1095-1)
- Information for traceability
- QAI Logo shown here:



Models :

MODEL	BASE COAT	SLURRY COAT	TEXTURE COAT	TOP COAT
ALX Standard Cementitious Partially Bonded System	TC-1 Cement 50lb. bag mixed with 1¼ gal. of WP-81 and ¼ gal. of water applied at a rate of 40 sqft. per mix for a dry film thickness of 0.142".	TC-1 Cement 50lb. bag mixed with 1 gal. of WP-81 and ½ gallon of water applied at a rate of 150 sqft. per mix for a dry film thickness of 0.063".	TC-3 Cement 50lb. bag mixed with 1 gal. of WP-81 and ½ gal. of water applied at a rate of 200 sqft. per mix.	SC-10 Two coats applied at a rate of 250 square feet per gallon or one coat at 125 square feet per gallon that provides a dry film thickness of 0.007 inches

Ratings:

The following outlines roof fire classifications of QAI certified Westcoat Specialty Coating Systems Cementitious Partially Bonded System products:

Westcoat Specialty Coating Systems Cementitious Partially Bonded System 1 – Class A Roof Fire Assembly (¼ : 12 Slope)

SHEATHING	UNDERLAYMENT	DECK COVERING
5/8" Nominal Plywood	6" wide WP-40 Peel and Stick (ESR 3585) applied at sheathing seams.	Westcoat Specialty Coating Systems ALX (System 1) Cementitious Partially Bonded System consisting of: WP-40 (seam treatment) 2.5 lbs per square foot galvanized metal lath. Base Coat. Slurry Coat. Texture Coat. Top Coat.

Westcoat Specialty Coating Systems Cementitious Partially Bonded System 1A – Class A Roof Fire Assembly (1/4 : 12 Slope)

SHEATHING	UNDERLAYMENT	DECK COVERING
5/8" Nominal Plywood	WP-40 Peel and Stick (ESR 3585) applied over sheathing	Westcoat Specialty Coating Systems ALX (System 1A) Cementitious Partially Bonded System consisting of: WP-40 (fully applied) 2.5 lbs per square foot galvanized metal lath. Base Coat. Slurry Coat. Texture Coat. Top Coat.

Notes:

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warrantee is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.
