

## WINDOWS & DOORS LISTING PROGRAM

Customer: Lipsett Glazing Systems Inc., DBA: Sashmasters Window & Door  
 Class: Fenestration  
 Location: Burnaby, BC  
 Website: [www.sashmasters.ca](http://www.sashmasters.ca)  
 Listing No. W486-2  
 Project No. W486-2 ED1  
 Effective Date: March 31, 2017  
 Last Revised Date: March 31, 2017  
 Standards: CSA A440.2 "Fenestration Energy Performance"  
 Product: Wood Doors  
 Markings: Products are marked with the following content in a permanent manner where it is readily visible after installation:

- a) Manufacturer's name, Trademark or other recognized symbol or identification.
- b) QAI file Number: W486
- c) QAI logo shown here:



- d) "Evaluation for energy performance in accordance with CSA A440.2" / "Évalué pour la performance d'énergie en accord à la norme CSA A440.2"

Models / Ratings:

<b>1-3/4" Wood Doors Inswing Wood or Aluminum Sill and Outswing Wood Sill</b>
---

Model Code	No Lite	1/4 Lite	1/2 Lite	3/4 Lite	Full Lite
MVD-W175-DR01-GO-01-X/X-SS	1.75	1.74	1.70	1.69	1.66
MVD-W175-DR01-GO-02-X/X-SS	1.75	1.70	1.65	1.60	1.54
MVD-W175-DR01-GO-03-X/X-SS	1.75	1.70	1.65	1.60	1.54
MVD-W175-DR01-GO-04-X/X-SS	1.75	1.74	1.70	1.69	1.66
MVD-W175-DR02-GO-01-X/X-SS	2.02	1.97	1.91	1.86	1.81
MVD-W175-DR02-GO-02-X/X-SS	2.02	1.94	1.85	1.78	1.69
MVD-W175-DR02-GO-03-X/X-SS	2.02	1.94	1.85	1.78	1.69
MVD-W175-DR02-GO-04-X/X-SS	2.02	1.97	1.91	1.86	1.81

Model Code	No Lite	1/4 Lite	1/2 Lite	3/4 Lite	Full Lite
MVD-W175-DR03-GO-01-X/X-SS	2.19	2.12	2.03	1.97	1.89
MVD-W175-DR03-GO-02-X/X-SS	2.19	2.08	1.97	1.89	1.78
MVD-W175-DR03-GO-03-X/X-SS	2.19	2.08	1.97	1.89	1.78
MVD-W175-DR03-GO-04-X/X-SS	2.19	2.12	2.03	1.97	1.89

Model Code	No Lite	1/4 Lite	1/2 Lite	3/4 Lite
MVD-W175-DR04-GO-01-X/X-SS	1.91	1.85	1.78	1.73
MVD-W175-DR04-GO-02-X/X-SS	1.91	1.81	1.71	1.64
MVD-W175-DR04-GO-03-X/X-SS	1.91	1.81	1.71	1.64
MVD-W175-DR04-GO-04-X/X-SS	1.91	1.85	1.78	1.73
MVD-W175-DR05-GO-01-X/X-SS	2.13	2.05	1.96	1.89
MVD-W175-DR05-GO-02-X/X-SS	2.13	2.02	1.90	1.81
MVD-W175-DR05-GO-03-X/X-SS	2.13	2.02	1.90	1.81
MVD-W175-DR05-GO-04-X/X-SS	2.13	2.05	1.96	1.89
MVD-W175-DR06-GO-01-X/X-SS	2.31	2.19	2.08	1.99
MVD-W175-DR06-GO-02-X/X-SS	2.31	2.15	2.02	1.91
MVD-W175-DR06-GO-03-X/X-SS	2.31	2.15	2.02	1.91
MVD-W175-DR06-GO-04-X/X-SS	2.31	2.19	2.08	1.99
MVD-W175-DR07-GO-01-X/X-SS	1.86	1.81	1.75	1.71
MVD-W175-DR07-GO-02-X/X-SS	1.86	1.78	1.69	1.62
MVD-W175-DR07-GO-03-X/X-SS	1.86	1.78	1.69	1.62
MVD-W175-DR07-GO-04-X/X-SS	1.86	1.81	1.75	1.70
MVD-W175-DR08-GO-01-X/X-SS	2.23	2.11	1.99	1.91
MVD-W175-DR08-GO-02-X/X-SS	2.23	2.07	1.93	1.82
MVD-W175-DR08-GO-03-X/X-SS	2.23	2.07	1.93	1.82
MVD-W175-DR08-GO-04-X/X-SS	2.23	2.11	1.99	1.91
MVD-W175-DR09-GO-01-X/X-SS	2.40	2.25	2.12	2.02
MVD-W175-DR09-GO-02-X/X-SS	2.40	2.22	2.06	1.94
MVD-W175-DR09-GO-03-X/X-SS	2.40	2.22	2.06	1.94
MVD-W175-DR09-GO-04-X/X-SS	2.40	2.25	2.12	2.02

Model Code	No Lite	1/4 Lite	1/2 Lite	3/4 Lite
MVD-W175-DR10-GO-01-X/X-SS	1.90	1.84	1.77	1.72
MVD-W175-DR10-GO-02-X/X-SS	1.90	1.81	1.71	1.64
MVD-W175-DR10-GO-03-X/X-SS	1.90	1.81	1.71	1.64
MVD-W175-DR10-GO-04-X/X-SS	1.90	1.84	1.77	1.72
MVD-W175-DR11-GO-01-X/X-SS	2.10	2.02	1.94	1.88
MVD-W175-DR11-GO-02-X/X-SS	2.10	1.99	1.88	1.79
MVD-W175-DR11-GO-03-X/X-SS	2.10	1.99	1.88	1.79
MVD-W175-DR11-GO-04-X/X-SS	2.10	2.02	1.94	1.88
MVD-W175-DR12-GO-01-X/X-SS	2.25	2.16	2.06	1.99
MVD-W175-DR12-GO-02-X/X-SS	2.25	2.12	1.99	1.90
MVD-W175-DR12-GO-03-X/X-SS	2.25	2.12	1.99	1.90
MVD-W175-DR12-GO-04-X/X-SS	2.25	2.16	2.06	1.99
MVD-W175-DR13-GO-01-X/X-SS	1.85	1.80	1.75	1.71
MVD-W175-DR13-GO-02-X/X-SS	1.85	1.77	1.69	1.62
MVD-W175-DR13-GO-03-X/X-SS	1.85	1.77	1.69	1.62
MVD-W175-DR13-GO-04-X/X-SS	1.85	1.80	1.75	1.71
MVD-W175-DR14-GO-01-X/X-SS	2.16	2.07	1.96	1.90
MVD-W175-DR14-GO-02-X/X-SS	2.16	2.03	1.90	1.81
MVD-W175-DR14-GO-03-X/X-SS	2.16	2.03	1.90	1.81
MVD-W175-DR14-GO-04-X/X-SS	2.16	2.07	1.96	1.90
MVD-W175-DR15-GO-01-X/X-SS	2.32	2.20	2.08	2.00
MVD-W175-DR15-GO-02-X/X-SS	2.32	2.17	2.02	1.92
MVD-W175-DR15-GO-03-X/X-SS	2.32	2.17	2.02	1.92
MVD-W175-DR15-GO-04-X/X-SS	2.32	2.20	2.08	2.00
MVD-W175-DR16-GO-01-X/X-SS	1.95	1.87	1.79	1.74
MVD-W175-DR16-GO-02-X/X-SS	1.95	1.84	1.73	1.65
MVD-W175-DR16-GO-03-X/X-SS	1.95	1.84	1.73	1.65
MVD-W175-DR16-GO-04-X/X-SS	1.95	1.87	1.79	1.74
MVD-W175-DR17-GO-01-X/X-SS	2.11	2.03	1.94	1.89
MVD-W175-DR17-GO-02-X/X-SS	2.11	1.99	1.88	1.80

Model Code	No Lite	1/4 Lite	1/2 Lite	3/4 Lite
MVD-W175-DR17-GO-03-X/X-SS	2.11	1.99	1.88	1.80
MVD-W175-DR17-GO-04-X/X-SS	2.11	2.03	1.94	1.89
MVD-W175-DR18-GO-01-X/X-SS	2.28	2.17	2.07	1.99
MVD-W175-DR18-GO-02-X/X-SS	2.28	2.15	2.04	1.91
MVD-W175-DR18-GO-03-X/X-SS	2.28	2.15	2.04	1.91
MVD-W175-DR18-GO-04-X/X-SS	2.28	2.17	2.07	1.99
MVD-W175-DR19-GO-01-X/X-SS	1.83	1.79	1.74	1.71
MVD-W175-DR19-GO-02-X/X-SS	1.83	1.76	1.68	1.62
MVD-W175-DR19-GO-03-X/X-SS	1.83	1.76	1.68	1.62
MVD-W175-DR19-GO-04-X/X-SS	1.83	1.79	1.74	1.71
MVD-W175-DR20-GO-01-X/X-SS	2.20	2.09	1.98	1.91
MVD-W175-DR20-GO-02-X/X-SS	2.20	2.06	1.92	1.82
MVD-W175-DR20-GO-03-X/X-SS	2.20	2.06	1.92	1.82
MVD-W175-DR20-GO-04-X/X-SS	2.20	2.09	1.98	1.91
MVD-W175-DR21-GO-01-X/X-SS	2.37	2.24	2.11	2.02
MVD-W175-DR21-GO-02-X/X-SS	2.37	2.21	2.04	1.94
MVD-W175-DR21-GO-03-X/X-SS	2.37	2.21	2.04	1.94
MVD-W175-DR21-GO-04-X/X-SS	2.37	2.24	2.11	2.02

**2-1/4" Wood Doors Inswing Wood or Aluminum Sill and Outswing Wood Sill**

Model Code	No Lite	1/4 Lite	1/2 Lite	3/4 Lite	Full Lite
MVD-W225-DR01-GO-05-X/X-SS	1.62	1.56	1.50	1.46	1.40
MVD-W225-DR01-GO-06-X/X-SS	1.62	1.53	1.43	1.36	1.27
MVD-W225-DR01-GO-07-X/X-SS	1.62	1.54	1.46	1.40	1.32
MVD-W225-DR01-GO-08-X/X-SS	1.62	1.60	1.58	1.56	1.54
MVD-W225-DR01-GO-09-X/X-SS	1.62	1.57	1.52	1.48	1.43
MVD-W225-DR01-GO-10-X/X-SS	1.62	1.60	1.58	1.56	1.54
MVD-W225-DR01-GO-11-X/X-SS	1.62	1.57	1.51	1.47	1.42
MVD-W225-DR02-GO-05-X/X-SS	1.78	1.72	1.65	1.61	1.54
MVD-W225-DR02-GO-06-X/X-SS	1.78	1.68	1.58	1.50	1.41

Model Code	No Lite	1/4 Lite	1/2 Lite	3/4 Lite	Full Lite
MVD-W225-DR02-GO-07-X/X-SS	1.78	1.69	1.60	1.53	1.45
MVD-W225-DR02-GO-08-X/X-SS	1.78	1.76	1.73	1.71	1.68
MVD-W225-DR02-GO-09-X/X-SS	1.78	1.71	1.65	1.60	1.53
MVD-W225-DR02-GO-10-X/X-SS	1.78	1.75	1.72	1.70	1.67
MVD-W225-DR02-GO-11-X/X-SS	1.78	1.71	1.65	1.60	1.53
MVD-W225-DR03-GO-05-X/X-SS	1.87	1.82	1.74	1.70	1.63
MVD-W225-DR03-GO-06-X/X-SS	1.87	1.78	1.67	1.60	1.49
MVD-W225-DR03-GO-07-X/X-SS	1.87	1.78	1.69	1.62	1.53
MVD-W225-DR03-GO-08-X/X-SS	1.87	1.85	1.82	1.79	1.77
MVD-W225-DR03-GO-09-X/X-SS	1.87	1.81	1.74	1.69	1.62
MVD-W225-DR03-GO-10-X/X-SS	1.87	1.85	1.81	1.79	1.75
MVD-W225-DR03-GO-11-X/X-SS	1.87	1.82	1.75	1.70	1.64

Model Code	No Lite	1/4 Lite	1/2 Lite	3/4 Lite
MVD-W225-DR04-GO-05-X/X-SS	1.72	1.63	1.55	1.48
MVD-W225-DR04-GO-06-X/X-SS	1.72	1.59	1.47	1.39
MVD-W225-DR04-GO-07-X/X-SS	1.72	1.60	1.49	1.41
MVD-W225-DR04-GO-08-X/X-SS	1.72	1.67	1.62	1.58
MVD-W225-DR04-GO-09-X/X-SS	1.72	1.62	1.54	1.48
MVD-W225-DR04-GO-10-X/X-SS	1.72	1.66	1.62	1.57
MVD-W225-DR04-GO-11-X/X-SS	1.72	1.62	1.54	1.48
MVD-W225-DR05-GO-05-X/X-SS	1.95	1.83	1.72	1.65
MVD-W225-DR05-GO-06-X/X-SS	1.95	1.79	1.65	1.54
MVD-W225-DR05-GO-07-X/X-SS	1.95	1.80	1.66	1.57
MVD-W225-DR05-GO-08-X/X-SS	1.95	1.87	1.79	1.74
MVD-W225-DR05-GO-09-X/X-SS	1.95	1.82	1.71	1.64
MVD-W225-DR05-GO-10-X/X-SS	1.95	1.86	1.79	1.74
MVD-W225-DR05-GO-11-X/X-SS	1.95	1.82	1.71	1.64
MVD-W225-DR06-GO-05-X/X-SS	2.09	1.96	1.83	1.75
MVD-W225-DR06-GO-06-X/X-SS	2.09	1.92	1.76	1.65
MVD-W225-DR06-GO-07-X/X-SS	2.09	1.92	1.78	1.68
MVD-W225-DR06-GO-08-X/X-SS	2.09	1.99	1.91	1.85
MVD-W225-DR06-GO-09-X/X-SS	2.09	1.95	1.83	1.74
MVD-W225-DR06-GO-10-X/X-SS	2.09	1.99	1.90	1.84

Model Code	No Lite	1/4 Lite	1/2 Lite	3/4 Lite
MVD-W225-DR06-GO-11-X/X-SS	2.09	1.96	1.84	1.75
MVD-W225-DR07-GO-05-X/X-SS	1.62	1.56	1.50	1.46
MVD-W225-DR07-GO-06-X/X-SS	1.62	1.52	1.43	1.36
MVD-W225-DR07-GO-07-X/X-SS	1.62	1.53	1.45	1.39
MVD-W225-DR07-GO-08-X/X-SS	1.62	1.60	1.58	1.56
MVD-W225-DR07-GO-09-X/X-SS	1.62	1.56	1.50	1.45
MVD-W225-DR07-GO-10-X/X-SS	1.62	1.60	1.57	1.55
MVD-W225-DR07-GO-11-X/X-SS	1.62	1.56	1.49	1.45
MVD-W225-DR08-GO-05-X/X-SS	1.86	1.77	1.69	1.62
MVD-W225-DR08-GO-06-X/X-SS	1.86	1.74	1.61	1.53
MVD-W225-DR08-GO-07-X/X-SS	1.86	1.74	1.63	1.55
MVD-W225-DR08-GO-08-X/X-SS	1.86	1.81	1.76	1.73
MVD-W225-DR08-GO-09-X/X-SS	1.86	1.77	1.68	1.62
MVD-W225-DR08-GO-10-X/X-SS	1.86	1.81	1.75	1.71
MVD-W225-DR08-GO-11-X/X-SS	1.86	1.77	1.68	1.61
MVD-W225-DR09-GO-05-X/X-SS	2.01	1.90	1.80	1.73
MVD-W225-DR09-GO-06-X/X-SS	2.01	1.87	1.73	1.62
MVD-W225-DR09-GO-07-X/X-SS	2.01	1.87	1.74	1.65
MVD-W225-DR09-GO-08-X/X-SS	2.01	1.94	1.87	1.83
MVD-W225-DR09-GO-09-X/X-SS	2.01	1.90	1.79	1.72
MVD-W225-DR09-GO-10-X/X-SS	2.01	1.94	1.87	1.82
MVD-W225-DR09-GO-11-X/X-SS	2.01	1.90	1.81	1.73
MVD-W225-DR10-GO-05-X/X-SS	1.70	1.62	1.54	1.48
MVD-W225-DR10-GO-06-X/X-SS	1.70	1.58	1.46	1.38
MVD-W225-DR10-GO-07-X/X-SS	1.70	1.58	1.48	1.41
MVD-W225-DR10-GO-08-X/X-SS	1.70	1.65	1.61	1.58
MVD-W225-DR10-GO-09-X/X-SS	1.70	1.61	1.53	1.47
MVD-W225-DR10-GO-10-X/X-SS	1.70	1.65	1.61	1.57
MVD-W225-DR10-GO-11-X/X-SS	1.70	1.61	1.53	1.47
MVD-W225-DR11-GO-05-X/X-SS	1.95	1.83	1.73	1.65
MVD-W225-DR11-GO-06-X/X-SS	1.95	1.79	1.65	1.54
MVD-W225-DR11-GO-07-X/X-SS	1.95	1.81	1.67	1.57

Model Code	No Lite	1/4 Lite	1/2 Lite	3/4 Lite
MVD-W225-DR11-GO-08-X/X-SS	1.95	1.87	1.80	1.74
MVD-W225-DR11-GO-09-X/X-SS	1.95	1.83	1.72	1.64
MVD-W225-DR11-GO-10-X/X-SS	1.95	1.87	1.79	1.74
MVD-W225-DR11-GO-11-X/X-SS	1.95	1.83	1.71	1.64
MVD-W225-DR12-GO-05-X/X-SS	2.10	1.97	1.84	1.75
MVD-W225-DR12-GO-06-X/X-SS	2.10	1.93	1.77	1.65
MVD-W225-DR12-GO-07-X/X-SS	2.10	1.94	1.78	1.68
MVD-W225-DR12-GO-08-X/X-SS	2.10	2.00	1.91	1.85
MVD-W225-DR12-GO-09-X/X-SS	2.10	1.96	1.83	1.74
MVD-W225-DR12-GO-10-X/X-SS	2.10	2.00	1.91	1.84
MVD-W225-DR12-GO-11-X/X-SS	2.10	1.97	1.85	1.75
MVD-W225-DR13-GO-05-X/X-SS	1.62	1.56	1.50	1.46
MVD-W225-DR13-GO-06-X/X-SS	1.62	1.52	1.43	1.36
MVD-W225-DR13-GO-07-X/X-SS	1.62	1.53	1.45	1.39
MVD-W225-DR13-GO-08-X/X-SS	1.62	1.60	1.58	1.56
MVD-W225-DR13-GO-09-X/X-SS	1.62	1.56	1.50	1.45
MVD-W225-DR13-GO-10-X/X-SS	1.62	1.60	1.57	1.55
MVD-W225-DR13-GO-11-X/X-SS	1.62	1.56	1.49	1.45
MVD-W225-DR14-GO-05-X/X-SS	1.87	1.78	1.69	1.62
MVD-W225-DR14-GO-06-X/X-SS	1.87	1.74	1.62	1.53
MVD-W225-DR14-GO-07-X/X-SS	1.87	1.75	1.64	1.55
MVD-W225-DR14-GO-08-X/X-SS	1.87	1.82	1.77	1.73
MVD-W225-DR14-GO-09-X/X-SS	1.87	1.77	1.69	1.62
MVD-W225-DR14-GO-10-X/X-SS	1.87	1.81	1.76	1.71
MVD-W225-DR14-GO-11-X/X-SS	1.87	1.77	1.69	1.61
MVD-W225-DR15-GO-05-X/X-SS	2.12	1.99	1.86	1.77
MVD-W225-DR15-GO-06-X/X-SS	2.12	1.95	1.79	1.67
MVD-W225-DR15-GO-07-X/X-SS	2.12	1.96	1.81	1.69
MVD-W225-DR15-GO-08-X/X-SS	2.12	2.03	1.94	1.87
MVD-W225-DR15-GO-09-X/X-SS	2.12	1.98	1.86	1.76
MVD-W225-DR15-GO-10-X/X-SS	2.12	2.02	1.93	1.86
MVD-W225-DR15-GO-11-X/X-SS	2.12	1.99	1.87	1.77

Model Code	No Lite	1/4 Lite	1/2 Lite	3/4 Lite
MVD-W225-DR16-GO-05-X/X-SS	1.89	1.74	1.62	1.52
MVD-W225-DR16-GO-06-X/X-SS	1.89	1.70	1.54	1.42
MVD-W225-DR16-GO-07-X/X-SS	1.89	1.71	1.56	1.45
MVD-W225-DR16-GO-08-X/X-SS	1.89	1.78	1.69	1.62
MVD-W225-DR16-GO-09-X/X-SS	1.89	1.73	1.61	1.51
MVD-W225-DR16-GO-10-X/X-SS	1.89	1.77	1.69	1.61
MVD-W225-DR16-GO-11-X/X-SS	1.89	1.73	1.61	1.51
MVD-W225-DR17-GO-05-X/X-SS	1.92	1.82	1.71	1.64
MVD-W225-DR17-GO-06-X/X-SS	1.92	1.78	1.64	1.54
MVD-W225-DR17-GO-07-X/X-SS	1.92	1.79	1.66	1.57
MVD-W225-DR17-GO-08-X/X-SS	1.92	1.86	1.79	1.74
MVD-W225-DR17-GO-09-X/X-SS	1.92	1.81	1.70	1.64
MVD-W225-DR17-GO-10-X/X-SS	1.92	1.85	1.78	1.74
MVD-W225-DR17-GO-11-X/X-SS	1.92	1.81	1.70	1.64
MVD-W225-DR18-GO-05-X/X-SS	2.06	1.95	1.83	1.76
MVD-W225-DR18-GO-06-X/X-SS	2.06	1.91	1.75	1.66
MVD-W225-DR18-GO-07-X/X-SS	2.06	1.91	1.78	1.69
MVD-W225-DR18-GO-08-X/X-SS	2.06	1.98	1.91	1.86
MVD-W225-DR18-GO-09-X/X-SS	2.06	1.94	1.82	1.75
MVD-W225-DR18-GO-10-X/X-SS	2.06	1.98	1.90	1.85
MVD-W225-DR18-GO-11-X/X-SS	2.06	1.95	1.83	1.77
MVD-W225-DR19-GO-05-X/X-SS	1.73	1.64	1.55	1.48
MVD-W225-DR19-GO-06-X/X-SS	1.73	1.60	1.48	1.38
MVD-W225-DR19-GO-07-X/X-SS	1.73	1.60	1.50	1.41
MVD-W225-DR19-GO-08-X/X-SS	1.73	1.67	1.62	1.58
MVD-W225-DR19-GO-09-X/X-SS	1.73	1.63	1.54	1.48
MVD-W225-DR19-GO-10-X/X-SS	1.73	1.67	1.62	1.57
MVD-W225-DR19-GO-11-X/X-SS	1.73	1.62	1.54	1.47
MVD-W225-DR20-GO-05-X/X-SS	1.88	1.78	1.69	1.63
MVD-W225-DR20-GO-06-X/X-SS	1.88	1.75	1.62	1.53
MVD-W225-DR20-GO-07-X/X-SS	1.88	1.75	1.64	1.56
MVD-W225-DR20-GO-08-X/X-SS	1.88	1.82	1.77	1.73
MVD-W225-DR20-GO-09-X/X-SS	1.88	1.78	1.69	1.62



Model Code	No Lite	1/4 Lite	1/2 Lite	3/4 Lite
MVD-W225-DR20-GO-10-X/X-SS	1.88	1.82	1.76	1.72
MVD-W225-DR20-GO-11-X/X-SS	1.88	1.78	1.69	1.62
MVD-W225-DR21-GO-05-X/X-SS	2.08	1.96	1.84	1.75
MVD-W225-DR21-GO-06-X/X-SS	2.08	1.92	1.77	1.65
MVD-W225-DR21-GO-07-X/X-SS	2.08	1.92	1.79	1.68
MVD-W225-DR21-GO-08-X/X-SS	2.08	1.99	1.91	1.85
MVD-W225-DR21-GO-09-X/X-SS	2.08	1.95	1.83	1.74
MVD-W225-DR21-GO-10-X/X-SS	2.08	1.99	1.91	1.85
MVD-W225-DR21-GO-11-X/X-SS	2.08	1.96	1.85	1.76

**Wood Eclipse Door 1-3/4"**

Model Code	Full Lite
MVD-W175D-EC01-GO-01-SS	1.67
MVD-W175D-EC01-GO-02-SS	1.56
MVD-W175D-EC01-GO-03-SS	1.56
MVD-W175D-EC01-GO-04-SS	1.67
MVD-W175D-EC02-GO-01-SS	1.79
MVD-W175D-EC02-GO-02-SS	1.63
MVD-W175D-EC02-GO-03-SS	1.63
MVD-W175D-EC02-GO-04-SS	1.79
MVD-W175D-EC03-GO-01-SS	1.86
MVD-W175D-EC03-GO-02-SS	1.67
MVD-W175D-EC03-GO-03-SS	1.67
MVD-W175D-EC03-GO-04-SS	1.86

**Wood Eclipse Door 2-1/4"**

Model Code	Full Lite
MVD-W225D-EC01-GO-05-SS	1.43
MVD-W225D-EC01-GO-06-SS	1.30
MVD-W225D-EC01-GO-07-SS	1.35
MVD-W225D-EC01-GO-08-SS	1.57
MVD-W225D-EC01-GO-09-SS	1.45
MVD-W225D-EC01-GO-10-SS	1.57
MVD-W225D-EC01-GO-11-SS	1.45
MVD-W225D-EC02-GO-05-SS	1.52
MVD-W225D-EC02-GO-06-SS	1.39
MVD-W225D-EC02-GO-07-SS	1.43
MVD-W225D-EC02-GO-08-SS	1.66
MVD-W225D-EC02-GO-09-SS	1.52
MVD-W225D-EC02-GO-10-SS	1.65
MVD-W225D-EC02-GO-11-SS	1.51
MVD-W225D-EC03-GO-05-SS	1.60
MVD-W225D-EC03-GO-06-SS	1.46
MVD-W225D-EC03-GO-07-SS	1.49
MVD-W225D-EC03-GO-08-SS	1.73
MVD-W225D-EC03-GO-09-SS	1.58
MVD-W225D-EC03-GO-10-SS	1.71
MVD-W225D-EC03-GO-11-SS	1.60

**Additional Model Options:**

- The above noted models can be constructed with a Chromatech Ultra spacer bar by increasing the U-Value by **0.017** W/m<sup>2</sup>\*K and changing the 'SS' in the model code to 'CU'.
- The above noted 1-3/4" door models can be constructed with an Outswing Aluminum Sill by increasing the U-Value by **0.018** W/m<sup>2</sup>\*K and adding 'AL' the model code.
- The above noted 2-1/4" door models can be constructed with an Outswing Aluminum Sill by increasing the U-Value by **0.028** W/m<sup>2</sup>\*K and adding 'AL' the model code.
- The above noted models can be constructed with True Divided Lites (TDL) by increasing the U-Value as indicated below and adding 'T' to the model code.

U-Value Penalty (W/m <sup>2</sup> *K)			
1/4 Lite	1/2 Lite	3/4 Lite	Full Lite
<b>0.034</b>	<b>0.068</b>	<b>0.097</b>	<b>0.148</b>

**Notes:**

Listed products meet the energy requirements of the standards listed above. Doors are not intended for installation in storefronts, nonoperable portions of curtain wall, fixed glazing cast into precast concrete panels, greenhouses, skylights or sloped glazing. Test procedures are designed to test the performance of the test specimen only and are not necessarily used to test the performance of the installation, particularly the perimeter sealant joint and anchoring of the assembly.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at [www.qai.org](http://www.qai.org) for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to [info@qai.org](mailto:info@qai.org). Please include the listing number in the request.

\*\*\*\*