

ELECTRICAL LISTING PROGRAM

Customer: ITC Inc.
 Class: LED Lighting for use in Recreational Vehicles
 Location: Hudsonville, MI, 49426, USA
 Listing No. E10589
 Report No. E10589-1702 Edition 5
 Project No. E10589-1903
 Effective Date: June 27, 2017
 Last Revised: November 29, 2019
 Date:
 Expires: N/A

Standards: CSA C22.2 No. 250.0 Luminaires
 UL 234 Low Voltage Lighting for Use in Recreational Vehicles

Product: Luminaires and LED Equipment for use in Recreational Vehicles.
 Dry or Suitable for Wet Location, Permanently Connected.

Markings: Products are marked in a permanent manner where it is readily visible after installation with the following:

- a) Manufacturer's name or trademark
- b) Model designation
- c) Month and year of manufacture
- d) Product ratings: voltage, frequency, watts
- e) QAI file Number: E10589
- f) The wording "Conforms to CSA C22.2 No. 250.0 and UL 234"
- g) Warning markings as required by the standards in English and French



h) QAI Logo

Models /
Ratings:

Model / Series #	Volts VDC	Current A	Wattage W	Location
69047 ¹ 1 ² -XX ³ -XX ⁴ -12 ⁵ .XXX ⁶ Series	13.6 Vdc max.	2.1 A max.	28.5 W max.	Wet Locations
Where: 7 ¹ – 12.8 mm Pitch LED 1 ² – Single LED Strip XX ³ – Length XX = up to 72 inch maximum XX ⁴ – LED Color Temperature XX = 30 3000K, XX = 40 4000K or XX = 50 5000K 12 ⁵ – 12 Vdc XXX ⁶ – Optional non-safety changes (Housing color, wire exit style, etc.)				



69711-XX-XK	10~14Vdc	0.63A max	6.3W	Wet Locations
Where: XX = Housing Finish, BK= Black color, WH: White Color and CH: Chromed Plated XK = LED Color Temperature, 3K, 3.5K, or 6.5K				
69711F-XX-XK	10~14Vdc	0.355A max.	3.55W	Wet Locations
Where: XX = Housing Finish, BK= Black color, WH: White Color and CH: Chromed Plated XK = LED Color Temperature, 3K, 3.5K, or 6.5K				
69400XX-YYKK-VV	11~14Vdc	0.134 A max. Per circuit/color	1.876 W max. Per circuit/color	Dry Locations
Where: XX – Mounting Style XX = None (Spring Mount) XX = NS (Screw Mount) YY – Finish YY = NI – Nickel YY = CH – Chrome YY = BK – Black KK – LED Color Temperature KK = 36 (3000K/6500K, Two Color in Single LED) VV – Voltage VV = None (12VDC)				
69400NS-XXKKX	11~14Vdc	N/A	1.8W	Dry Locations
Where: 69400NS = No Spring 69400 = Spring XX – Finish YY = NI – Nickel YY = CH – Chrome YY = BK – Black YY = Truffle,etc, KK – LED Color Temperature KK = 3K, 4K, 6K X – C = Edison LED/Constant Current E = Edison LED/Resistive				
69410NS-XXKKX	11~14Vdc	N/A	1.8W	Dry Locations
Where: 69400NS = No Spring 69400 = Spring XX – Finish YY = NI – Nickel YY = CH – Chrome YY = BK – Black YY = Truffle,etc, KK – LED Color Temperature KK = 3K, 4K, 6K X – C = Edison LED/Constant Current E = Edison LED/Resistive				

Notes: 1- Devices included in this listing are for use in Recreational Vehicles only. Final acceptance of those devices in the recreational vehicle is subject to inspection by the Recreational Vehicle Certifier.

- 2- ELV fixture to be connected to the secondary side of approval power supply – Class 2 or similar certified / listed limited power supply sources, supply to be fused, 5A max.
- 3- Product not intended for use as running or clearance lights.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warrantee is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.
