VANCOUVER, BC: LOS ANGELES, CA: TULSA, OK: TORONTO, ON: WEBSITE:

877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 918.437.8333 ph. | 918.437.8487 fx. 905.605.5444

WWW.QAI.ORG

FIRE DOORS LISTING PROGRAM

Customer: Tru Tech Corporation (Tru Tech Doors)

Class: Fire Doors

Location: Vaughan, Ontario Website: www.trutechdoors.com

Listing No.: F446 Project No.: F446-1

Effective Date: June 7, 2023 Last Revised Date: June 7, 2023

> Expires: N/A

Standards: Fire Tests of Doors Assemblies. **UL 10B**

> **UL 10C** Fire Tests of Doors Assemblies.

NFPA 252 Standard Methods of Fire Tests of Door Assemblies.

Product: 20-Minute Fire-Resistance Rated Category B Doors

Markings: See QAI FD001 - Fire Door Labeling requirements.

Models: 20-MINUTE W/OUT HOSE STREAM STEEL SKIN FOAM CORE

FIRE DOORS:

Minimum 1-3/4" Thickness

Swing Type	Maximum Dimensions Width Length		Panel Type	Latching
Single	3'0"	6'8"	Flush and	Single Point
Swing	(914 mm)	(2032 mm)	Embossed Panels	(Mortised or Cylindrical)

Category B doors where used in positive pressure applications require the use of a rated Category G gasket approved with the respective door type.

Limitations (Review Machining Specifications for further detail):

- Cylindrical Latches (Listed and Labelled)
- · Deadbolts (Listed and Labelled)
- Viewers (Listed and Labelled)
- Surface Mounted Door Closer (Listed and Labelled)
- Surface Mounted Door Bottom (Listed and Labelled)



VANCOUVER, BC: LOS ANGELES, CA: TULSA, OK: TORONTO, ON: WEBSITE: 877.461.8378 ph. | 604.527.8368 fx. 905,605,5444

909.483.0250 ph. | 909.483.0336 fx. 918.437.8333 ph. | 918.437.8487 fx.

WWW.QAI.ORG

Notes:

- Refer to QAI evaluation report F446-1 and the applicable test reports for test assembly configurations used for fire endurance testing.
- Refer to the QAI FD002 Fire Door Guidelines for general guidelines of fire door assemblies.
- Final acceptance of the product in the intended application is to be determined by the authority having jurisdiction (AHJ).
- Product is to be installed in accordance with the manufacturer's published installation instructions by qualified installing personnel.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warrantee is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@gai.org. Please include the listing number in the request.