

VANCOUVER, BC: LOS ANGELES, CA: WASHINGTON, DC: TULSA, OK: TORONTO, ON WEBSITE:

877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 540.636.9445 ph. | 540.636.9414 fx. 918.437.8333 ph. | 918.437.8487 fx. 416.550.9280 WWW.QALORG

FIRE DOORS LISTING PROGRAM

Customer: Bayer Built Woodworks, Inc.

Class: Fire Doors Location: Belgrade, MN

Website: www.bayerbuilt.com

Listing No. F448-1

Project No. F448-1 Edition 1

Effective Date: October 11, 2017 Last Revised Date: October 11, 2017

Standards: UL 10(b) Fire Tests of Doors Assemblies.

UL 10(c) Fire Tests of Doors Assemblies.

NFPA 252 Standard Methods of Fire Tests of Door Assemblies.

Product: 20 min Rated Category B Fire Doors, Neutral and Positive Pressure

Labels: See FD001 - Fire Door Labeling requirements

Models: 20-MINUTE FOAM CORE STEEL EDGE STEEL FIRE DOORS:

Minimum 1-3/4" Thickness

Swing	Maximum Dimensions		Banal Type	Lotobing
Type:	Width:	Length:	Panel Type:	Latching:
Single Swing	3'0" (914 mm)	6'8" (2032 mm)	Flush and Embossed Panels	Single Point (Mortised or Cylindrical)

Limitations: (Review Machining Report for further detail)

- Cylindrical Latches (Listed and Labelled)
- Deadbolts (Listed and Labelled)
- Viewers (Listed and Labelled)
- Surface Mounted Door Closer (Listed and Labelled)
- Surface Mounted Door Bottom (Listed and Labelled)



VANCOUVER, BC: LOS ANGELES, CA: WASHINGTON, DC: TULSA, OK: TORONTO, ON WEBSITE: 877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 540.636.9445 ph. | 540.636.9414 fx. 918.437.8438 ph. | 918.437.8487 fx. 416.550.9280 WWW.QAL.ORG

Notes: Refer to QAI evaluation report F446-1 and the applicable test reports for test assembly configurations used for fire endurance testing.

Refer to the QAI FD002 - Fire Door Guidelines for general guidelines of fire door assemblies

Final acceptance of the product in the intended application is to be determined by the authority having jurisdiction (AHJ).

Product is to be installed in accordance with the manufacturer's published installation instructions by qualified installing personnel.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warrantee is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.

**