

FIRE DOORS LISTING PROGRAM

Customer: Doorland 2000 Inc.
 Class: Fire Doors
 Location: Woodbridge, ON
 Website: www.doorlandgroup.com

Listing No. F447

Effective Date: October 27, 2017
 Last Revised: October 27, 2017

Standards: CAN/ULC-S104	<i>Standard Method for Fire Tests of Door Assemblies.</i>
UL 10(b)	<i>Fire Tests of Doors Assemblies.</i>
UL 10(c)	<i>Fire Tests of Doors Assemblies.</i>
NFPA 252	<i>Standard Methods of Fire Tests of Door Assemblies.</i>

Label: See [FD001 - Fire Door Labeling requirements](#)

Models / Ratings: **Fire Doors:**

<u>Specification Owner</u>	<u>Manufacturing/Machining Specifications:</u>	<u>Listing No.:</u>	<u>Description</u>
BASF SE	20 minute Fire Rated Door	F411-1-1-20	Wood Core
BASF SE	20 minute Fire Rated Door	F411-1-1-20	Palusol Laminated Core
FyreWerks	20 minute Fire Rated Door	F447-1-2-20	Laminated Core
Marshfield	20 minute Fire Rated Door	F447-1-3-20	Wood Core Flush Doors
GP	20 minute Fire Rated Door	F447-1-4-20	Neutral Pressure
GP	20 minute Fire Rated Door	F447-1-4-20	Neutral Pressure Dutch Door
GP	20 minute Fire Rated Door	F447-1-4-20	Positive Pressure
Lexington	20 minute Fire Rated Door	F447-1-5-20	Composite Core
Lexington	20 minute Fire Rated Door	F447-1-5-20	Fire Fiber 20 Composite Core
Marshfield	30 minute Fire Rated Door	F447-1-3-30	Wood Core Flush Door
BASF SE	45 minute Fire Rated Door	F411-1-1-45	Palusol Laminated Core
FyreWerks	45 minute Fire Rated Door	F447-1-2-45	Laminated Core
Marshfield	45 minute Fire Rated Door	F447-1-3-45	Laminated Core
Marshfield	45 minute Fire Rated Door	F447-1-3-45	Particleboard Core
GP	45 minute Fire Rated Door	F447-1-4-45	Neutral Pressure
GP	45 minute Fire Rated Door	F447-1-4-45	Neutral Pressure Dutch Door
GP	45 minute Fire Rated Door	F447-1-4-45	Positive Pressure
GP	45 minute Fire Rated Door	F447-1-4-45	Positive Pressure Acoustical Core
GP	45 minute Fire Rated Door	F447-1-4-45	Positive Pressure Dutch Door
GP	45 minute Fire Rated Door	F447-1-4-45	Positive Pressure Profiled Core



Lexington	45 minute Fire Rated Door	F447-1-5-45	Composite Core
Lexington	45 minute Fire Rated Door	F447-1-5-45	Fire Fiber 45 Composite Core
BASF SE	60 minute Fire Rated Door	F411-1-1-60	Palusol Laminated Core
FyreWerks	60 minute Fire Rated Door	F447-1-2-60	Laminated Core
Marshfield	60 minute Fire Rated Door	F447-1-3-60	Laminated Core
GP	60 minute Fire Rated Door	F447-1-4-60	Neutral Pressure
GP	60 minute Fire Rated Door	F447-1-4-60	Neutral Pressure Dutch Door
GP	60 minute Fire Rated Door	F447-1-4-60	Positive Pressure
GP	60 minute Fire Rated Door	F447-1-4-60	Positive Pressure Acoustical Core
GP	60 minute Fire Rated Door	F447-1-4-60	Positive Pressure Dutch Door
GP	60 minute Fire Rated Door	F447-1-4-60	Positive Pressure Profiled Core
Lexington	60 minute Fire Rated Door	F447-1-5-60	Composite Core
Lexington	60 minute Fire Rated Door	F447-1-5-60	Fire Guard 60 Composite Core
Lexington	60 minute Fire Rated Door	F447-1-5-60	Fire Guard 60 Mineral Core
BASF SE	90 minute Fire Rated Door	F411-1-1-90	Palusol Laminated Core
FyreWerks	90 minute Fire Rated Door	F447-1-2-90	Laminated Core
Marshfield	90 minute Fire Rated Door	F447-1-3-90	Laminated Core
GP	90 minute Fire Rated Door	F447-1-4-90	Neutral Pressure
GP	90 minute Fire Rated Door	F447-1-4-90	Positive Pressure
Lexington	90 minute Fire Rated Door	F447-1-5-90	Fire Shield 90 Mineral Core
Lexington	90 minute Fire Rated Door	F447-1-5-90	Temperature Rise Mineral Core

Fire Door Frames:

<u>Specification Owner</u>	<u>Manufacturing/Machining Specifications:</u>	<u>Listing No.:</u>	<u>Description</u>
BASF SE	20 minute Fire Rated Door Frame	F411-2-20	Wood Core Frame
FyreWerks	20 minute Fire Rated Door Frame	F447-2-2-20	FyreFrame Wood Frame
BASF SE	45 minute Fire Rated Door Frame	F411-2-45	Palusol Laminated Core Frame
FyreWerks	45 minute Fire Rated Door Frame	F447-2-2-45	FyreFrame Composite Frame
GP	45 minute Fire Rated Door Frame	F447-2-3-45	Firestop Frame
BASF SE	60 minute Fire Rated Door Frame	F411-2-60	Palusol Laminated Core Frame
FyreWerks	60 minute Fire Rated Door Frame	F447-2-2-60	FyreFrame Composite Frame
GP	60 minute Fire Rated Door Frame	F447-2-3-60	Firestop Frame
BASF SE	90 minute Fire Rated Door Frame	F411-2-90	Palusol Laminated Core Frame
FyreWerks	90 minute Fire Rated Door Frame	F447-2-2-90	FyreFrame Composite Frame
GP	90 minute Fire Rated Door Frame	F447-2-3-90	Firestop Frame



LABORATORIES

CERTIFICATION TESTING INSPECTION

VANCOUVER, BC: 877.461.8378 ph. | 604.527.8368 fx.
LOS ANGELES, CA: 909.483.0250 ph. | 909.483.0336 fx.
WASHINGTON, DC: 540.636.9445 ph. | 540.636.9414 fx.
TULSA, OK: 918.437.8333 ph. | 918.437.8487 fx.
TORONTO, ON: 416.550.9280
SEATTLE, WA: 425.512.8419
WEBSITE: WWW.QAI.ORG

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warrantee is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.
