

VANCOUVER, BC: LOS ANGELES, CA: WASHINGTON, DC: TULSA, OK: TORONTO, ON WEBSITE: 877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 540.636.9445 ph. | 540.636.9414 fx. 918.437.8333 ph. | 918.437.8487 fx. 416.550.9280 WWW.QAI.ORG

## FIRE DOORS LISTING PROGRAM

Customer: Doortech Manufacturing & Distribution Ltd. Class: Fire Door Frames Location: Winnipeg, Manitoba Website: www.doortechltd.ca

Listing No. F450-2 Project No. F450-2 Edition 1

Effective Date: January 1, 2018 Last Revised Date: January 1, 2018

> Standards: CAN/ULC-S104 UL 10(b) **NFPA 252**

Standard Method for Fire Tests of Door Assemblies Fire Tests of Doors Assemblies. Standard Methods of Fire Tests of Door Assemblies.

- Product: 45 min Rated Fire Door Frames, Neutral Pressure
- Labels: See FD001 Fire Door Labeling requirements

## Models: 45-MINUTE PRESSED STEEL DOOR FRAME WITH TRANSOM AND PANELS:

Swing Type:		Maximum Dimensions	
		Width:	Height:
Maximum Opening		8'0" (2438 mm)	9'0" (2743 mm)
Maximum Overall Size		12'0" (3658 mm)	11'4" (3454 mm)
Transom Panel	Single	4'0" (1219 mm)	4'2" (1270 mm)
	Pairs	8'0" (2438 mm)	4'0" (1219 mm)

## LIMITATIONS:

Minimum Throat Opening: 3"

12 or 16 gauge steel.

Maximum Glazing Sizes: 1296 sq. in. with 3/4" stop depth (max. dimension 54") 600 sq. in. with 11/16" stop depth (max. dimension 54") 500 sq. in. with 5/8" stop depth (max. dimension 54") 400 sq. in. with 9/16" stop depth (max. dimension 54") 300 sq. in. with 1/2" stop depth (max. dimension 54")



VANCOUVER, BC: 877.461.8378 ph. | 604.527.8368 fx. LOS ANGELES, CA: 909.483.0250 ph. | 909.483.0336 fx. WASHINGTON, DC: 540.636.9445 ph. | 540.636.9414 fx. TULSA, OK: 918.437.8333 ph. | 918.437.8487 fx. TORONTO, ON 416.550.9280 WEBSITE: WWW.QAI.ORG

## Notes: Refer to QAI evaluation report F450-2 and the applicable test reports for test assembly configurations used for fire endurance testing.

Refer to the <u>QAI FD002 - Fire Door Guidelines for general guidelines of fire door</u> assemblies

Final acceptance of the product in the intended application is to be determined by the authority having jurisdiction (AHJ).

Product is to be installed in accordance with the manufacturer's published installation instructions by qualified installing personnel.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warrantee is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at <u>www.qai.org</u> for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to <u>info@qai.org</u>. Please include the listing number in the request.

\*\*\*