



BUILDING PRODUCTS LISTING PROGRAM

Customer: CertainTeed Corporation
Class: Roofing Underlayment
Location: Malvern, PA
Website: www.certainteed.com

Listing No. B1107
Project No. B1107-1, Edition 1
Effective Date: May 31, 2018
Last Revised Date: May 31, 2018
Expires: <N/A>

Standards: ASTM E108 – “Standard Test Methods for Fire Tests of Roof Coverings.”

Also complies with the performance requirements of:

ASTM D226 – “Standard Specification of Asphalt-Saturated Organic Felt Used in Roofing and Waterproofing.”

Product: RoofRunner Roofing Underlayment

DiamondDeck Roofing Underlayment

Markings: Listed products are identified with a label bearing the following information:

- Product Name
- Company name, logo, address and phone number
- Manufacturing plant address, including city and state of manufacture
- Information for traceability
- QAI file Number: B1107-1
- Roll length and width
- QAI logo shown here:



Models:

Model	WIDTH	LENGTH	WEIGHT
RoofRunner	48-inches	250 feet	110 grams/m ²
Diamond Deck	48-inches	250 feet	185 grams/m ²

Ratings: The following outlines the physical property classification of the QAI certified CertainTeed underlayment products:

CertainTeed Underlayments – Physical Property Specifications

PRODUCT	TEST METHOD	CLASSIFICATION
RoofRunner	ASTM D226 ¹	Type II
DiamondDeck	ASTM D226 ¹	Type II

Note 1: ASTM D226 outline specifications for asphalt-impregnated organic felt materials. CertainTeed non-asphalt underlayment products in this table were tested and found to comply with the performance specifications outlined in ASTM D226 for the classifications noted.

The following outlines roof fire classifications or QAI certified CertainTeed underlayment products:

CertainTeed Roofing Underlayment – Class A Roof Fire Assembly (No Slope Limitations)

SHEATHING	UNDERLAYMENT	ROOF COVERING
Minimum 15/32” Exposure 1 Plywood	RoofRunner Or DiamondDeck	One layer of Class A listed* asphalt roof shingles, or equivalent, complying with ASTM D3018, and having a minimum installed weight of 180 pounds per 100 ft ² (9.28 kg/m ²), installed per the manufacturer’s installation instructions. or Brick, masonry, slate, clay or concrete roof tile, exposed concrete decks.

*Note 1: Asphalt Shingles are listed Class A components of a listed roof



deck assembly by an Approved Agency. The third party program in which products are certified, carry a label, and are listed in the directory of an agency accredited by the International Accreditation Service, Inc. (IAS), or by an accredited body that is a partner with IAS in a mutual recognition arrangement, pertaining to certification bodies and their compliance with ISO/IEC Guide 65, General Requirements for Bodies Operating Product Certification Systems. The asphalt shingle components are to meet Class A Classification when tested to ASTM E108.

Notes: The product must be installed in accordance with the code enforced by the authority having jurisdiction. Final acceptance of the product in the final installation is subject to inspection by the authority having jurisdiction.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warrantee is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.