

ELECTRICAL LISTING PROGRAM


Customer: Trendy Lighting US
 Class: LED Lighting for use in Recreational Vehicles
 Location: 340 S Lemon Ave #2818 Walnut, CA, 91789, USA
 Listing No. E10930
 Report No. E10930-1701
 Project No. E10930-1701
 Effective Date: April 10, 2018
 Last Revised Date: N/A
 Expires: N/A

Standards: CSA C22.2 No. 250.0 Luminaires
 UL 234 Low Voltage Lighting for Use in Recreational Vehicles

Product: Luminaires and LED Equipment for use in Recreational Vehicles.
 Dry or Suitable for Damp Locations use, Permanently Connected.

Markings: Products are marked in a permanent manner where it is readily visible after installation with the following:

- a) Manufacturer's name or trademark
- b) Model designation
- c) Month and year of manufacture
- d) Product ratings: voltage, frequency, watts
- e) QAI file Number: E10930
- f) The wording "CSA C22.2 No. 250.0 and UL 234"
- g) Warning markings as required by the standards in English and French

h) QAI logo 

Models / Ratings:

Model #	Volts VDC	Wattage W	Descriptions	Location
RV16718A	12	4	4.5" RV 360 Lumen 3500K surface ceiling mount puck light without touchable On/Off on the rim	Damp Location
RV16718B	12	4	4.5" RV 360 Lumen 3500K surface ceiling mount puck light with touchable On/Off on the rim	Damp Location
RV16713A	12	3	3" RV 280 Lumen 3500K surface mount ceiling puck light without touchable On/Off on the rim	Damp Location
RV16713B	12	3	3" RV 280 Lumen 3500K surface ceiling mount puck light with touchable On/Off on the rim	Damp Location
RV-ST3A	12	3	Recessed 3 Inch w/Plastic Lens Complete Fixture Nylon Threaded	Dry Location



			Trim Ring Inside For Safe Easy Installation with spring, with easy connects, 3W SMD LED 210LM	
RV-ST3B	12	3	Recessed 3 Inch w/Plastic Lens Complete Fixture Nylon Threaded Trim Ring Inside For Safe Easy Installation, with easy terminal block connects, 3W SMD LED 210LM	Dry Location
RV-ST4A	12	4	Recessed 4.5 Inch w/Plastic Lens Complete Fixture Nylon Threaded Trim Ring Inside For Safe Easy Installation with spring, with easy connects, 4W SMD LED 280LM	Dry Location
RV-ST4B	12	4	Recessed 4.5 Inch w/Plastic Lens Complete Fixture Nylon Threaded Trim Ring Inside For Safe Easy Installation, with easy terminal block connects, 4W SMD LED 280LM	Dry Location
RV-PC3	12	6	Flat Double - Low Profile Construction w/Frosted Lens Cover Lens - easy installation & removal 6W SMD LED 470LM ON/OFF Switch Size: L 9.25" X W 3.74" X E 1.6"	Dry Location
TDFP101224	12	18	Panel Light with edge lit LED, 12"x24"x3/5", 18W	Dry Location
TDFP10624	12	9	Panel Light with edge lit LED, 6"x24"x3/5", 9W	Dry Location

- Notes:
- 1- Devices included in this listing are for use in Recreational Vehicles only. Final acceptance of those devices in the recreational vehicle is subject to inspection by the Recreational Vehicle Certifier.
 - 2- Supply to be fused, 5A max.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warrantee is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.
