



WINDOWS & DOORS LISTING PROGRAM

Customer: Norden Windows and Doors Ltd.
Class: Fenestration Products – Energy Performance
Location: Delta, British Columbia
Website: www.nordenwindow.com

Listing No. W567-2
Project No. W567-2 ED7
Effective Date: December 20, 2019
Last Revised Date: July 4, 2025
Expires: N/A

Standards: CSA A440.2-19 “Fenestration Energy Performance”

Product: Vinyl Doors

Markings: Products are marked with the following content in a permanent manner where it is readily visible after installation:

- a) Manufacturer’s name, Trademark or other recognized symbol or identification.
- b) QAI file Number: W567
- c) QAI logo shown here:



- d) “Evaluation for energy performance in accordance with CSA A440.2” / “Évalué pour la performance d’énergie en accord à la norme CSA A440.2”

Models / Ratings:

5200 Series Sliding Patio Door

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	NOR-5200SD-3,180(2)-3,CL-13AR90SS-R1	1.62	0.54	35
G02	NOR-5200SD-3,180(2)-3,CL-13AR90SS-R1-G1<1	1.62	0.47	31
G03	NOR-5200SD-3,180(2)-3,i89(4)-13AR90SS-R1	1.35	0.52	40
G04	NOR-5200SD-3,180(2)-3,i89(4)-13AR90SS-R1-G1<1	1.35	0.46	37
G05	NOR-5200SD-3,270(2)-3,CL-13AR90SS-R1	1.56	0.31	23



Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G06	NOR-5200SD-3,270(2)-3,CL-13AR90SS-R1-G1<1	1.56	0.27	21
G07	NOR-5200SD-3,270(2)-3,i89(4)-13AR90SS-R1	1.31	0.30	28
G08	NOR-5200SD-3,270(2)-3,i89(4)-13AR90SS-R1-G1<1	1.31	0.27	27
G09	NOR-5200SD-3,366(2)-3,CL-13AR90SS-R1	1.53	0.23	19
G10	NOR-5200SD-3,366(2)-3,CL-13AR90SS-R1-G1<1	1.53	0.20	18
G11	NOR-5200SD-3,366(2)-3,i89(4)-13AR90SS-R1	1.29	0.22	24
G12	NOR-5200SD-3,366(2)-3,i89(4)-13AR90SS-R1-G1<1	1.29	0.20	23
G13	NOR-5200SD-5,180(2)-5,i89(4)-12AR90SS-R1	1.35	0.50	39
G14	NOR-5200SD-5,180(2)-5,i89(4)-12AR90SS-R1-G1<1	1.35	0.44	35
G15	NOR-5200SD-5,366(2)-5,i89(4)-12AR90SS-R1	1.29	0.22	24
G16	NOR-5200SD-5,366(2)-5,i89(4)-12AR90SS-R1-G1<1	1.29	0.20	23

2752 Series Out-Swing Side-Hinged Door

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	NOR-2752OSHD-4,180(2)-4,CL-13AR90SS-R1	1.59	0.38	26
G02	NOR-2752OSHD-4,180(2)-4,CL-13AR90SS-R1-G1<1	1.59	0.33	23
G03	NOR-2752OSHD-4,270(2)-4,CL-13AR90SS-R1	1.55	0.22	18
G04	NOR-2752OSHD-4,270(2)-4,CL-13AR90SS-R1-G1<1	1.55	0.20	17
G05	NOR-2752OSHD-4,366(2)-4,CL-13AR90SS-R1	1.53	0.17	16
G06	NOR-2752OSHD-4,366(2)-4,CL-13AR90SS-R1-G1<1	1.53	0.15	14
G07	NOR-2752OSHD-4,270(2)-4,i89(4)-13AR90SS-R1	1.37	0.22	22
G08	NOR-2752OSHD-4,270(2)-4,i89(4)-13AR90SS-R1-G1<1	1.37	0.19	20
G09	NOR-2752OSHD-4,366(2)-4,i89(4)-13AR90SS-R1	1.36	0.17	19
G10	NOR-2752OSHD-4,366(2)-4,i89(4)-13AR90SS-R1-G1<1	1.36	0.15	18
G11	NOR-2752OSHD-4,180(2)-4,CL-4,CL-11AR90SS-R1	1.31	0.35	31
G12	NOR-2752OSHD-4,270(2)-4,CL-4,CL-11AR90SS-R1	1.29	0.21	23
G13	NOR-2752OSHD-4,366(2)-4,CL-4,CL-11AR90SS-R1	1.27	0.16	21
G14	NOR-2752OSHD-4,180(2)-4,CL-4,180(5)-11AR90SS-R1	1.13	0.33	34
G15	NOR-2752OSHD-4,270(2)-4,CL-4,270(5)-11AR90SS-R1	1.10	0.19	26
G16	NOR-2752OSHD-4,366(2)-4,CL-4,366(5)-11AR90SS-R1	1.08	0.15	24

2752 Series In-Swing Side-Hinged Door

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	NOR-2752ISHD-4,180(2)-4,CL-13AR90SS-R1	1.52	0.37	28
G02	NOR-2752ISHD-4,180(2)-4,CL-13AR90SS-R1-G1<1	1.52	0.32	25
G03	NOR-2752ISHD-4,270(2)-4,CL-13AR90SS-R1	1.48	0.22	20
G04	NOR-2752ISHD-4,270(2)-4,CL-13AR90SS-R1-G1<1	1.48	0.19	18
G05	NOR-2752ISHD-4,366(2)-4,CL-13AR90SS-R1	1.46	0.17	17
G06	NOR-2752ISHD-4,366(2)-4,CL-13AR90SS-R1-G1<1	1.46	0.15	16
G07	NOR-2752ISHD-4,270(2)-4,i89(4)-13AR90SS-R1	1.30	0.21	23



Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G08	NOR-2752ISHD-4,270(2)-4,i89(4)-13AR90SS-R1-G1<1	1.30	0.19	22
G09	NOR-2752ISHD-4,366(2)-4,i89(4)-13AR90SS-R1	1.29	0.16	21
G10	NOR-2752ISHD-4,366(2)-4,i89(4)-13AR90SS-R1-G1<1	1.29	0.14	19
G11	NOR-2752ISHD-4,180(2)-4,CL-4,CL-11AR90SS-R1	1.30	0.34	31
G12	NOR-2752ISHD-4,270(2)-4,CL-4,CL-11AR90SS-R1	1.27	0.20	23
G13	NOR-2752ISHD-4,366(2)-4,CL-4,CL-11AR90SS-R1	1.26	0.15	21
G14	NOR-2752ISHD-4,180(2)-4,CL-4,180(5)-11AR90SS-R1	1.11	0.32	34
G15	NOR-2752ISHD-4,270(2)-4,CL-4,270(5)-11AR90SS-R1	1.09	0.19	27
G16	NOR-2752ISHD-4,366(2)-4,CL-4,366(5)-11AR90SS-R1	1.07	0.14	24

2700 Series Folding Door

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	NOR-2700FD-4,CL-4,180(3)-13AR90SS-R1	1.64	0.47	30
G02	NOR-2700FD-4,CL-4,180(3)-13AR90SS-R1-G1<1	1.64	0.41	27
G03	NOR-2700FD-4,270(2)-4,CL-13AR90SS-R1	1.59	0.26	19
G04	NOR-2700FD-4,270(2)-4,CL-13AR90SS-R1-G1<1	1.59	0.23	17
G05	NOR-2700FD-4,366(2)-4,CL-13AR90SS-R1	1.57	0.20	16
G06	NOR-2700FD-4,366(2)-4,CL-13AR90SS-R1-G1<1	1.57	0.18	15
G07	NOR-2700FD-4,270(2)-4,i89(4)-13AR90SS-R1	1.39	0.25	23
G08	NOR-2700FD-4,270(2)-4,i89(4)-13AR90SS-R1-G1<1	1.39	0.22	21
G09	NOR-2700FD-4,366(2)-4,i89(4)-13AR90SS-R1	1.37	0.19	20
G10	NOR-2700FD-4,366(2)-4,i89(4)-13AR90SS-R1-G1<1	1.37	0.17	19
G11	NOR-2700FD-4,270(2)-4,CL-4,180(5)-8AR90SS-R1	1.30	0.24	24
G12	NOR-2700FD-4,366(2)-4,CL-4,180(5)-8AR90SS-R1	1.29	0.18	21
G13	NOR-2700FD-4,180(2)-4,CL-4,180(5)-11AR90SS-R1	1.17	0.37	35
G14	NOR-2700FD-4,270(2)-4,CL-4,270(5)-11AR90SS-R1	1.13	0.22	27
G15	NOR-2700FD-4,366(2)-4,CL-4,366(5)-11AR90SS-R1	1.11	0.17	25
G16	NOR-2700FD-4,CL-4,180(3)-12AR90EN-R1	1.64	0.46	30
G17	NOR-2700FD-4,CL-4,180(3)-12AR90EN-R1-G1<1	1.64	0.40	26
G18	NOR-2700FD-4,270(2)-4,CL-12AR90EN-R1	1.59	0.25	19
G19	NOR-2700FD-4,270(2)-4,CL-12AR90EN-R1-G1<1	1.59	0.22	17
G20	NOR-2700FD-4,366(2)-4,CL-12AR90EN-R1	1.57	0.19	16
G21	NOR-2700FD-4,366(2)-4,CL-12AR90EN-R1-G1<1	1.57	0.17	14
G22	NOR-2700FD-4,270(2)-4,i89(4)-12AR90EN-R1	1.40	0.25	23
G23	NOR-2700FD-4,270(2)-4,i89(4)-12AR90EN-R1-G1<1	1.40	0.22	21
G24	NOR-2700FD-4,366(2)-4,i89(4)-12AR90EN-R1	1.38	0.19	20
G25	NOR-2700FD-4,366(2)-4,i89(4)-12AR90EN-R1-G1<1	1.38	0.17	19
G26	NOR-2700FD-4,270(2)-4,CL-4,180(5)-8AR90EN-R1	1.29	0.23	24
G27	NOR-2700FD-4,366(2)-4,CL-4,180(5)-8AR90EN-R1	1.28	0.18	21



Notes:

- Products are not intended for installation in storefronts, non-operable portions of curtain wall, fixed glazing cast into precast concrete panels, greenhouses, skylights or sloped glazing.
- Test procedures are designed to test the performance of the test specimen only and are not necessarily used to test the performance of the installation, particularly the perimeter sealant joint and anchoring of the assembly.
- The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI.
- No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing.
- Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.