VANCOUVER, BC: LOS ANGELES, CA: WASHINGTON, DC: TULSA, OK: TORONTO, ON WEBSITE: 877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 540.636.9445 ph. | 540.636.9414 fx. 918.437.8333 ph. | 918.437.8487 fx. 416.550.9280 WWW QALORG

## FIRE DOOR LISTING PROGRAM

Customer: Tadpole Products, LLC

Class: Fire-Resistant Fire Door Frame Hardware Component

Location: Cleveland, OH

Listing No. F466-1

Project No. F466-1 Edition 1

Effective Date: May 14, 2020 Last Revised Date: May 14, 2020

Standards: UL 10B Fire Tests of Door Assemblies

UL 10C Positive Pressure Fire Tests of Door Assemblies
NFPA 252 Standard Methods of Fire Tests of Door Assemblies
CAN/ULC S104 Standard Method for Fire Tests of Door Assemblies

Product: Frame Frog Frame Hardware for use with Fire-Resistance Rated Fire Door

Frames.

Markings: Each product unit is marked with the following content on a permanent label that is

readily visible after installation:

- Company name

Product name or model

- QAI Component Logo

- QAI Listing file number (F466)

- The statement "Listed Frame Hardware Fire Rating to 180 Minutes"

Applicable Standards: UL 10B, UL 10C, NFPA 252, and CAN/ULC S104

## Models:

Product	Frame	Pressure	Maximum
Name	Type <sup>1</sup>	Type	Fire-resistance Rating
Frame Frog	Steel	Positive or Neutral	≤ 180 Minutes

Note 1: Frame to be caulked to fire-rated wall assembly appropriately to maintain seal.

Notes: The listing noted pertains to Frame Frog products listed intended for use with door

frame products in fire-resistance rated applications. Where openings have additional criteria beyond the scope of fire-resistance rating, the Authority Having Jurisdiction (AHJ) should be consulted for approval of Frame Frog Frame Hardware.

Product is to be installed in accordance with the manufacturer's installation instructions.

Refer to the <u>FD002 - Fire Door Guidelines</u> for general guidelines of fire door assemblies.



VANCOUVER, BC: LOS ANGELES, CA: WASHINGTON, DC: TULSA, OK: TORONTO, ON WEBSITE: 877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 540.636.9445 ph. | 540.636.9414 fx. 918.437.8333 ph. | 918.437.8487 fx. 416.550.9280 WWW.QAI.ORG

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at <a href="www.qai.org">www.qai.org</a> for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to <a href="mailto:info@qai.org">info@qai.org</a>. Please include the listing number in the request.

\*\*\*