WWW.QAI.ORG



ELECTRICAL LISTING PROGRAM

Leggett & Platt, Incorporated Customer:

Class: Control Box Carthage, MO

Location: **USA**

Website: N/A Listing No. E10759

Report No. E10759-2201 Ed. 3

Project No. E10759-2201 Ed. 3 (QA-1904)

Effective Date: October 23, 2023

Last Revised

June 20, 2025 Date:

N/A Expires:

CSA C22.2 No. 68 Standards:

UL 962

This device is intended to control motor-operated motion furniture, where

Product: the device is intermittently used. This device is intended to be connected

to 29VDC, 3.2A by means of a Listed Class 2 power source

Markings: A. Products are marked in a permanent manner where it is readily visible

after installation with the following:

B. Manufacturer's name multiple listee name or trade name or other

recognized symbol of identification.

C. Model designation

D. Month and year of manufacture

E. Product ratings: voltage and current rating

F. QAI file Number: E10759

G. The wording "CSA C22.2 No. 68 and UL 962"

H. Warning markings as required by the standards in English and French

QAI logo shown here:





877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 918.437.8333 ph. | 918.437.8487 fx. 905 605 5444

WWW.QAI.ORG



Models / Ratings:

Model	Voltage	Current	Environmental Locations
209 M001	29Vdc	3.2A	Dry Location only

- Notes: 1. The manufacturer / Listee maintains a system to ensure each product complies with this report prior to application of the QAI mark.
 - 2. The product is installed in accordance with the NEC and CEC as applicable
 - 3. Suitability of the product in its final installation is subject to inspection by the Authority Having Jurisdiction (AHJ)
 - 4. This product is certified as a component only where the suitability of the final combination with the complete system is to be determined by the complete system certifier.
 - 5. The device was subjected to the Temperature Test at motor duty cycle: 2 minutes "ON" / 18 minutes "OFF"; vibration and light running continuous. The suitability of duty cycles for motor control shall be determined in the end-use application.
 - 6. The device shall be installed in compliance with enclosure, mounting, spacing, and segregation requirements of the final application.
 - 7. The device is intended for factory wiring only. The suitability of connections made to these devices shall be determined in the final application.
 - 8. The device has not been evaluated for use in safety or limiting applications. No protective or safety functions to motors (i.e. Running Overload, Lock Rotor) were evaluated. Protective or safety functions to motors are to be evaluated in final application.
 - 9. Abnormal operations/tests within UL 962 and CSA C22.2 No. 68 are to be evaluated in final application.
 - 10. Only two actuators are intended to be operated at any given time.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warrantee is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@gai.org. Please include the listing number in the request.