VANCOUVER, BC: LOS ANGELES, CA: TORONTO, ON: TULSA, OK: MIAMI. FL: WEBSITE:

877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 905.605.5444 ph. 918.437.8333 ph. | 918.437.8487 fx. 305.885.3328 ph. | 305.885.3329 fx. WWW.QAI.ORG

## FIRE DOOR LISTING PROGRAM

Customer: Ocean Design LLC

Class: Fire Resistant Doors and Frames

Location: Miami, Florida

Website: www.oceandsgn.com

Listing No. F469

Projects No. F469-1 Edition 1

F469-2 Edition 1

Effective Date: September 3, 2020 Last Revised Date: September 3, 2020

Expires: N/A

Standards: UL 10B Fire Tests of Door Assemblies

Positive Pressure Fire Tests of Door Assemblies **UL 10C** Standard Methods of Fire Tests of Door Assemblies NFPA 252 CAN/ULC S104 Standard Method for Fire Tests of Door Assemblies

Product: 20 to 90 minute Neutral & Positive Pressure Rated Category "A" Wood and

Composite Fire Doors and Category "C" Fire Door Frames with and without Hose

Stream.

Markings: See FD001 - Fire Door Labeling requirements

Models / Ratings: **Fire Resistance Rated Doors** 

Spec. Owner	Fire Rating	Category	Listing #	Description
BASF SE	20 minute	А	F411-1-1-20	Wood Core
BASF SE	20 minute	А	F411-1-2-20	Composite Core
BASF SE	45 minute	А	F411-1-1-45	Composite Core
BASF SE	60 minute	А	F411-1-1-60	Composite Core
BASF SE	90 minute	Α	F411-1-1-90	Composite Core

## **Fire Resistance Rated Door Frames**

Spec Owner	Fire Rating	Category	Listing #	Description
BASF SE	20 minute	С	F411-2-20	Composite Frame
BASF SE	45 minute	С	F411-2-45	Composite Frame
BASF SE	60 minute	С	F411-2-60	Composite Frame
BASF SE	90 minute	С	F411-2-90	Composite Frame



VANCOUVER, BC: LOS ANGELES, CA: TORONTO, ON: TULSA, OK: MIAMI. FL:

WEBSITE:

877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 905.605.5444 ph. 918.437.8333 ph. | 918.437.8487 fx. 305.885.3328 ph. | 305.885.3329 fx.

WWW.QAI.ORG

- **Notes:** Refer to QAI evaluation reports F469-1 and F469-2 and the applicable test reports for test assembly configurations used for fire endurance testing.
  - Refer to the QAI FD002 Fire Door Guidelines for general guidelines of fire door <u>assemblies</u>
  - Final acceptance of the product in the intended application is to be determined by the authority having jurisdiction (AHJ).
  - Product is to be installed in accordance with the manufacturer's published installation instructions by qualified installing personnel.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@gai.org. Please include the listing number in the request.

\*\*\*