VANCOUVER, BC: LOS ANGELES, CA: TORONTO, ON: TULSA, OK: MIAMI, FL: WEBSITE:

877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 905.605.5444 ph. 918.437.8333 ph. | 305.885.3328 ph. | 305.885.3329 fx. WWW.QAI.ORG

909.483.0336 fx. 918.437.8487 fx.

## FIRE DOOR LISTING PROGRAM

Customer: Rolling Door Industries LLC

Class: Fire Resistant Doors

Location: Miami, Florida

Website: www.rolling-door.com

Listing No. F470-1

Project No. F470-1 Edition 1

Effective Date: October 16, 2020 Last Revised Date: October 16, 2020

> Expires: N/A

Standards: **UL 10B** Standard for Fire Tests of Door Assemblies

> Standard Method for Fire Tests of Door Assemblies CAN/ULC-S104 UL 1784 Standard for Air Leakage Tests of Door Assemblies and

> > Other Opening Protectives

Product: 180 minute Neutral Pressure rated Fire Doors

Markings: Refer to QAI evaluation report # F470-1

Models: **180-MINUTE STEEL ROLLING DOORS:** 

Description	<b>Maximum Dimensions</b>		Door Type
	Width:	Height:	Door Type
Steel Rolling Door	10'0"	10'0"	Interlocking Metal Slats
(Fire Rated only)	(3048 mm)	(3048 mm)	
Steel Rolling Door	10'0"	10'0"	Interlocking Metal Slats
(Fire and Smoke Rated)	(3048 mm)	(3048 mm)	

Permitted Slat Options		
Material:	<ul><li>Galvanized steel</li><li>Stainless steel</li></ul>	
Metal gauge:	<ul><li>22 gauge</li><li>20 gauge</li><li>18 gauge</li></ul>	
Finish:	<ul> <li>Bake on enamel paint</li> <li>Powder coat paint</li> <li>Unpainted galvanized or stainless steel</li> </ul>	
Insulation:	<ul> <li>No insulaton – no back slat required</li> <li>16 mm (5/8 in.) thickness mineral wool with 24 gauge back slat.</li> </ul>	



VANCOUVER, BC: LOS ANGELES, CA: TORONTO, ON: TULSA, OK: MIAMI, FL: WEBSITE:

877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. 905.605.5444 ph. 918.437.8333 ph. 305.885.3328 ph. | WWW.QAI.ORG

909.483.0336 fx. 918.437.8487 fx. 305.885.3329 fx.

Refer to QAI evaluation report F470-1 and the applicable test reports for test Notes: assembly configurations used for fire endurance testing.

Final acceptance of the product in the intended application is to be determined by the authority having jurisdiction (AHJ).

Product is to be installed in accordance with the manufacturer's published installation instructions by qualified installing personnel.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.