

PLUMBING PRODUCTS LISTING PROGRAM

Customer: Vista Water Group, LLC

Class: **Dual Check Backflow Preventers**

Location: Ashland, OH

Website: https://vistawatergroup.com

P379-2 Listing No.

Effective Date: December 13, 2021 Last Revised Date: August 5, 2025

> Expires: N/A

Standards: ASME A112.18.1 / CSA B125.1 Plumbing Supply Fittings.

> Performance Requirements for Backflow ASSE A112.18.3

> > Protection Devices And Systems In

Plumbing Fixture Fittings

ASSE 1024 Performance Requirements for Dual

Check Backflow Preventers.

ASSE 1032 Performance Requirements for Dual

Check Backflow Preventers for

Carbonated Beverage Dispensers, Post

Mix Type.

NSF 61 Drinking Water System Components -

Health Effects.

Drinking Water System Components -NSF 372

Lead Content.

Product: Vista Dual Check Backflow Preventers of the Following Types:

MODELS		
PVC	Anodized Aluminum	
VCB025-P	VCB025-A	
VCB038-P	VCB038-A	
VC050-P	VC050-A	
VC075-P	VC075-A	
VC100-P	VC100-A	
VC125-P	VC125-A	
VC150-P	VC150-A	
VC250-A	-	
VC250-B	-	
VC025-QC	-	
VC038-QC	-	

Markings: Products are marked in a permanent manner where it is readily visible after

installation with the following:

a) Manufacturer's name or trademark



VANCOUVER, BC: LOS ANGELES, CA: TULSA, OK: TORONTO, ON WEBSITE: 877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 918.437.8333 ph. | 918.437.8487 fx. 905.605.5444 WWW.QAL.ORG

b) Model designation

- c) The wording "ASME A112.18.1 / CSA B125.1", "ASME A112.18.3" or "ASME 1024", or "ASSE 1032" as appropriate.
- d) QAI logo with 'c' and 'us' or "us" identifier as outlined below as appropriate.
- e) QAI file Number: P379-2





or

*cQAlus mark applied to products compliant with CSA B125.1 products.

Ratings: Vista Water Group Dual Check Backflow Preventers comply with the requirements as outlined below.

Table 1. Vista Water Group Dual Check Backflow Preventer Specifications

MODEL	DESCRIPTION	SPECIFICATION
VC250-A ¹	Dual check backflow preventer with ¼" push-to-connect end connections.	ASME A112.18.1 / CSA B125.1, ASME A112.18.3 Compliant.
VC250-B ¹	Dual check backflow preventer with 3/8" push-to-connect end connections.	ASME A112.18.1 / CSA B125.1 , ASME A112.18.3 Compliant.
VC025-QC ¹	Dual check backflow preventer with 1/4" push-to-connect end connections.	ASME A112.18.1 / CSA B125.1, ASME A112.18.3 Compliant.
VC038-QC ¹	Dual check backflow preventer with 3/8" push-to-connect end connections.	ASME A112.18.1 / CSA B125.1, ASME A112.18.3 Compliant.
VC050-A to VC150-A ¹	Dual check backflow preventer with ½" to 1-1/2" valves – Aluminum	ASME A112.18.1 / CSA B125.1, ASME A112.18.3, and ASSE 1024 Compliant.
VC050-P to VC150-P1	Dual check backflow preventer with ½" to 1-1/2" valves - PVC	ASME A112.18.1 / CSA B125.1, ASME A112.18.3, and ASSE 1024 Compliant.
VCB025-A to VCB038-A ¹	Dual check backflow preventer with 1/4" and 3/8" valves for use with carbonated beverage dispensers - Aluminum	ASME A112.18.1 / CSA B125.1, ASME A112.18.3, ASSE 1024, and ASSE 1032 Compliant.
VCB025-P to VCB038-P1	Dual check backflow preventer with ¼" and 3/8" valves for use with carbonated beverage dispensers - PVC	ASME A112.18.1 / CSA B125.1, ASME A112.18.3, ASSE 1024, and ASSE 1032 Compliant.

Note 1: Products have been found eligible for use in potable water systems based on evaluation to NSF 61 and NSF 372 requirements.

•

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.
