VANCOUVER, BC: LOS ANGELES, CA: TULSA, OK: TORONTO, ON WEBSITE:

877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 918.437.8333 ph. | 918.437.8487 fx. 905.605.5444 WWW.QAI.ORG

BUILDING PRODUCTS LISTING PROGRAM

Customer: Eternit Colombiana S.A.
Class: Fiber-Cement Siding
Location: Valle del Cauca, Colombia

Website: www.eternit.com.co

Listing No. B1133-1

Effective Date: March 31, 2022 Last Revised July 12, 2022

Expiration: N/A

Standards: ASTM C1186 Standard Specification for Flat Fiber-Cement Sheets.

ASTM E84 Standard Test Method for Surface Burning Characteristics of

Building Materials.

ASTM E136 Standard Test Method for Behavior of Materials in a Vertical

Tube Furnace of 750°C.

Product(s): Eternit Grade II Type A Fiber-Cement siding products.

Markings: Products are labeled with the following information:

a) Company Name: Eternit Colombiana S.A.b) ASTM C1186 Grade II Type A Compliant.

c) ASTM E84 Flame Spread Smoke Developed Index (FSI ≤ 0 / SDI ≤ 5)

d) Classified Non-combustible / ASTM E136 compliant.

e) Traceability code including date of manufacture.

f) QAI Mark as shown below:



VANCOUVER, BC: LOS ANGELES, CA: TULSA, OK: TORONTO, ON WEBSITE: 877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 918.437.8333 ph. | 918.437.8487 fx. 905.605.5444 WWW.QALORG

Ratings: Eternit fiber-cement siding of 5/16" – 25/32" (8 mm – 20 mm) thickness complies with Grade II Type A requirements per ASTM C1186.

Eternit Grade II Type A fiber-cement siding has the following surface burning characteristics determined in accordance with ASTM E84.

ETERNIT FIBER-CEMENT SIDING SURFACE BURNING CHARACTERISTICS PER ASTM E841				
PRODUCTS	THICKNESSES		FLAME SPREAD	SMOKE DEVELOPED
	inches	mm	INDEX	INDEX
Grade II Type A Siding	5/16 – 25/32	8 - 20	≤ 0	≤ 5

Eternit fiber-cement siding is classified non-combustible complying with ASTM E136 requirements.

Note: Final acceptance of the product in the intended application is to be determined by the authority having jurisdiction.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.
