

BUILDING PRODUCT LISTING PROGRAM

Customer: Westlake Royal Roofing LLC
Class: Concrete Roof Tiles
Location: 2801 Post Oak Blvd., Suite 600
Houston, TX 77056
Website: www.WestlakeRoyalBuildingProducts.com

Listing No. B1044-2
Report No. B1044-2, Edition 10

Effective Date: March 29, 2012
Last Revised
Date: July 17, 2026
Expires: <N/A>

Standards: CSA A220.0-06(R2021) *Concrete Roof Tiles.*
CAN/ULC S107:2019 *Standard Methods of Fire Tests of Roof Coverings.*
ASTM E 108-20a *Standard Specification for Fire Tests of Roof Coverings.*
FM 4473-2011 *Test Standard for Impact Resistance Testing of Rigid Roofing Materials by Impacting with Freezer Ice Balls.*

Product: NewPoint® Concrete Roof Tiles

Markings: Products are palletized and marked with a label that includes the following information.

- a) Manufacturer's name (NewPoint®)
- b) Tile Profile
- c) SAP Number
- d) QAI file Number: B1044-2
- e) The wording "CSA A220"(when applicable)
- f) FM 4473 Class "rating" (when applicable)
- g) ASTM E108 / CAN/ULC S107 Class A
- h) QAI logo shown here*:



OR



*Products recognized in the CSA A220 table below are labeled with the cQAIus mark. All other profiles and locations will have the QAIus mark.



Models /
Ratings:

Product Name	Saxony 900/Saxony -Slate, Shake, Country Slate, Old English Thatch, Hartford Slate	Saxony 700 – Slate, Shake, Split Shake	Saxony 600-Slate, Shake, Split Shake
Length, in	16.5 - 17	17	17
Width, in	13	13	13
Height, in	1.141-1.375 Slate 1.188-1.500 Shake	1.063 Slate 1.125 Shake	1.000 Slate 1.125 Shake
Mass, lbs	10.6 - 10.9	8.6	7.39
Installed Weight, psf	9.1 – 10.3	7.2	5.9
Manufacturing Locations	Denver, CO Henderson, NV Lake Wales, FL Lathrop, CA Phoenix, AZ Okeechobee, FL Rialto, CA	Rialto, CA Lathrop, CA	Rialto, CA
Product Name	Saxony Impact		
Length, in	16.5 - 17		
Width, in	13		
Height, in	1.438		
Mass, lbs	11.8 – 11.94		
Installed Weight, psf	10.2 – 10.8		
Manufacturing Locations	Denver, CO		
Product Name	Villa 900/Villa	Villa 600	Villa Impact
Length, in	16.5 - 17	17	17
Width, in	13	13	13
Height, in	2.125 – 2.188	2.125	2.313
Mass, lbs	9.9 – 10.6	6.85	11.07
Installed Weight, psf	9.0 – 9.3	5.8 – 6.0	9.7
Manufacturing Locations	Denver, CO Lake Wales, FL Rialto, CA Phoenix, AZ Lathrop, CA	Rialto, CA	Denver, CO



Product Name	Barcelona/España 900	Barcelona/España 600	Mission S/Barcelona
Length, in	17	17	16.5
Width, in	12.375 - 13	12.375-13	13
Height, in	3.625	3.625	3.5
Mass, lbs	9.7 - 10.6	6.7	10.2
Installed Weight, psf	9.0 – 9.5	5.9	10.3
Manufacturing Locations	Henderson, NV Lake Wales, FL Lathrop, CA Rialto, CA	Rialto, CA	Phoenix, AZ
Product Name	Bermuda	Spanish “S” Nuevo	
Length, in	16.125	17	
Width, in	10.063	9.75	
Height, in	1.188 Slate 1.25 Broomed	2.844	
Mass, lbs	9.44	8.5	
Installed Weight, psf	11.62	9.94	
Manufacturing Locations	Okeechobee, FL	Lake Wales, FL	
Product Name	Estate “S”	Galena Spanish “S”	Plantation
Length, in	16.5	17	16.5
Width, in	13	10	13
Height, in	2.375	2.688	1.156 Slate 1.219 Shake
Mass, lbs	9.71	8.30	11.33
Installed Weight, psf	8.79	9.42	10.47
Manufacturing Locations	Okeechobee, FL	Okeechobee, FL	Okeechobee, FL
Product Name	Cedarlite 600	Madera 900	Madera 700
Length, in	13.5	13.5	13.5
Width, in	13	13	13
Height, in	0.875	0.875	0.875
Mass, lbs	4.95	7.9	6.1
Installed Weight, psf	5.9	9.6	7.45
Manufacturing Locations	Denver, CO	Denver, CO	Denver, CO

Product Name	Capri	Rake	Ridge
Length, in	16.875	16.875	16.875
Width, in	Nose side 9.875 Head side 9.125	8.25	10.5
Height, in	Head Height 3.25 Nose Height 4.063	4.125	2.875
Mass, lbs	7.20	8.45	7.65
Installed Weight, psf	N/A	N/A	N/A
Manufacturing Locations	Lathop, CA	Lathop, CA	Lathop, CA

Class A Roofing Assembly: Unlimited Slope
-In accordance with ASTM E108 and CAN/ULC S107

Sheathing	Underlayment	Roof Covering
Minimum 15/32-inch AC Exterior Plywood	Minimum one-layer Type II (No. 30) asphalt-saturated felt complying with ASTM D226/CSA A123.3, Type 2.	Saxony/Saxony 900 Saxony 700 Saxony 600 Saxony Impact Villa Villa/Villa 900 Villa 600 Villa Impact Barcelona/Espana 900 Barcelona/Espana 600 Mission S/Barcelona Spanish "S" Nuevo Bermuda Estate "S" Galena Spanish "S" Plantation Cedarlite 600 Madera 900 Madera 700 Capri
	Minimum one layer of Sol- R-Skin® BLUE underlayment mechanically fastened with a head overlap of 6-inches.	
	Minimum one layer of Fyratek™ Ember Resistant Underlayment	

Installation is approved for unlimited slope.

Underlayment is to be installed in accordance with the applicable code, the manufacturers installation instructions and the above detail. Where differences exist, the applicable code and above detail should be followed.

Installation of the roof covering is to be in accordance with the applicable code, and the manufacturer's installation instructions for resisting intended service loads.

CSA A220 approved profiles

Manufacturing Location	Profile
Lathrop, CA	Barcelona 900
	Villa 900
	Saxony 900/Saxony-Slate, Shake, Country Slate, Old English Thatch, Hartford Slate
	Ridge
	Rake
	Capri

Products noted above are evaluated in accordance with CSA A220.0.
 Installation is to be in accordance with the CSA A220.1 and the applicable code.

Impact Resistant Assemblies -In accordance with FM 4473

Sheathing	Underlayment	Roof Covering	Location	Class
Minimum 15/32-inch AC Exterior Plywood	Unrestricted	Saxony Impact	Denver	Class 4
		Mission S/Barcelona	Phoenix	Class 3
			Rialto	
			Henderson	
		Saxony	Denver	
			Phoenix	
		Villa/Villa 900	Denver	
			Lathrop	
		Madera 900	Denver	

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.
