

WINDOWS & DOORS LISTING PROGRAM

Customer: Wintegra Windows Inc.
Class: Fenestration Products – Energy Performance
Location: Abbotsford, British Columbia
Website: www.wintegra.ca

Listing No. W591-2
Project No. W591-2 ED1
Effective Date: May 21, 2026
Last Revised Date: May 21, 2026
Expires: N/A

Standards: CSA A440.2-19 “Fenestration Energy Performance”

Product: Vinyl Doors

Markings: Products are marked with the following content in a permanent manner where it is readily visible after installation:

- a) Manufacturer’s name, Trademark or other recognized symbol or identification.
- b) QAI file Number: W591
- c) QAI logo shown here:



- d) “Evaluation for energy performance in accordance with CSA A440.2” / “Évalué pour la performance d’énergie en accord à la norme CSA A440.2”

Models / Ratings:
5000 Series Lift & Slide Door

GO #	Model Code	U-Value (W/m ² K)	Product SHGC	Energy Rating
G01	WIN-5000LSD-4,180(2)-4,CL-16AR90SS	1.53	0.4	N/A
G02	WIN-5000LSD-4,270(2)-4,CL-16AR90SS	1.48	0.24	N/A
G03	WIN-5000LSD-5,270(2)-5,CL-16AR90SS	1.48	0.23	N/A
G04	WIN-5000LSD-6,270(2)-6,CL-13AR90SS	1.46	0.23	N/A
G05	WIN-5000LSD-4,366(2)-4,CL-16AR90SS	1.46	0.18	N/A
G06	WIN-5000LSD-5,366(2)-5,CL-16AR90SS	1.46	0.18	N/A
G07	WIN-5000LSD-7,366L(2)-5,CL-13AR90SS	1.43	0.18	N/A
G08	WIN-5000LSD-4,180(2)-4,CL-4,180(5)-16AR90SS	1.01	0.35	N/A
G09	WIN-5000LSD-4,270(2)-4,CL-4,270(5)-16AR90SS	0.98	0.2	N/A
G10	WIN-5000LSD-4,270(2)-4,270(4)-4,CL-16AR90SS	0.98	0.18	N/A
G11	WIN-5000LSD-4,270(2)-4,270(4)-5,i89(6)-16AR90SS	0.92	0.18	N/A
G12	WIN-5000LSD-5,180(2)-5,CL-5,180(5)-14AR90SS	1.02	0.34	N/A
G13	WIN-5000LSD-5,270(2)-5,CL-5,270(5)-14AR90SS	0.98	0.2	N/A
G14	WIN-5000LSD-5,270(2)-5,270(4)-5,i89(6)-14AR90SS	0.92	0.18	N/A
G15	WIN-5000LSD-6,270(2)-6,CL-6,270(5)-13AR90SS	1.00	0.2	N/A

4700 Series In-Swing Side-Hinged Door With Aluminum Sill & Steel Reinforcement

GO #	Model Code	U-Value (W/m ² K)	Product SHGC	Energy Rating
G01	WIN-A4700ISHD-4,180(2)-4,CL-16AR90SS-R1	1.51	0.39	28
G02	WIN-A4700ISHD-4,270(2)-4,CL-16AR90SS-R1	1.47	0.23	20
G03	WIN-A4700ISHD-7,270L(2)-4,CL-16AR90SS-R1	1.46	0.22	20
G04	WIN-A4700ISHD-4,366(2)-4,CL-16AR90SS-R1	1.45	0.17	17
G05	WIN-A4700ISHD-5,180(2)-5,CL-16AR90SS-R1	1.51	0.39	29
G06	WIN-A4700ISHD-5,270(2)-5,CL-16AR90SS-R1	1.47	0.23	20
G07	WIN-A4700ISHD-7,270L(2)-5,CL-16AR90SS-R1	1.46	0.22	20
G08	WIN-A4700ISHD-5,366(2)-5,CL-16AR90SS-R1	1.45	0.17	17
G09	WIN-A4700ISHD-4,270(2)-4,CL-4,CL-16AR90SS-R1	1.19	0.21	25
G10	WIN-A4700ISHD-4,366(2)-4,CL-4,CL-16AR90SS-R1	1.18	0.16	22
G11	WIN-A4700ISHD-4,270(2)-4,CL-4,270(5)-16AR90SS-R1	0.98	0.19	29
G12	WIN-A4700ISHD-4,270(2)-4,270(4)-4,CL-16AR90SS-R1	0.98	0.18	28
G13	WIN-A4700ISHD-5,270(2)-5,CL-5,CL-14AR90SS-R1	1.19	0.21	25
G14	WIN-A4700ISHD-5,366(2)-5,CL-5,CL-14AR90SS-R1	1.18	0.16	22
G15	WIN-A4700ISHD-5,270(2)-5,CL-5,270(5)-14AR90SS-R1	0.98	0.19	29
G16	WIN-A4700ISHD-5,270(2)-5,270(4)-5,CL-14AR90SS-R1	0.98	0.18	28
G17	WIN-A4700ISHD-4,180(2)-4,CL-4,CL-16AR90SS-R1	1.22	0.36	33
G18	WIN-A4700ISHD-4,180(2)-4,CL-4,180(5)-16AR90SS-R1	1.01	0.34	37
G19	WIN-A4700ISHD-4,366(2)-4,CL-4,366(5)-16AR90SS-R1	0.96	0.15	27
G20	WIN-A4700ISHD-4,270(2)-4,CL-4,366(5)-16AR90SS-R1	0.96	0.17	28
G21	WIN-A4700ISHD-4,180(2)-4,CL-16AR90SS-R1-G1>1	1.51	0.29	23
G22	WIN-A4700ISHD-4,270(2)-4,CL-16AR90SS-R1-G1>1	1.47	0.17	17
G23	WIN-A4700ISHD-4,366(2)-4,CL-16AR90SS-R1-G1>1	1.45	0.13	15
G24	WIN-A4700ISHD-5,180(2)-5,CL-16AR90SS-R1-G1>1	1.51	0.29	23
G25	WIN-A4700ISHD-5,270(2)-5,CL-16AR90SS-R1-G1>1	1.47	0.17	17
G26	WIN-A4700ISHD-5,366(2)-5,CL-16AR90SS-R1-G1>1	1.45	0.13	15
G27	WIN-A4700ISHD-4,270(2)-4,CL-4,CL-16AR90SS-R1-G1>1	1.19	0.16	22
G28	WIN-A4700ISHD-4,366(2)-4,CL-4,CL-16AR90SS-R1-G1>1	1.18	0.12	20
G29	WIN-A4700ISHD-5,270(2)-5,CL-5,CL-14AR90SS-R1-G1>1	1.19	0.16	22
G30	WIN-A4700ISHD-5,366(2)-5,CL-5,CL-14AR90SS-R1-G1>1	1.18	0.12	20
G31	WIN-A4700ISHD-5,270(2)-5,270(4)-5,CL-14AR90SS-R1-G1>1	0.98	0.14	26

4700 Series In-Swing Side-Hinged Door With PVC Sill & Steel Reinforcement

GO #	Model Code	U-Value (W/m ² K)	Product SHGC	Energy Rating
G01	WIN-P4700ISHD-4,180(2)-4,CL-16AR90SS-R1	1.48	0.39	29
G02	WIN-P4700ISHD-4,270(2)-4,CL-16AR90SS-R1	1.43	0.22	20
G03	WIN-P4700ISHD-7,270L(2)-4,CL-16AR90SS-R1	1.43	0.22	20
G04	WIN-P4700ISHD-4,366(2)-4,CL-16AR90SS-R1	1.41	0.17	18
G05	WIN-P4700ISHD-5,180(2)-5,CL-16AR90SS-R1	1.48	0.38	29
G06	WIN-P4700ISHD-5,270(2)-5,CL-16AR90SS-R1	1.44	0.22	20
G07	WIN-P4700ISHD-7,270L(2)-5,CL-16AR90SS-R1	1.43	0.22	20
G08	WIN-P4700ISHD-5,366(2)-5,CL-16AR90SS-R1	1.42	0.17	18
G09	WIN-P4700ISHD-4,270(2)-4,CL-4,CL-16AR90SS-R1	1.17	0.21	26
G10	WIN-P4700ISHD-4,366(2)-4,CL-4,CL-16AR90SS-R1	1.15	0.16	23
G11	WIN-P4700ISHD-4,270(2)-4,CL-4,270(5)-16AR90SS-R1	0.95	0.19	29
G12	WIN-P4700ISHD-4,270(2)-4,270(4)-4,CL-16AR90SS-R1	0.95	0.18	29
G13	WIN-P4700ISHD-5,270(2)-5,CL-5,CL-14AR90SS-R1	1.16	0.21	26
G14	WIN-P4700ISHD-5,366(2)-5,CL-5,CL-14AR90SS-R1	1.15	0.16	23
G15	WIN-P4700ISHD-5,270(2)-5,CL-5,270(5)-14AR90SS-R1	0.95	0.19	29
G16	WIN-P4700ISHD-5,270(2)-5,270(4)-5,CL-14AR90SS-R1	0.95	0.17	28
G17	WIN-P4700ISHD-4,180(2)-4,CL-4,CL-16AR90SS-R1	1.19	0.36	34
G18	WIN-P4700ISHD-4,180(2)-4,CL-4,180(5)-16AR90SS-R1	0.99	0.34	37
G19	WIN-P4700ISHD-4,366(2)-4,CL-4,366(5)-16AR90SS-R1	0.94	0.15	27
G20	WIN-P4700ISHD-4,270(2)-4,CL-4,366(5)-16AR90SS-R1	0.94	0.17	28
G21	WIN-P4700ISHD-4,180(2)-4,CL-16AR90SS-R1-G1>1	1.48	0.29	23
G22	WIN-P4700ISHD-4,270(2)-4,CL-16AR90SS-R1-G1>1	1.43	0.17	18
G23	WIN-P4700ISHD-4,366(2)-4,CL-16AR90SS-R1-G1>1	1.41	0.13	16
G24	WIN-P4700ISHD-5,180(2)-5,CL-16AR90SS-R1-G1>1	1.48	0.28	23
G25	WIN-P4700ISHD-5,270(2)-5,CL-16AR90SS-R1-G1>1	1.44	0.17	17
G26	WIN-P4700ISHD-5,366(2)-5,CL-16AR90SS-R1-G1>1	1.42	0.13	15
G27	WIN-P4700ISHD-4,270(2)-4,CL-4,CL-16AR90SS-R1-G1>1	1.17	0.16	23
G28	WIN-P4700ISHD-4,366(2)-4,CL-4,CL-16AR90SS-R1-G1>1	1.15	0.12	21
G29	WIN-P4700ISHD-5,270(2)-5,CL-5,CL-14AR90SS-R1-G1>1	1.16	0.16	23
G30	WIN-P4700ISHD-5,366(2)-5,CL-5,CL-14AR90SS-R1-G1>1	1.15	0.12	21
G31	sWIN-P4700ISHD-5,270(2)-5,270(4)-5,CL-14AR90SS-R1-G1>1	0.95	0.13	26

4700 Series In-Swing Side-Hinged Door With PVC Sill & Foam Insulation

GO #	Model Code	U-Value (W/m ² K)	Product SHGC	Energy Rating
G01	WIN-P4700ISHD-4,180(2)-4,CL-16AR90SS-F1	1.35	0.39	32
G02	WIN-P4700ISHD-4,270(2)-4,CL-16AR90SS-F1	1.31	0.22	23
G03	WIN-P4700ISHD-4,366(2)-4,CL-16AR90SS-F1	1.29	0.17	21
G04	WIN-P4700ISHD-5,270(2)-5,CL-16AR90SS-F1	1.31	0.22	23
G05	WIN-P4700ISHD-5,366(2)-5,CL-16AR90SS-F1	1.29	0.17	21
G06	WIN-P4700ISHD-4,270(2)-4,CL-4,270(5)-16AR90SS-F1	0.82	0.19	32
G07	WIN-P4700ISHD-4,270(2)-4,270(4)-4,CL-16AR90SS-F1	0.82	0.18	32
G08	WIN-P4700ISHD-4,270(2)-4,270(4)-5,i89(6)-16AR90SS-F1	0.76	0.17	32
G09	WIN-P4700ISHD-4,366(2)-4,CL-4,366(5)-16AR90SS-F1	0.81	0.15	30
G10	WIN-P4700ISHD-5,270(2)-5,CL-5,270(5)-14AR90SS-F1	0.82	0.19	32
G11	WIN-P4700ISHD-5,270(2)-5,270(4)-5,CL-14AR90SS-F1	0.82	0.17	31
G12	WIN-P4700ISHD-5,270(2)-5,270(4)-5,i89(6)-14AR90SS-F1	0.76	0.17	32
G13	WIN-P4700ISHD-4,180(2)-4,CL-4,CL-16AR90SS-F1	1.06	0.36	37
G14	WIN-P4700ISHD-4,180(2)-4,CL-4,180(5)-16AR90SS-F1	0.86	0.34	40
G15	WIN-P4700ISHD-4,270(2)-4,CL-4,366(5)-16AR90SS-F1	0.81	0.17	31
G16	WIN-P4700ISHD-4,180(2)-4,CL-16AR90SS-F1-G1>1	1.35	0.29	26
G17	WIN-P4700ISHD-4,270(2)-4,CL-16AR90SS-F1-G1>1	1.31	0.17	20
G18	WIN-P4700ISHD-4,366(2)-4,CL-16AR90SS-F1-G1>1	1.29	0.13	18
G19	WIN-P4700ISHD-5,270(2)-5,CL-16AR90SS-F1-G1>1	1.31	0.17	20
G20	WIN-P4700ISHD-5,366(2)-5,CL-16AR90SS-F1-G1>1	1.29	0.13	18
G21	WIN-P4700ISHD-4,270(2)-4,CL-4,270(5)-16AR90SS-F1-G1>1	0.82	0.15	30
G22	WIN-P4700ISHD-5,270(2)-5,CL-5,270(5)-14AR90SS-F1-G1>1	0.82	0.14	29
G23	WIN-P4700ISHD-5,270(2)-5,270(4)-5,i89(6)-14AR90SS-F1-G1>1	0.76	0.13	30

Notes:

- Windows and doors are not intended for installation in storefronts, non-operable portions of curtain wall, fixed glazing cast into precast concrete panels, greenhouses, skylights or sloped glazing.
- Test procedures are designed to test the performance of the test specimen only and are not necessarily used to test the performance of the installation, particularly the perimeter sealant joint and anchoring of the assembly.
- The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI.
- No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing.
- Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.