

BUILDING PRODUCTS LISTING PROGRAM

Customer: Wildhawk Investments, LLC dba Brava Roof Tile
Class: Plastic Roof Tiles
Location: 915 E. Tyler Street, Washington, IA
Website: www.bravarooftile.com

Listing No. B1138
Effective Date: August 30, 2022
Last Revised Date: August 17, 2026

Standards: ASTM E108-20a *Standard Test Methods for Fire Tests of Roof Coverings.*
UL 790-2022 *Standard Test Methods for Fire Tests of Roof Coverings.*
UL 2218-22 *Impact Resistance of Prepared Roof Covering Materials.*

Products: Brava Roof Tile roof coverings are polymeric products available in the following models:

- Brava Slate
- Brava Cedar Shake
- Brava Spanish Barrel Tile
- Brava Flat Tile

Markings: Listed products are identified with the following information:

- Address of manufacture
- Product Name
- Date of Manufacture
- Standards "UL2218", "ASTM E108" or "UL 790"
- QAI logo shown here:



Ratings: The following outlines roof-fire classified assemblies determined in accordance with ASTM E108 / UL 790 and UL 2218:

Assembly 1: Class A Roofing Applications: Unlimited Slope

SHEATHING	UNDERLAYMENT	APPROVED ROOF COVERING(s)	Maximum Exposure (inches)
Minimum 15/32" (12mm) Exposure 1 Plywood	1 layer of ASTM D226 Type II asphalt felt, with joints overlapped minimum 6 inches (152 mm).	Brava Slate Class A Brava Cedar Shake Class A Brava Spanish Barrel Tile Class A	10 10 13
Minimum 15/32" (12mm) Exposure 1 Plywood	1 layer of 4LMPX Low-E Therma Sheet underlayment with joints overlapped minimum 4 inches (102 mm).	Brava Slate Brava One Brava Cedar Shake Brava One	10 10
Minimum 15/32" (12mm) Exposure 1 Plywood	1 layer of Eco Chief Solarhide underlayment with joints overlapped minimum 4 inches (102 mm).	Brava Slate Brava One Brava Cedar Shake Brava One	10 10

Assembly 2: Class C Roofing Applications: Unlimited Slope

SHEATHING	UNDERLAYMENT ¹	APPROVED ROOF COVERING(s) ²	Maximum Exposure (inches)
Minimum 15/32" (12mm) Exposure 1 Plywood	1 layer of ASTM D226 Type II asphalt felt, with joints overlapped minimum 6 inches (152 mm).	Brava Slate Brava One Brava Cedar Shake Brava One Brava Spanish Barrel Tile Brava One	10 10 13
Minimum 15/32" (12mm) Exposure 1 Plywood	1 layer of Intertape Polymer Group® Palisade® synthetic underlayment, overlapped minimum 4 inches (102 mm).	Brava Flat Tile Brava One	14

Assembly 3: Impact Resistant (Class 4) Applications: Unlimited Slope

SHEATHING	UNDERLAYMENT ¹	APPROVED ROOF COVERING(s) ²	Maximum Exposure (inches)
Minimum 15/32" (12 mm) Exposure 1 Plywood	Unrestricted	Brava Slate Class A Brava Cedar Shake Class A Brava Spanish Barrel Tile Class A Brava Slate Brava One Brava Cedar Shake Brava One Brava Spanish Barrel Tile Brava One Brava Flat Tile Brava One	10 10 13 10 10 13 14

Note 1: Underlayment components are to be installed in accordance with the manufacturer's published installation instructions.

Note 2: These products are listed and labeled under QAI's certification program.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.
