

VANCOUVER, BC: LOS ANGELES, CA: WASHINGTON, DC: TULSA, OK: TORONTO, ON WEBSITE: 877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 540.636.9445 ph. | 540.636.9414 fx. 918.437.8333 ph. | 918.437.8487 fx.

416.550.9280 WWW.QAI.ORG

FIRE DOORS LISTING PROGRAM

Customer: Arista Custom Doors Inc.

Class: Fire Doors Location: North York, ON

Website: www.aristadoors.com

Listing No. F479-1

Project No. F479-1 Edition 1

Effective Date: June 6, 2022 Last Revised Date: June 6, 2022

Standards: CAN/ULC-S104 Standard Method for Fire Tests of Door Assemblies.

UL 10B Fire Tests of Door Assemblies.

Product: 20-minute Rated Fire-Resistant Doors

Labels: See <u>FD001 - Fire Door Labeling requirements</u>

Models: 20-MINUTE WOOD CORE PANEL DOORS:

Minimum 44 mm (1-3/4") Thickness

Swing Type:	Maximum Dimensions		Panel	Letchings
	Width:	Length:	Type:	Latching:
Single Swing	950 mm (3'0")	2750 mm (9'0")	Flush	Single Point (Mortised or Cylindrical)
	1250 mm (4'0")	2450 mm (8'0")		

Limitations: (Review Machining Report for further detail)

- Cylindrical Latches (Listed and Labelled)
- Mortise Lockset (Listed and Labelled)
- Deadbolts (Listed and Labelled)
- Viewers (Listed and Labelled)
- Surface Mounted Door Closer (Listed and Labelled)
- Glass Lights (Listed and Labelled)
 - Maximum area of exposed glass per door leaf is 0.064 m² (Max. width of 255 mm, Max. height of 635 mm).
- Surface Mounted Door Bottom (Listed and Labelled)
- Surface Mounted Protection Plates

Notes: Refer to QAI evaluation report F479-1 for evidence supporting product

certification.

Refer to the QAI FD002 - Fire Door Guidelines for general guidelines of fire door assemblies



VANCOUVER, BC: LOS ANGELES, CA: WASHINGTON, DC: TULSA, OK: TORONTO, ON WEBSITE: 877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 540.636.9445 ph. | 540.636.9414 fx. 918.437.8333 ph. | 918.437.8487 fx. 416.550.9280 WWW.QAI.ORG

Final acceptance of the product in the intended application is to be determined by the authority having jurisdiction (AHJ).

Product is to be installed in accordance with the manufacturer's published installation instructions by qualified installing personnel.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.
