

VANCOUVER, BC: LOS ANGELES, CA: WASHINGTON, DC: TULSA, OK: TORONTO, ON WEBSITE: 877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 540.636.9445 ph. | 540.636.9414 fx. 918.437.8333 ph. | 918.437.8487 fx. 416.550.9280

WWW.QAI.ORG

FIRE DOORS LISTING PROGRAM

Customer: Acemar Triplex S.A.S. Inc.

Class: Fire Doors Location: Largo, FL, USA

Website: https://www.acemar.us/

Listing No. F485

Project No. F485-2 Edition 1

Effective Date: July 12, 2023 Last Revised Date: July 12, 2023

Standards: CAN/ULC-S104 Standard Method for Fire Tests of Door Assemblies.

UL 10B Standard for Fire Tests of Door Assemblies.

UL 10C Standard for Positive Pressure Fire Tests of Door Assemblies.

Product: ACEMAR 20-MINUTE CATEGORY "C" FIRE-RESISTANT DOOR FRAMES

Labels: See FD001 - Fire Door Labeling requirements

Models / Ratings: 20-MINUTE CATEGORY C POPRIETARY WOOD TYPE FIRE DOOR

FRAMES:

Maximum sizes:

Swing Type:	Maximum Dimensions	
	Height:	Width:
Single Swing	94 5/8 in. (2406 mm)	40 in. (1017 mm)
Pairs	Not Permitted	
Double Egress	Not Permitted	

Limitations:

Permitted door types: Wood doors.
 Minimum frame depth: 6-1/2" (165 mm)

• Maximum frame leg depth: Equivalent to wall depth.

Minimum frame leg thickness: 2-1/4" (57 mm)
Stop Thickness: 5/8" (16 mm)

• Closers: Residential Frame: Surface Mounted Closers are permitted.

Commercial Frame: Concealed Closers are permitted of

maximum 1-3/8" (35 mm) x 1" (25 mm) depth.



VANCOUVER, BC: LOS ANGELES, CA: WASHINGTON, DC: TULSA, OK: TORONTO, ON WEBSITE: 877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 540.636.9445 ph. | 540.636.9414 fx. 918.437.8333 ph. | 918.437.8487 fx. 416.550.9280 WWW.QAI.ORG

Notes: Final acceptance of the product in the intended application is to be determined by the authority having jurisdiction.

Product is to be installed in accordance with the QAI Design Listing and manufacturer's published installation instructions by qualified installing personnel.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.
