



WINDOWS & DOORS LISTING PROGRAM

Customer: Stilewood International Door & Window
Class: Fenestration Products – Energy Performance
Location: Port Coquitlam, BC
Website: www.stilewood.com

Listing No. W478-2
Project No. W478-2 ED2
Effective Date: June 12, 2017
Last Revised Date: August 22, 2023
Expires: N/A

Standards: CSA A440.2 “Fenestration Energy Performance”

Product: Wood Doors

Markings: Products are marked with the following content in a permanent manner where it is readily visible after installation:

- a) Manufacturer’s name, Trademark or other recognized symbol or identification.
- b) QAI file Number: W478
- c) QAI logo shown here:



- d) “Evaluation for energy performance in accordance with CSA A440.2” / “Évalué pour la performance d’énergie en accord à la norme CSA A440.2”

Models / Ratings:

Wood Inswing Door

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	SIDW-WISHD-175FP	1.72	0.02	N/A
G02	SIDW-WISHD-225FP	1.44	0.01	N/A
G03	SIDW-WISHD-175FQL-3,SB60(2)-3,CL-10AR90TB	1.73	0.06	N/A
G04	SIDW-WISHD-175FQL-3,SB60(2)-3,ENAD(4)-10AR90TB	1.69	0.06	N/A
G05	SIDW-WISHD-225FQL-3,SB60(2)-3,CL-3,CL-11AR90TB	1.43	0.06	N/A



Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G06	SIDW-WISHD-225FQL-5,SB60(2)-5,SB60(4)-5,CL-8AR90TB	1.41	0.05	N/A
G07	SIDW-WISHD-175FHL-3,SB60(2)-3,CL-10AR90TB	1.71	0.11	N/A
G08	SIDW-WISHD-175FHL-3,SB60(2)-3,ENAD(4)-10AR90TB	1.65	0.10	N/A
G09	SIDW-WISHD-225FHL-3,SB60(2)-3,CL-3,CL-11AR90TB	1.40	0.10	N/A
G10	SIDW-WISHD-225FHL-5,SB60(2)-5,SB60(4)-5,CL-8AR90TB	1.37	0.08	N/A
G11	SIDW-WISHD-175FTL-3,SB60(2)-3,CL-10AR90TB	1.70	0.14	N/A
G12	SIDW-WISHD-175FTL-3,SB60(2)-3,ENAD(4)-10AR90TB	1.62	0.13	N/A
G13	SIDW-WISHD-225FTL-3,SB60(2)-3,CL-3,CL-11AR90TB	1.37	0.12	N/A
G14	SIDW-WISHD-225FTL-5,SB60(2)-5,SB60(4)-5,CL-8AR90TB	1.34	0.11	N/A
G15	SIDW-WISHD-175FFL-3,SB60(2)-3,CL-10AR90TB	1.69	0.18	N/A
G16	SIDW-WISHD-175FFL-3,SB60(2)-3,ENAD(4)-10AR90TB	1.57	0.17	N/A
G17	SIDW-WISHD-225FFL-3,SB60(2)-3,CL-3,CL-11AR90TB	1.35	0.16	N/A
G18	SIDW-WISHD-225FFL-5,SB60(2)-5,SB60(4)-5,CL-8AR90TB	1.30	0.14	N/A
G19	SIDW-WISHD-175RP	1.94	0.02	N/A
G20	SIDW-WISHD-225RP	1.59	0.01	N/A
G21	SIDW-WISHD-175RQL-3,SB60(2)-3,CL-10AR90TB	1.87	0.06	N/A
G22	SIDW-WISHD-175RQL-3,SB60(2)-3,ENAD(4)-10AR90TB	1.84	0.06	N/A
G23	SIDW-WISHD-225RQL-3,SB60(2)-3,CL-3,CL-11AR90TB	1.52	0.06	N/A
G24	SIDW-WISHD-225RQL-5,SB60(2)-5,SB60(4)-5,CL-8AR90TB	1.41	0.05	N/A
G25	SIDW-WISHD-175RHL-3,SB60(2)-3,CL-10AR90TB	1.81	0.11	N/A
G26	SIDW-WISHD-175RHL-3,SB60(2)-3,ENAD(4)-10AR90TB	1.74	0.10	N/A
G27	SIDW-WISHD-225RHL-3,SB60(2)-3,CL-3,CL-11AR90TB	1.45	0.10	N/A
G28	SIDW-WISHD-225RHL-5,SB60(2)-5,SB60(4)-5,CL-8AR90TB	1.37	0.08	N/A
G29	SIDW-WISHD-175RTL-3,SB60(2)-3,CL-10AR90TB	1.75	0.14	N/A
G30	SIDW-WISHD-175RTL-3,SB60(2)-3,ENAD(4)-10AR90TB	1.67	0.13	N/A
G31	SIDW-WISHD-225RTL-3,SB60(2)-3,CL-3,CL-11AR90TB	1.41	0.12	N/A
G32	SIDW-WISHD-225RTL-5,SB60(2)-5,SB60(4)-5,CL-8AR90TB	1.34	0.11	N/A
G33	SIDW-WISHD-175RFL-3,SB60(2)-3,CL-10AR90TB	1.69	0.18	N/A
G34	SIDW-WISHD-175RFL-3,SB60(2)-3,ENAD(4)-10AR90TB	1.57	0.17	N/A
G35	SIDW-WISHD-225RFL-3,SB60(2)-3,CL-3,CL-11AR90TB	1.35	0.16	N/A
G36	SIDW-WISHD-225RFL-5,SB60(2)-5,SB60(4)-5,CL-8AR90TB	1.30	0.14	N/A

Wood Outswing Door

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	SIDW-WOSHD-175FP	1.74	0.02	N/A
G02	SIDW-WOSHD-225FP	1.46	0.01	N/A
G03	SIDW-WOSHD-175FQL-3,SB60(2)-3,CL-10AR90TB	1.74	0.06	N/A
G04	SIDW-WOSHD-175FQL-3,SB60(2)-3,ENAD(4)-10AR90TB	1.71	0.06	N/A
G05	SIDW-WOSHD-225FQL-3,SB60(2)-3,CL-3,CL-11AR90TB	1.45	0.06	N/A
G06	SIDW-WOSHD-225FQL-5,SB60(2)-5,SB60(4)-5,CL-8AR90TB	1.44	0.05	N/A
G07	SIDW-WOSHD-175FHL-3,SB60(2)-3,CL-10AR90TB	1.73	0.11	N/A
G08	SIDW-WOSHD-175FHL-3,SB60(2)-3,ENAD(4)-10AR90TB	1.66	0.10	N/A
G09	SIDW-WOSHD-225FHL-3,SB60(2)-3,CL-3,CL-11AR90TB	1.42	0.10	N/A
G10	SIDW-WOSHD-225FHL-5,SB60(2)-5,SB60(4)-5,CL-8AR90TB	1.40	0.08	N/A
G11	SIDW-WOSHD-175FTL-3,SB60(2)-3,CL-10AR90TB	1.72	0.14	N/A
G12	SIDW-WOSHD-175FTL-3,SB60(2)-3,ENAD(4)-10AR90TB	1.64	0.13	N/A
G13	SIDW-WOSHD-225FTL-3,SB60(2)-3,CL-3,CL-11AR90TB	1.40	0.13	N/A
G14	SIDW-WOSHD-225FTL-5,SB60(2)-5,SB60(4)-5,CL-8AR90TB	1.36	0.11	N/A



Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G15	SIDW-WOSHD-175FFL-3,SB60(2)-3,CL-10AR90TB	1.71	0.18	N/A
G16	SIDW-WOSHD-175FFL-3,SB60(2)-3,ENAD(4)-10AR90TB	1.59	0.17	N/A
G17	SIDW-WOSHD-225FFL-3,SB60(2)-3,CL-3,CL-11AR90TB	1.37	0.16	N/A
G18	SIDW-WOSHD-225FFL-5,SB60(2)-5,SB60(4)-5,CL-8AR90TB	1.32	0.14	N/A
G19	SIDW-WOSHD-175RP	1.96	0.02	N/A
G20	SIDW-WOSHD-225RP	1.61	0.02	N/A
G21	SIDW-WOSHD-175RQL-3,SB60(2)-3,CL-10AR90TB	1.89	0.06	N/A
G22	SIDW-WOSHD-175RQL-3,SB60(2)-3,ENAD(4)-10AR90TB	1.86	0.06	N/A
G23	SIDW-WOSHD-225RQL-3,SB60(2)-3,CL-3,CL-11AR90TB	1.54	0.06	N/A
G24	SIDW-WOSHD-225RQL-5,SB60(2)-5,SB60(4)-5,CL-8AR90TB	1.53	0.05	N/A
G25	SIDW-WOSHD-175RHL-3,SB60(2)-3,CL-10AR90TB	1.82	0.11	N/A
G26	SIDW-WOSHD-175RHL-3,SB60(2)-3,ENAD(4)-10AR90TB	1.75	0.10	N/A
G27	SIDW-WOSHD-225RHL-3,SB60(2)-3,CL-3,CL-11AR90TB	1.48	0.10	N/A
G28	SIDW-WOSHD-225RHL-5,SB60(2)-5,SB60(4)-5,CL-8AR90TB	1.45	0.09	N/A
G29	SIDW-WOSHD-175RTL-3,SB60(2)-3,CL-10AR90TB	1.77	0.14	N/A
G30	SIDW-WOSHD-175RTL-3,SB60(2)-3,ENAD(4)-10AR90TB	1.69	0.13	N/A
G31	SIDW-WOSHD-225RTL-3,SB60(2)-3,CL-3,CL-11AR90TB	1.43	0.13	N/A
G32	SIDW-WOSHD-225RTL-5,SB60(2)-5,SB60(4)-5,CL-8AR90TB	1.40	0.11	N/A
G33	SIDW-WOSHD-175RFL-3,SB60(2)-3,CL-10AR90TB	1.71	0.18	N/A
G34	SIDW-WOSHD-175RFL-3,SB60(2)-3,ENAD(4)-10AR90TB	1.59	0.17	N/A
G35	SIDW-WOSHD-225RFL-3,SB60(2)-3,CL-3,CL-11AR90TB	1.37	0.16	N/A
G36	SIDW-WOSHD-225RFL-5,SB60(2)-5,SB60(4)-5,CL-8AR90TB	1.32	0.14	N/A

Wood Eclipse Folding Door

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	SIDW-WEFD-3,SB60(2)-3,CL-10AR90TB	1.69	N/A	N/A
G02	SIDW-WEFD-3,SB60(2)-3,ENAD(4)-10AR90TB	1.56	N/A	N/A
G03	SIDW-WEFD-3,SB60(2)-3,CL-3,CL-11AR90TB	1.36	N/A	N/A
G04	SIDW-WEFD-5,SB60(2)-5,SB60(4)-5,CL-8AR90TB	1.30	N/A	N/A
G05	SIDW-WEFD-6,SB60L(2)-3,CL-6,CLLM-8AR90TB	1.44	N/A	N/A

Aluminum Clad Wood Eclipse Folding Door *

* **Note:** Aluminum Clad Wood Eclipse Folding Door was thermally modeled to the job-specific height of 2613 mm. Thermal performance values apply only to the product of the same height as thermally modeled.

Glass / Grille Option #	Model Code	U-Factor (W/m ² K)	Product SHGC	Energy Rating
G01	SIDW-AWEFD-4,7138(2)-4,CL-11AR90XL	1.68	0.25	N/A
G02	SIDW-AWEFD-4,366(2)-4,CL-11AR90XL	1.66	0.18	N/A
G03	SIDW-AWEFD-3,272(2)-3,CL-3,272(5)-8AR90XL	1.36	0.23	N/A



Notes:

- Products are not intended for installation in storefronts, non-operable portions of curtain wall, fixed glazing cast into precast concrete panels, greenhouses, skylights or sloped glazing.
- Test procedures are designed to test the performance of the test specimen only and are not necessarily used to test the performance of the installation, particularly the perimeter sealant joint and anchoring of the assembly.
- The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI.
- No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing.
- Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.