



BUILDING PRODUCT LISTING PROGRAM

Customer: Star Lumber Canada Ltd.
Class: Wood Shakes and Shingles
Location: Mission, BC Canada
Website: www.starlumber.ca

Listing No. B1149

Effective Date: October 25, 2023
Last Revised Date: October 25, 2023
Expires: N/A

Standards: CSSB – 97 *Grading and Packing Rules for Western Red Cedar Shakes and Western Red Cedar Shingles of the Cedar Shake and Shingle Bureau.*
UL 2218 *Impact Resistance of Prepared Roof Covering Materials.*

Product: Western Red Cedar roof coverings by Star Lumber Canada™, Green River™, Black Hawk™, and Goldband of the following types:

- Handsplit and Resawn Shakes.
- Tapersawn Shakes.
- Cedar Shingles.

Markings: Products are labeled per bundle with the following information:
a) Company name and location.
b) Product type.
c) CSSB 97 Grade
d) UL 2218 Impact Resistance Class
e) QAI Listing File Number
f) QAI logo shown here:





Models: Star Lumber Canada Cedar products are available in the following product types per CSSB – 97 Grade:

TYPE	PRODUCT	MINIMUM THICKNESS	WIDTH	LENGTHS	EXPOSURE	GRADE
Shake	Handsplit Resawn	½ inch (13 mm) ¾ inch (19 mm) 1-1/4 inch (31 mm) 1-1/2 inch (38 mm)	4 inches (102 mm) to 14 inches (356 mm)	24 inch (610 mm) 18 inch (457 mm)	10 inch (254) 7.5 inch (191 mm)	Premium / Grade #1
	Tapersawn	5/8-inch (16 mm) ¾ inch (19 mm) 7/8-inch (22 mm) 1-inch (25 mm)		24 inch (610 mm) 18 inch (457 mm)	10 inch (254) 7.5 inch (191 mm)	Premium / Grade #1
Shingles	Royal	½-inch (13 mm)		24 inch (610 mm)	7.5 inch (191 mm)	Grade #1 / Grade #2
	Perfection	0.45-inch (11.5 mm)		18 inch (457 mm)	5.5-inch (140 mm)	Grade #1 / Grade #2
	16-inch	0.40 (10 mm)		16 inch (406 mm)	5-inch (127 mm)	Grade #1 / Grade #2

Ratings: Star Lumber Canada Cedar products have the following impact resistance classification when evaluated per UL 2218:

Substrate	Approved Underlayment	Approved Roof Covering	Minimum Thickness	Hail-Impact Classification ¹
Minimum 15/32-inch-thick plywood	Unrestricted	Handsplit Resawn Shake	≥ ½-inch (13 mm)	Class IV
		Tapersawn Shake	≥ 5/8-inch (16 mm)	
		Royal Shingle	≥ ½-inch (13 mm)	
		Perfection Shingle	≥ 0.45-inches (11.5 mm)	

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@qai.org. Please include the listing number in the request.
