

VANCOUVER, BC: LOS ANGELES, CA: TORONTO, ON: TULSA, OK: MIAMI. FL: WEBSITE:

877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 905.605.5444 ph. 918.437.8333 ph. | 918.437.8487 fx. 305.885.3328 ph. | 305.885.3329 fx. WWW.QAI.ORG

FIRE DOOR LISTING PROGRAM

Customer: Dimension Plywood Inc.

Class: Fire Resistance Rated Doors and Frames

Location: New Albany, Indiana

Website: http://dimensionplywood.com/

Listing No. F488

Projects No. F488 Edition 1

Effective Date: November 1, 2023 Last Revised Date: November 1, 2023

Expires: N/A

Standards: UL 10B Fire Tests of Door Assemblies

> **UL 10C** Positive Pressure Fire Tests of Door Assemblies NFPA 252 Standard Methods of Fire Tests of Door Assemblies Standard Method for Fire Tests of Door Assemblies CAN/ULC S104

Product: 20-to-90-minute Neutral & Positive Pressure Rated Category "A" Wood and

Composite Fire Doors and Category "C" Fire Door Frames with and without Hose

Stream.

See FD001 - Fire Door Labeling requirements Markings:

Fire Resistance Rated Doors Models / Ratings:

Spec. Owner	Fire Rating	Category	Listing #	Description
Wolman	20 minutes	Α	F411-1-1-20	Wood / Composite Core
Wolman	45 minutes	Α	F411-1-1-45	Composite Core
Wolman	60 minutes	А	F411-1-1-60	Composite Core
Wolman	90 minutes	А	F411-1-1-90	Composite Core

Fire Resistance Rated Door Frames

Spec Owner	Fire Rating	Category	Listing #	Description
Wolman	20 minutes	С	F411-2-20	Composite Frame
Wolman	45 minutes	С	F411-2-45	Composite Frame
Wolman	60 minutes	С	F411-2-60	Composite Frame
Wolman	90 minutes	С	F411-2-90	Composite Frame

Notes:

- Refer to QAI evaluation reports F489 and the applicable test reports for test assembly configurations used for fire endurance testing.
- Refer to the QAI FD002 Fire Door Guidelines for general guidelines of fire door assemblies
- Final acceptance of the product in the intended application is to be determined by the authority having jurisdiction (AHJ).



VANCOUVER, BC: LOS ANGELES, CA: TORONTO, ON: TULSA, OK: MIAMI. FL: WEBSITE:

877.461.8378 ph. | 604.527.8368 fx. 909.483.0250 ph. | 909.483.0336 fx. 905.605.5444 ph. 918.437.8333 ph. | 918.437.8487 fx. 305.885.3328 ph. | 305.885.3329 fx. WWW.QAI.ORG

 Product is to be installed in accordance with the manufacturer's published installation instructions by qualified installing personnel.

The materials, products or systems listed herein have been qualified to bear the QAI Listing Mark under the conditions stated with each Listing. Only those products bearing the QAI Listing Mark are considered to be listed by QAI. No warranty is expressed or implied, and no guarantee is provided that any jurisdictional authority will accept the Listing found herein. The appropriate authorities should be contacted regarding the acceptability of any given Listing. Visit the QAI Online Listing Directory located at www.qai.org for the most up to date version of this Listing and to validate that this QAI Listing is active. Questions regarding this listing may be directed to info@gai.org. Please include the listing number in the request.
